Entered in NID File	Checked by Chief . + WB. Approval Letter = 12-15-73 Disapproval Letter
Date Well Completed 6.10:13 OW WW TA GW OS PA	Location Inspected Bond released State or Fee Land
LOGS FI	ILED
Driller's Log	Mi-L Sonic


FILE NOTATIONS

SUBMIT IN T. .. LICATE* (Other instructions on reverse side)

STATE OF UTAH DEPARTMENT OF NATURAL RESOURCES DIVISION OF OIL & GAS

	DIVISION OF	OIL & GAS		•	o. Bease Designation and	a Seriai No.
4 5 5 1 6 4 7 1 6 4 1					Patented If Indian, Allottee or	Triba Numa
	FOR PERMIT TO	D DRILL, DEEP	EN, OR PLUG	BACK	. It indian, Another of	Time Ivame
1a. Type of Work	L 🔀	DEEPEN	DILIC D	ACK [] 7	. Unit Agreement Name	
b. Type of Well	. . 🖸	DEELEIJ [PLUG B	ACK [
Oil X Ga	s Other		Single X Mu Zone Zo		. Farm or Lease Name	
2. Name of Operator She	ll Oil Company (I	Rocky Mtn Div		ne	Doyle	
Chev	vron Oil and Gul:	f Oil Corporat	ion	9	. Well No.	
3. Address of Operator					1-10B3	
1700	O Broadway, Denve	er, Colorado 8	0202	1	0. Field and Pool, or W	ildest
4. Location of Well (Repo At surface	rt location clearly and in ac				Altamont &	<u> </u>
	2382' FNL and 21	rad, tar sec i	.0	1	and Survey or Area	
At proposed prod, zone					SE/4 NW/4 Se	ection 10-
14. Distance in miles and	direction from nearest town	or post office*			T 2S-R 3W 2. County or Parrish	13. State
5 miles SE	of Altamont				Duchesne	Utah
15. Distance from propose	d* 2157' from sec	line 16. N	lo. of acres in lease		acres assigned	
location to nearest property or lease line, (Also to nearest drlg. I	ft. 483! from proj	perty &	161	to this v	vell 640	
18. Distance from proposed	d location*	1e	roposed depth	20. Rotary o	or cable tools	*
or applied for, on this	g, completed, No other lease, ft. on lease		13,300		Total	
21. Elevations (Show wheth			<u> </u>		22, Approx, date work	will start*
	6	6033 GL (Ungra	.ded)		Soon	
23.			D CEMENTING PROGRA	A.M		
Size of Hole	Size of Casing	Weight per Foot	Setting Depth		Quantity of Cement	
17½"	13 3/8"	Weight ber 2000	300 !		Circ to sfc	
121."	9 5/8"		62001		Cmt lower 15	5001
					Sqz 13 3/8"	
					annulus	/ // -
8 3/4"	7"		10,900'		Cmt lower 15	500 t
6 1/8"	5" liner		10,700-13,30	0 1	Circ entire	liner
						4
					1.	/ -
					13101	7
	As ner :	sttached conti	fied survey pl	o+ and	, i i	
	-		n Monitoring Eq		AB'	
		ip, and Mud	1 11011110111116 119	arpinom,	Section 1	ner."
	101 1300	. p, a				
					4	
Verbal appro	val to drill obta	ained from Pau	ıl Burchell by	our Mr.	C. Van Kirk l	2-8-72.
N ABOVE SPACE DESCI luctive zone. If proposal i	KIBE PROPOSED PROGRAI is to drill or deepen direction	M: If proposal is to de	epen or plug back, give	lata on present	productive zone and pr	oposed new pro-
revencer program, if any.		and, give perment (at	a on subsurface locations	and measured	and true vertical depth	s. Give blowout
4.	< P)				
Signed	X Walley	Title Div	ision Operatio	ns Engr.	Date Dec.	12. 1972
(This space for Federal	r State office use)				Date	
	13 - 4 6 1.10	- 				
Permit No	12 12 12 1 At 1 1 A	<i>f</i>	Approval Date			
Approved by Conditions of approval,	if any:	Title			Date	
	v :					

T2S, R3W, U.S.B. & M.



X = Corners found & used.

PROJECT

SHELL OIL COMPANY

Well location, I-10B3, located as shown in the SE I/4 NW I/4 Section 10, T2S, R3W, U.S.B. & M., Duchesne County, Utah.



CERTIFICATE

THIS IS TO CERTIFY THAT THE ABOVE PLAT WAS PREPARED FROM FIELD NOTES OF ACTUAL SURVEYS MADE BY ME OR UNDER MY SUPERVISION AND THAT THE SAME ARE TRUE AND CORRECT TO THE BEST OF MY KNOWLEDGE AND BELIEF.

REGISTERED LAND SURVEYOR REGISTRATION № 3154

STATE OF UTAH

UINTAH ENGINEERING & LAND SURVEYING
POBOX Q - 110 EAST - FIRST SOUTH
VERNAL, UTAH - 84078

SCALE	DATE
l" = 1000'	23 Oct. 1972
PARTY	REFERENCES
G.S. & H.M.	G.L.O. Plat
WEATHER	FILE
Cool	Shell Oil Company

Mud System Monitoring Equipment

Equipment will be installed (with derrick floor indicators) and used throughout the period of drilling after setting and cementing intermediate string or upon reaching a depth at which abnormal pressures could occur.

BOP Equipment

300-6,200' - Bag Type
6,200'-TD - 3-ram type BOP's and 1 bag type
5,000# working pressure

Tested when installed. Operative every trip and tested to 5,000 psi every 14 days. All information recorded on Tour sheets and daily drilling wire.

Mud

Surface - 9,600' - Clear water
Circulate reserve pit
Flocculate as necessary

9,600'-13,300' - Weighted gel chemical

December 15, 1972

Shell Oil Company 1700 Broadway Denver, Colorado

> Re: Shell et al Doyle #1-1083 Sec. 10, T. 2 S, R. 3 W, USM Duchesne County, Utah

Gentlemen:

Insofar as this office is concerned, approval to drill the above referred to well is hereby granted in accordance with the Order issued in Cause No. 131-14, dated August 11, 1971.

Should you determine that it will be necessary to plug and abandon this well, you are hereby requested to immediately notify the following:

PAUL W. BURCHELL - Chief Petroleum Engineer HOME: 277-2890 OFFICE: 328-5771

This approval terminates within 90 days if the well is not spudded-in within said period; however, the termination period may be extended upon written request of the operator and subsequent approval of this Division.

Enclosed please find Form OGC-8-X, which is to be completed whether or not water sands (aquifers) are encountered during drilling.

The API number assigned to this well is 43-013-30187.

Very truly yours,

DIVISION OF OIL & GAS CONSERVATION

CLEON B. FEIGHT DIRECTOR Form OGCC-3

SUBMIT IN DUPLICATE*

10

STATE OF UTAH

(See other instructions on reverse side)

1. 6 Pi	OIL & G	AS C	ONSER	VATION	COM	MISSIOI	V	reverse				TION AND SERIAL N
										Patent		TTEE OR TRIBE NAM
WELL CO	OMPLETIO	N OF	RECO	MPLET	ION I	REPORT	AN	D LOG	*	•• •••	,	
1a. TYPE OF W		IL X	GAS WELL		RY	Other			7.	UNIT AGR	EEMEN	T NAME
b. TYPE OF CO												
WELL X		EEP-	PLUG BACK			Other				FARM OR	LEASE	NAME
2. NAME OF OPER	MATORShell O	il Co	mpany	(Rocky	Mount	tain Div	• Pr	oductio		Doyle		
	Chevron	Oil	and Gu	lf Oil	Corp.	•			9.	WELL NO.	,	
3. ADDRESS OF O	PERATOR									1-10H		
4. LOCATION OF W	1700 Br	oadwa	y, Den	ver, Co	olorac	lo 80202						L, OR WILDCAT
4. LOCATION OF W							remen	ts) *	-	Altan		
	2382' F		nd 2157	' FWL S	Sec 10)			1	OR AREA	, ,	OR BLOCK AND SURVE
At top prod. i	nterval reported	below										Section 10-
At total depth	ı									T 2S-F	3W	
				14. PE	RMIT NO	1/17	DATE	ISSUED	12	. COUNTY	OR	13. STATE
				43-0)13-3(101	12	2-14-72		Duches Duches	sne	Utah
15. DATE SPUDDED	16. DATE T.D.	REACHE	D 17. DA					VATIONS (DF,			19.	ELEV. CASINGHEAD
12-18-72	2-8-	73		6-10	73		6033	GL, 60	48 KB			251
20. TOTAL DEPTH, M	ľ	LUG, BAC	K T.D., MD &	TVD 22.	IF MUL	TIPLE COMPL.		23. INTERV	ALS R	OTARY TOO	LS .	CABLE TOOLS
13,19	5	1	.3 , 125						<u> </u>	Total		
24. PRODUCING INT	ERVAL(S), OF TH	IS COMP	LETION-TO	Р, ВОТТОМ,	NAME (N	MD AND TVD)*	'			1.	25	SURVEY MADE
Green Ri	ver, Wasat	ch. a	nd Fla	gstaff	perfs	s 10.76/.	- 13.	104			İ	No
26. TYPE ELECTRIC											97 10	AS WELL CORED
	DIL, FDC-C		CRT	CR ar	a uni						21. W	
28.	110-0	INITY CITY				ort all string	e act is	n angll)				No
CASING SIZE	WEIGHT, LI	B./FT.		ET (MD)		LE SIZE	1		TING REC	ORD		AMOUNT PULLED
13 3/8"	68#			3061	7	-7불"		27	5 sx			0
9 5/8"	40#			200'		2 ¹ / ₄ 11			0 sx	····		0
7"	26 &			754'		8 3/4"	ļ —		O CF			0
29.		LINE	R RECORI) 				30.	TUB	ING RECO	ORD	
SIZE	TOP (MD)		OM (MD)	SACKS CE		SCREEN (M	D)	SIZE	DEPT	H SET (M	D)	PACKER SET (MD)
5"	10,577	<u> 13</u>	195	520	<u> </u>				_ -			
31. PERFORATION R	ECORD (Interval.	size and	number)	<u> </u>								
			, ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,			32.		ID, SHOT, F				
						DEPTH INT	ERVAL	(MD)	AMOUN	r AND KIN	D OF M	IATERIAL USED
					As ne	r attacl	men	nt.s				
					PC	4 00000	111101.					· · · · · · · · · · · · · · · · · · ·
33.*						UCTION		· · · · · · · · · · · · · · · · · · ·				
DATE FIRST PRODUC	PRO PRO	DUCTION	METHOD (mping—size	and ty	(pe of pump)			STATUS t-in)	(Producing or
6-10-73	HOURS TESTE		HOKE SIZE		'lowin							Producing
6-27-73	24	, .	14/64	PROD'N TEST F		01L—86L. 614		GAS—MCF.	w	ATER—BBL	.	GAS-OIL RATIO
FLOW. TUBING PRESS.		URE C	ALCULATED	OIL-B		GAS—		710		15		1156
1750	0		4-HOUR RAT	CE 1	14	GAS—	710		TER—BBL 15	.		45.1°
34. DISPOSITION OF	1	or fuel, r	ented, etc.			<u> </u>	1 +0			ST WITNES		
Used for	fuel on la	se, s	ome so	ld to M	tn Fu	el, and	som	e flare				
35. LIST OF ATTAC	HMENTS		7									
Well Log	and Histor	<u>су</u> , С	sg a n d	Cmtg D	etail	.S						
36. I hereby certif	y that the forego	ing and	attached i	nformation	is compl	ete and corre	ct as	determined f	rom all a	vailable re	cords	
SIGNED L	W De	lev				vision (20 72
Promen -	- / I/			TIT	LE TT	ATDIOIT C	, her	a o T O II 2 I	nr81.•	DATE	TO	-30 -7 3

Shell-Gulf-Doyle 1-10B3 (D) 13,195' Wasatch Test 5" liner @ 13,195' TD 13,195. PB 13,125. Flowing. On 24-hr test, flwd 452 BO, 9 BW and 625 MCF gas on 10/64" chk w/2200 psi FTP and zero CP. JUN 21 1373

Shell-Gulf-Doyle 1-10B3 (D) 13,195' Wasatch Test 5" liner @ 13,195'

TD 13,195. PB 13,125. Flowing. On 24-hr test, well flwd 459 BO, 9 BW and 643 MCF gas on 10/64" chk w/2200 psi FTP and zero CP. JUN 22 1373

Shell-Gulf-Doyle 1-10B3 (D) 13,195' Wasatch Test 5" liner @ 13,195' TD 13,195. PB 13,125. Flowing. On 24-hr tests, flwd JUN 25 1973 as follows: Report CP FTP MCF Gas Chk BWDate ΒO 0. 10/64" 2100 491 443 11 6/23 . 0 10/64" 2000 440 9 388 6/24 10/64" 1900 0 411 11 6/25 376

Shell-Guir-Doyle 1-10B3 (D) 13,195' Wasatch Test 5" liner @ 13,195' TD 13,195. PB 13,125. Flowing. On 24-hr test, flwd 598 BO, no wtr and 680 MCF gas on 15/64" chk w/1450 psi FTP and zero CP. JUN 2 6 1973

Shell-Gulf-Doyle 1-10B3 (D)
13,195' Wasatch Test
5" liner @ 13,195'
Shell-Gulf-Doyle 1-10B3 (D)
13,195' Wasatch Test
5" liner @ 13,195'

TD 13,195. PB 13,125. Flowing. On 24-hr test, flwd 569 BO, no wtr and 634 MCF gas on 15/64" chk w/1200 psi FTP and zero CP. 30, 2 7 1973

TD 13,195. PB 13,125. Flowing. OIL WELL COMPLETE. On 24-hr test 6/27/73, flowed 614 BO, 15 BW and 710 MCF gas on 15/64" chk w/1750 psi FTP and zero CP from Green River, Wasatch and Flagstaff perfs 10,764, 10,792, 10,801, 10,809, 10,815, 10,824, 10,831, 10,865, 10,926, 10,940, 10,974, 10,990, 11,055, 11,065, 11,088, 11,203, 11,367, 11,393, 11,439, 11,499, 11,528, 11,553, 11,625, 11,633, 11,656, 11,727, 11,760, 11,806, 11,852, 11,859, 11,879, 11,886, 11,902, 11,912, 11,939, 11,962, 11,996, 12,005, 12,022, 12,054, 12,067, 12,174, 12,233, 12,255, 12,258, 12,299, 12,301, 12,386, 12,424, 12,428, 12,475, 12,484, 12,504, 12,562, 12,616, 12,654, 12,658, 12,660, 12,732, 12,761, 12,910, 12,942, 12,972, 13,021, 13,051, and 13,104. Oil Gravity: 45.1° API @ 60°F. Compl Test Date; 6/27/73. Initial Prod Date: 6/10/73. Elev: 6033 GL, 6048 KB. 9,185 (-3137) Log Tops: TGRa

UPPER WASATCH TRANSITION 10,920 (-4872) FLAGSTAFF 11,150 (-5102)

This well was drilled for routine development. FINAL REPORT. JUN 2 8 1973

FIELD	ALTA	MONT	WELL	Doyle 1	L-10B3	KB TO CH	F <u>25'</u>	
			Shoe jt s	tarted in	hole 7:30 A	ıM	12-20-72	
			•		ST&C 13 3/8	•		
			•					
JTS	<u>WT</u>	GRADE	ST&C	NEW	FEET	FROM	TO	
8	68#	K-55	X	X	313	KB	306	
	(Total)							
				Howco	Insert Fill	L Collar at	246	
				Howco	Plain Guide	e Shoe at _	306	

No., Make and Type

No centralizers

Cementing

Broke circ 11:30 AM w/300 psi. Reciprocated and circ 20 min. With 40 bbls water ahead, cemented through shoe at 306' w/275 sx BJ Class "G" cem, 2% CaCl2 blended w/110# Diamix. Bumped plug w/500 psi, float held ok. CIP 11:15 AM 12-20-72. Had 100% returns but fell away 10'. Grouted w/ready mix. Press to 1500 psi in 1 min. Bled back 1 bbl.

FIELD	ALTAMO	NT_		ÆLL	1	OOYLI	E 1-10	DB3	KB T	O CHF_	25'	·
			Sho	e jt	sta	rted	in h	ole at	9:30	AM	1-2-73	3
			Ran	153	jts	40#	K-55	ST&C	& LT&C	9 5/8"	csg to	62001
JTS	<u>WT</u>	GRADE	ļ		T&C T&C		<u>NEW</u>		FEET	FRO	<u>M</u>	<u>TO</u>
60	40#	K-55		S	T&C		X		2459	. (0 2	2459
93	40#	K-55		L	T&C		X		3741	245	9 6	5200
153 jts	(Total)											
								Howc	o Fillu	p Colla	r at	6118
								Howc	o Guide	Shoe a	t	6200

No., Make and Type

2 centralizers spaced at 6195 and 6115.

Cementing

Broke circ at 6 PM w/l,000 psi. Reciprocated and circ. Washed to bottom. With 5 bbls water ahead, cemented through shoe at 6200' w/625 cu ft B-J LNE followed by 235 cu ft Class "G" w/1% R-5. Lost circ w/290 bbls displaced. Bumped plug w/464 bbls wtr w/1500 psi, fload held ok. CIP 9 PM 1-2-73. Bled back $l\frac{1}{2}$ bbls.

FIELD _	ALTA	MONT	WEIL DOYLE	1-10B3	KB TO CF	IF <u>2</u>	51
		5	Shoe jt starte	d in hol	e 3 AM	1	-20-73
]	Ran 255 jts 26	# CF-95	LT&C 7" csg	g to <u> </u>	0,740'
<u>JTS</u>	<u>WT</u>	GRADE	<u>LT&C</u>	NEW	FEET	FROM	TO
213	26#	CF-95	X	X	8974	0	8974
42	29#	CF-95	X	X	1779	8974	10,740
255 jts	(10,758)) Total					
				77 7	77 4 . T72 7 7	- 0-11	a+ 10 611
•				Howco i	float fillu	b corrar	at <u>10,611</u>
				Howco I	Float Shoe	at	10,740

No., Make and Type

3 centralizers spaced at 10,750, 10,670, and 10,590

Cementing

Broke circ at 12 PM w/650 psi. Reciprocated and circ 5 min. With 5 bbls wtr ahead, cemented through shoe at 10,740' w/420 cu ft BJ lightwt and 200 sx cu ft Class "G". Displaced w/420 bbls mud w/100% returns. Wt - 12.4-15.9#/gal. Mixing complete in 25 min. Press - Max 1500. Plug down 2 PM 1-21-73 w/1800 psi, float held. Bled back $l\frac{1}{2}$ bbls.

OIL WELL LEASE SHELL-GULF-DIVISION ROCKY MOUNTAIN ELEV 6043 KB FROM: 12-19-72 - 6-28-73 COUNTY DUCHESNE STATE

HATU

ALTAMONT :

Shell-Gulf-Doyle 1-10B3 (D) Brinkerhoff #54 13,300' Wasatch Test "FR" 223/71/1/223. Drilling.

Located 2382' FNL and 2157' FWL, Section 10-T2S-R3W,

Duchesne County, Utah.

Elev: 6033 GL (ungraded)

13,300' Wasatch Test

DEC 1 9 1972

Shell Working Interest: 93.75% Drilling Contractor: Brinkerhoff

This is a routine Wasatch development well.

Dev: 3/4° @ 130': Spudded well @ 6:30 PM, 12/13/72.

Mud: Wtr

Shell-Gulf-Doyle 1-10B3 (D) Brinkerhoff #54 13,300' Wasatch Test 325/71/2/102. Running 13-3/8" csg. Dev: 1° @ 325'.

Reamed hole for 11-3/4 hrs. DEC 2 0 1072

Mud: Wtr

Shell-Gulf-Doyle 1-10B3 (D) Brinkerhoff #54 13,300' Wasatch Test 13-3/8" csg @ 306'

325/71/3/0. Drilling cmt and baffle. Ran 8 jts (306') 13-3/8" 68# K55 csg w/Howco guide shoe @ 306' and insert fill collar @ 246'. B-J cmtd w/275 sx Class "G" treated w/ 2% CaCl₂ blended w/110# Diamix. Bumped plug w/500 psi, float held OK. CIP @ 11:15 AM, 12/20/72. Had 100% returns but fell away 10'. Grouted w/ready mix. Nippled up BOP's and tested to 1500 psi for 15 min, OK. Mud: Wtr 56621 1972

Shell-Gulf-Doyle 1-1083 (D) Brinkerhoff #54 13,300' Wasatch Test 13-3/8" csg € 306'

1047/71/4/722. Drilling. With top of cmt @ 224', Do cmt for 34 hrs. Dev: 10 @ 600', 1/20 @ 1000'.080 2 ; 7/2 Mud: Wtr

Shell-Gulf-Doyle 1-1033 (D) Brinkerhoff #54 13,300' Wasatch Test 13-3/8" csg @ 306'

12/23: 1850/71/5/803. Drilling. Dev: 3/4° @ 1310.

Mud: Wtr

12/24: 2585/71/6/735. Tripping for new bit. Dev:

10 @ 1960 and 2585.

Mud: Wtr

12/25: 3245/71/7/660. Drilling. Dev: 1/2° @ 3025.

Mud: Wtr

12/26: 3750/71/8/505. Drilling. Dev: 1/20@ 3464.

Tripped for new bit @ 3464'. DEG 2 & 1372

Mud: Wtr

Shell- Gulf-Doyle 1-10B3 (D) Brinkerhoff #54 13,300' Wasatch Test 13-3/8" csg @ 306'

3865/71/9/115. Repairing engine clutch. Magnafluxed DC's and changed BHA.

Shell- Gulf-Doyle 1-10B3 (D) Brinkerhoff #54 13,300' Wasatch Test 13-3/8" csg @ 306'

4194/71/10/329. Drilling. Repaired engine clutch and tripped in hole w/new bit. Washed to btm - had 300' fill. 050 25 1972 Mud: Wtr

Shell- Gulf-Doyle 1-10B3 (D) Brinkerhoff #54 13,300' Wasatch Test 13-3/8" csg @ 306' 4745/71/11/551. Drilling. 050 20 1893

Shell-Gulf-Doyle 1-10B3 (D) Brinkerhoff \$54 13,300' Wasatch Test 13-3/8" csg @ 306'

12/30: 5250/71/12/505. Drilling.
12/31: 5626/71/13/376. Tripping for bit. Dev: 1/4°
@ 5626.

1/1: 5950/71/14/324. Drilling. Tripped in w/new bit, washing 400' to btm.
1/2: 6200/71/15/250. Laying down 9" DC's. Circ and sptd 800 bbls gel and wtr. Pulled bit.
Mud: Wtr

Shell-Gulf-Doyle 1-10B3 (D) Brinkerhoff #54 13,300' Wasatch Test 9-5/8" csg @ 6200'

6200/71/16/0. Nippling up. Dev: 1° @ 6200'. RU and ran 153 jts (6192') 9-5/8" K-55 ST&C and LT&C csg, washing 80' to btm. Howco guide shoe @ 6200 and fillup collar @ 6118. Cmtd w/625 cu ft B-J LNE followed by 235 cu ft Class "G" w/1% R-5. Lost circ w/290 bbls displaced. Bumped plug w/464 bbls wtr w/1500 psi, float held OK. CIP @ 9 PM, 1/2/73. 38% 3

Shell-Culf-Doyle 1-10B3 (D) Brinkerhoff #54 13,300' Wasatch Test 9-5/8" csg @ 6200'

6200/71/17/0. Nippling up. 3A8 4 1973

Shell-Gulf-Doyle 1-10B3 (D) Brinkerhoff #54 13,300' Wasatch Test 9-5/8" csg @ 6200'

6300/71/18/100. Drilling. Nippled up and tested BOP's. DO cmt and FC @ 6118. Tested csg to 1500 psi for 15 min, OK. B-J pmpd 300 sx Class "G" between 13-3/8" and 9-5/8" - fell away. 184 5 1973
Mud: Wtr

Shell-Gulf-Doyle 1-10B3 (D) Brinkerhoff #54 13,300' Wasatch Test 9-5/8" csg @ 6200'

1/6: 6840/71/19/540. Drilling.

Mud: Wtr

1/7: 7366/71/20/526. Tripping for bit.

Mud: Wtr

1/8: 7730/71/21/364. Drilling. Dev: 3° @ 7366'.

Mud: Wtr

Shell-Gulf-Doyle 1-10B3 (D) Brinkerhoff #54 13,300' Wasatch Test 9-5/8" csg @ 6200' 8052/71/22/322 . Tripping for new bit. Dev: 20 0 8050. Mud: Wtr $_{\rm MAS}$ = 2070

Shell-Gulf-Doyle 1-10B3 (D) Brinkerhoff #54 13,300' Wasatch Test 9-5/8" csg @ 6200'

8595/71/23/543. Drilling.
Mud: Wtr JAN 10 1973

Shell-Gulf-Doyle 1-10B3 (D) Brinkerhoff #54 13,300' Wasatch Test 9-5/8" csg @ 6200'

8963/71/24/368. Tripping for new bit. Dev: 2-3/4° @ 8960.
Mud: Wtr 44/314 444

Shell-Gulf-Doyle 1-10B3 (D) Brinkerhoff #54 13,300' Wasatch Test 9-5/8" csg @ 6200'

9440/71/25/477. Drilling. Washed and reamed to btm. Mud: Wtr $340.19\,1972$

Shell-Gulf-Doyle 1-1083 (D) Brinkerhoff #54 13,300' Wasatch Test 9-5/8" csg @ 6200' 1/13: 9923/71/26/483. Tripping for new bit.
1/14: 10,253/71/27/330. Drilling. Dev: 2½0 @ 9923.

Mud: Wtr
1/15: 10,495/71/28/242. Drilling. Mudded up. Lost
110 bbls mud @ 10,430. Connection gas @ 10,450: 3000
units.

Mud: 11 x 41 x 8 (3% oil) MAX 15 MAX

Shell-Gulf-Doyle 1-10B3 (D) Brinkerhoff #54 13,300' Wasatch Test 9-5/8" csg @ 6200' 10,628/71/29/133. On btm, prep to drill ahead. Lost 50 bbls mud last 24 hrs. $\frac{30.013}{10.000}$ Mud: (gradient .610) 11.7 x 43 x 8 (2#/bbl LCM) (2% oil)

Shell-Gulf-Doyle 1-10B3 (D) Brinkerhoff #54 13,300' Wasatch Test 9-5/8" csg @ 6200'

10,742/71/30/114. Drilling. Built mud wt to 12.1-12.3 ppg. Lost 100% returns, losing 400 bbls mud last 24 hrs. Mud presently 11.9 ppg w/no mud loss. Mud: 11.9 x 44 x 8.4 (3#/bbl LCM) (2% oil) 320 17 333

Shell-Gulf-Doyle 1-10B3 (D) Brinkerhoff #54 13,300' Wasatch Test 9-5/8" csg @ 6200'

10,779/71/31/37. Pulling out to log. Lost 200 bbls mud last 24 hrs. Background gas: 180 units. Short trip gas: 400 units. Mud: 11.9 x 44 x 7 (2#/bbl LCM) (2% oil) $\frac{11.9 \times 14}{11.9 \times 14}$

Shell-Gulf-Doyle 1-10B3 (D) Brinkerhoff #54 13,300' Wasatch Test 9-5/8" csg @ 6200' 10,779/71/32/0. Tripping in hole. Ran logs as follows: DIL and FDC-CNL-GR from 10,764-6200 and BHCS-GR from 10,764-300. Schl lost 7" x 9-5/8" swage off lubricator while logging. Hit swage w/bit - jammed into wear bushing. Dev: $1\frac{1}{4}$ ° @ 10,779 Mud: 11.9 x 44 x 7 ($2\frac{\pi}{6}$)bbl LCM) ($2\frac{\pi}{6}$ oil)

Shell-Gulf-Doyle 1-10B3 (D) Brickerhoff #54 13,300' Wasatch Test 7" @ 10,754'

1/20: 10,779/71/33/0. Running 7" csg. Circ btms up. Laid down 5" DP and DC's. Background gas: 40 units. Btms up gas: 400 units.

Mud: 11.9 x 44 x 7 (2#/bbl LCM) (2% oil)

1/21: 10,779/71/34/0. Nippling up 7". Ran 255 jts (10,758') 7" 26 and 29# CF-95 csg w/Howco shoe @ 10,754 and float @ 10,625. B-J cmtd w/5 BV ahead followed by 420 cu ft B-J lightwt and 200 cu ft Class "G". Displaced w/420 bbls mud w/100% returns. CIP @ 2 AM, 1/21/73. Bumped plug w/1800 psi, float held.

Mud: 11.9 x 44 x 7 (2#/bbl LCM) (2% oil)

1/22: 10,779/71/35/0. Testing BOP's. JAN 23 1813

Mud: 11.9 x 44 x 7 (2#/bbl LCM) (2% oil)

Shell- Gulf-Doyle 1-10B3 (D) Brinkerhoff #54 13,300' Wasatch Test 7" csg @ 10,754' 10,779/71/36/0. Drilling cmt. Tested BOP stack to 5000 psi and hydril to 3000 psi. Tested csg to 3500 psi. Drld cmt, FC and shoe.

Mud: (gradient .624) $12.0 \times 50 \times 10.2$ (2% oil)

Shell- Gulf-Doyle 1-10B3 (D) Brinkerhoff #54-13,300' Wasatch Test 7" csg @ 10,740'

10,845/71/37/66. Drilling. Tripped for dia bit @ 10,782. SLM corrected csg shoe @ 10,740 instead of $\frac{10.754}{10.000}$. Mud: (gradient .728) 14.0 x 50 x 8.4

Shell--Gulf-Doyle 1-10B3 (D) Brinkerhoff #54 13,300' Wasatch Test 7" csg @ 10,740' 10,980/71/38/135. Drilling. Background gas: 22 units. Connection gas: 45 units. Lost 50 bbls mud. $_{\rm AAN}$ 0.5 19/3 Mud: (gradient .806) 15.5 x 50 x 6.2

Shell-Gulf-Doyle 1-10B3 (D) Brinkerhoff #54 13,300' Wasatch Test 7" csg @ 10,740' 11,080/71/39/100. Drilling. Lost 25 bbls mud. Background gas: 20 units. Connection gas: 160 units. Mud: (gradient .811) 15.6 x 54 x 5.4 $_{\rm MAN}$ 2 6 1073

Shell-Gulf-Doyle 1-10B3 (D) Brinkerhoff #54 13,300' Wasatch Test 7" csg @ 10,740' 1/27: 11,185/71/40/105. Drilling. Background gas:
45 units. Connection gas: 300 units.
Mud: (gradient .811) 15.6 x 48 x 4.8
1/28: 11,260/71/41/75. Drilling. Tripped for bit @
11,190. Background gas: 130 units. Connection gas:
630 units. Trip gas: 1200 units.
Mud: (gradient .816) 15.7 x 54 x 4.8
1/29: 11,410/71/42/150. Drilling. Background gas:
25 units. Connection gas: 100 units. Max gas: 350 units.
Mud: (gradient .820) 15.8 x 58 x 4.4

Shell-Gulf-Doyle 1-10B3 (D) Brinkerhoff #54 13,300' Wasatch Test 7" csg @ 10,740' 11,552/71/43/142. Drilling. Background gas: 30 units. Connection gas: 200 units. Mud: (gradient .820) 15.8 x 54 x 4.4

Shell-Gulf-Doyle 1-10B3 (D) Brinkerhoff #54 13,300' Wasatch Test 7" csg @ 10,740' 11,682/71/44/130. Drilling. Background gas: 40 units. Connection gas: 250 units. Mud: $15.8 \times 54 \times 4.2$

Shell- Gulf-Doyle 1-10E3 (D) Brinkerhoff #54 13,300' Wasatch Test 7" csg @ 10,14)'

11,806/71/45/124. Drilling. Background gas: 25 units. Connection gas: 300 units. FEB 1 1973 Mud: (gradient .820) 15.8 x 55 x 4.4

Shell-Gulf-Doyle 1-10B3 (D) Brinkerhoff #54 13,300' Wasatch Test 7" csg @ 10,740'

11,940/71/46/134. Drilling. Background gas: 25 units. Connection gas: 200 units. Mud: (gradient .820) 15.8 x 54 x 4.4 $^{\circ}$ 2 $^{\circ}$

Shell-Gulf-Doyle 1-1083 (D) Brinkerhoff #54 13,300' Wasatch Test 7" csg @ 10,740"

2/3: 12,056/71/47/116. Drilling. Background gas: 20. units. Connection gas: 225 units.

Mud: $15.9 \times 53 \times 4.5$ 2/4: 12,142/71/48/86. Drilling. Changed bits @ 12,071.

Circ 30 min. Picked up 12 DC's and 20 jts HWDP.

Mud: (gradient .820) 15.8 x 52 x 4.4 2/5: 12,342/71/49/200. Drilling. Connection tight had high torque, then no torque. Downtime and connection gas: 200 units. Background gas: 25 units.

Mud: (gradient .820) 15.8 x 62 x 4.4

Shell- Gulf-Doyle 1-10B3 (D) Brinkerhoff #54 13,300' Wasatch Test 7" csg @ 10,740'

12,600/71/50/258. Drilling. Hole sloughing. Background gas: 35 units. Connection gas: 150 units. Mud: (gradient .820) 15.8 x 54 x 4.6

Shell- Gulf-Doyle 1-1083 (D) Brinkerhoff #54 13,300' Wasatch Test 7" csg @ 10,740'

12,875/71/51/275. Drilling. Background gas: 40 units. Connection gas: 120 units. Mud: (gradient .820) 15.8 x 54 x 4.6

Shell-Gulf-Doyle 1-10B3 (D) Brinkerhoff #54 13,300' Wasatch Test 7" csg @ 10,740'

13,090/71/52/215. Drilling. Background gas: 25 units. Connection gas: 100 units. Mud: (gradient .821) $15.8 \times 58 \times 4.6$

Shell-Gulf-Doyle 1-1083 (D) Brinkerhoff #54 13,200' Wasatch Test 7" csg @ 10,740'

13,200/71/53/110. Logging. Made SLC: 13,195 = 13,200. Circ 5 hrs to cond hole for logs. Background gas: 25-30 units. Connection gas: 100 units. Short trip gas: 250 units. Mud: (gradient .821) $15.8 \times 50 \times 3.2$

Shell-Gulf-Doyle 1-10B3 (D) Brinkerhoff #54 13,200' Wasatch Test 7" csg @ 10,740'

2/10: 13,195/71/54/0. Logging DTL log. On first log run, tool failed on btm; had excessive drag @ 12,139' on second run. Made wiper trip to cond hole. Having tool problems at report time. Mud: (gradient .821) 15.8 x 51 x 3.6 2/11: 13,195/71/55/0. Logging. Unable to get log due to Schl tool failures. Cond hole while WO new truck and tools. Background gas: 30 units. Trip gas: 350 units. Mud: (gradient .821) $15.8 \times 53 \times 3.2$ 2/12: 13,195/71/56/0. Circ and cond hole. Ran CBL, GR

and VDL from 10,742-9000. Ran BHCS-ER from 13,207-10,742. Had tool failure on DIL log. Background gas: 30 units. Trip gas: 250 units. TES 10 HE

Mud: (gradient .821) $15.8 \times 51 \times 3.2$

Note: SLC should have read: 13,200 = 13,195.

Shell- Gulf-Doyle 1-10B3 (D) Brinkerhoff #54 13,200' Wasatch Test 5" liner @ 13,195'

13,195/71/57/0. Cmtg 5" liner. Ran CNL-FDC-GR log from 13,207-11,740. Ran 63 jts (2657') 5", 18# hydril SFJ-P, S00-95, N-80 liner w/shoe @ 13,195, Burns liner hanger @ 10,577 and Howco diff float @ 13,090. Mud: 15.8 x 53 FEB 12 - 273

Shall- Gulf-Doyle 1-10B3 (D) Brinkerhoff #54 13,195' Wasatch Test 5" liner @ 13,195'

13,195/71/58/0. Running in hole to sqz lap. B-J cmtd 5" liner w/5 BW ahead followed by 520 sx Class "G" w/l% D-31 and 0.04% R-5. Displaced w/121 bbls 15.8 ppg mud. Had good returns. Bumped plug @ 13,090 w/3000 psi, float held. CIP @ 7:30 AM, 2/13. Tested 7" x 9-5/8" csg - no press. Tested liner lap, breaking down w/450 psi. Mud: 15.8 x 53 FES 14 1973

Shell-Gulf-Doyla 1-10B3 (D) Brinkerhoff #54 13,195' Wasatch Test 5" liner @ 13,195'

13,195/71/59/0. Tripping for new bit. Set Hal RTTS tool @ 10,270. Sqzd w/150 sx Class "G" cmt. Tested to 2500 psi for 15 min, OK. Tripped out w/RTTS. Mud: 15.8 x 53 x 3.8 . spp a 7

Shell- Gulf-Doyle 1-1083 (D) Brinkerhoff #54 13,195' Wasatch Test 5" liner @ 13,195'

13,195/71/60.0. Testing csg. CO to top of liner and drld cmt to 13,125. Ran RTTS tool and inflow tested @ 9000', OK. FEB 1 6 1973

Shell- Gulf-Doyle 1-1083 (D) 13,195' Wasatch Test 5" liner at 13,195' TD 13,195. PB 13,125. 3/9: Ran 34 jts $5\frac{1}{2}$ " 14# K-55 ST&C csg (heat string). Installed back press valve, removed BOP's, installed and tested 6" 5,000 WP x 10" 5,000 WP tbg spool, installed and tested EOP's to 5,000 psi, and removed back press valve. Began picking up prod equip and tested to 7500 3/10: Ran prod equip and spaced out pkr. Displaced csg w/treated water and displaced tog w/2% SW. Landed thg and press tested to 7500 psi for 1 hr, had loss of 75#. Installed back press valve and removed EOP's. Installed 10,000% Xmas tree and press tested to 10,500 psi, ok. Released rig 3 PM 3/10. Ran prod equip as follows: Bkr Model "C" extended plug holder w/Bkr Model "B" pushout plug at 10,579, 30' 2 7/8" 10rd thd NU tbg tail, Bkr seal assmoly w/two seal units, Bkr "EL" on-off tool w/Otis 2.313" nipple and 2.255 No GO at 10,540, 8' x 2 7/8" EUE 8rd thrd N-80 tbg sub w/centralizer top at 10,532, 3 jts EUE 8rd thrd N-80 tbg, all tbg and sub follows the same, one Camco KEMG mandrel w/dunmy No. HN-4 at 10,434, 160 jts 2 7/8" EVE tbg, one Camco KEMG mandrel w/dummy No. HN-3 at 5498, 176 jts tbg, 1-2' sub, 2-10' subs, and 1 jt tbg. Total tbg - 340 jts. 3/11: MO Western Oilwell Service. Released rig 9 AM. RU Archer & Reed. Knocked out plug, chased to btm, and pulled out of hole. RD. Mag 13 1003 3/12: Prep to perf.

Shell-Gulf-Doyle 1-10B3 (D) 13,195' Wasatch Test 5" liner @ 13,195' TD 13,195. PB 13,125. Prep to perf. TAR 13 1873

Shell-Guli-Doyle 1-1083 (D) 13,195' Wasatch Test 5" liner @ 13,195' TD 13,195. PB 13,125. Perforating. MI&RU McC on 3/13. Perf'd the following intervals unidirectionally using magnetic decentralized 2" steel tube earrier gun w/JRC charges. Run #1: 10,764, 10,792, 10,801. Gun malfunctioned. Press 250 psi. Run #2: 10,809. Gun malfunctioned. Press 250 psi. Run #3: 10,815, 10,824, 10,831, 10,865, 10,926, 10,940, 10,974. Gun malfunctioned. Press from 250-1400 psi. Run #4: Gun malfunctioned - did not perf. RD&MO McC. (All perfs refer to BHCS log daced 2/2/73.) MAR 14 2023

Shell-Gulf-Doyle 1-10B3 (D) Brinkerhoff #54 13,195' Wasatch Test 5" liner 3 13,195' 2/17: 13,195/71/61/0. PB 13,125. Loading out D?. Tested all csg, OK. Laid down DP. DO to 13,125. Liner top corrected to 10,577. \$18.18 1008

Mud: 15.8 x 45

2/18: TD 13,195. PB 13,125. Loading eqmt, cleaning pits. Nippled down and installed Xmas tree. Released rig to standby @ 6 AM, 2/18/73. (RDUFA)

Shell-Gulf-Doyle 1-10B3 (D) Western Oilwell 13,195' Wasatch Test 5" liner @ 13,195' TD 13,195. PB 13,125. (RRD 2/19/73) Installing BOP. MI&RU Western Oilwell Service on 3/5/73. MAR \S

Shell- Gulf-Doyle 1-10B3 (D) Western Gilwell 13,195' Wasatch Test 5" liner @ 13,195' TD 13,195. PB 13,125. Picking up tbg. Finished RU Western. Installed BOP and tested to 5000 psi. Picked up 4-1/8" bit, 2575' of 2-7/8" tbg work string and 7" scraper. NAC 1973

Shell-Gulf-Doyle 1-10B3 (D) Western Oilwell 13,195' Wasatch Test 5" liner @ 13,195' TD 13,195. PB 13,125. Pulling tbg. Finished running tbg to PBTD. Circ out 15.8 ppg mud w/FW. Press tested csg to 5000 psi, OK. Checked for flowback, OK. Sptd 50 bbls 2% NaCl in liner and started pulling tbg. 1873

Shell-Gulf-Doyle I-10B3 (D) Western Oilwell 13,195! Wasatch Test 5" liner @ 13,195!

TD 13,195. PB 13,125. Going in hole w/5½" heat string. Pulled and laid down 7" scraper, 2575' of 2-7/8" tbg and 4-1/8" bit. RU McC and ran CBL, VDL and PDC logs from 10,000-13,125 w/3000 psi. Had poor bond from 11,010-11,470. Ran Baker Model "D" pkr and set @ 10,546 (WL measurement). Top of liner @ 10,571 (WL measurement).

Shell- Gulf-Doyle 1-1033 (D) 13,195' Wasatch Test 5" liner @ 13,195' TD 13,195. PB 13,125. Prep to acdz. MISRU OWP on 3/14. Perf'd the following intervals unidirectionally w/magnetic decentralized 2" steel tube carrier gun w/JRC charges:

Run #1: 10,990, 11,055, 11,065, 11,088, 11,203, 11,367, 11,393, 11,439, 11,499, 11,528, 11,553, 11,625, 11,633, 11,656, 11,727, 11,760, 11,806, 11,852, 11,859, 11,879, 11,886, 11,902, 11,912, 11,939, 11,962, 11,996, 12,005, 12,022, 12,054, 12,067, 12,174. Press 2700-2800 psi.

Run #2: 13,104, 12,233, 12,255, 12,258, 12,299, 12,301, 12,386, 12,424, 12,428, 12,475, 12,484, 12,504, 12,562, 12,616, 12,654, 12,658, 12,660, 12,732, 12,761, 12,910, 12,942, 12,972, 13,021, 13,051. Press 2800-2820 psi. The 1873

Shell-Gulf-Doyle 1-10B3 (D) 13,195' Wasatch Test 5" liner @ 13,195' TD 13,195. PB 13,125. WO rig. MI&RU B-J. Attempted to AT. After pumping 2 bbls, tbg communicated w/csg-annulus. CP 2500 psi, TP 5000 psi. RD B-J. RU Archer Reed. Set Otis blanking plug in "N" nipple @ 10,546. RD Archer Reed. MAR 1 6 1973

Shell- Gulf-Doyle 1-10B3 (D) 13,195' Wasatch Test 5" liner @ 13,195'

TD 13,195. PB 13,125.

3/17: MI&RU Western Oilwell Service.

3/18: SI. Finished MI&RU Western. Installed BPV,
removed Xmas tree, installed BOP, and removed BPV.
Picked up tbg - on-off connector was not latched.
Displaced 10 bbls trtd wtr in csg. Latched onto on-off connector. Press tested tbg to 7500 psi for 30 min lost 25 psi. Installed BPV, removed BOP, installed
10,000# Xmas tree and removed BPV. Released rig @ 4 PM,
3/17.

3/19: SI.

Shell-Gulf-Doyle 1-10B3 (D) 13,195' Wasatch Test 5" liner @ 13,195'

TD 13,195. PB 13,125. Prep to acdz. Pulled prong from Otis PN plug chk and Otis hand mandrel from 10,522.

Shell-Gulf-Doyle 1-10B3 (D) 13,195' Wasatch Test 5" liner @ 13,195' TD 13,195. PB 13,125. Prep to flow to pit to clean up. AT gross perfs 10,764-13,104 w/32,000 gal 15% HCl. Distributed seventy 7/8" x 1.24 gr ball sealers throughout acid. Each 1000 gal acid contained 20# G-5, 3 gal C-15, 10 gal J-7, 3 gal J-22 and 30# OS-160 Wide Range Unibeads and 30# OS-160 Unibead Buttons. Flushed w/4500 gal FW w/each 1000 gal containing 165# NaCl and 20# G-5. Max press 9600 psi, avg 8300 psi, min 6300 psi. Max rate 7 B/M, avg 6 B/M, min 1 B/M. ISIP 5600 psi decr to 5400 psi in 5 min to 5000 psi in 10 min to 4600 psi in 15 min and to 4500 psi in 20 min. Several breaks of 100 to 1400 psi. Good ball action. MAR 21 1973

Shell-Gulf-Doyle 1-10B3 (D) 13,195' Wasatch Test 5" liner @ 13,195' TD 13,195. PB 13,125. SI for BHP. Flowed to pit 5 hrs on 64/64" chk, flwg est 500 BO and 450 BW w/GOR of 1300 w/850-900 psi FTP. Last hr, flowed est 160 BO and 40 BW on 64/64" chk w/900 psi FTP. Chks and press's as follows: Choke Pressure Choke Pressure

 Choke
 Pressure
 Choke
 Pressure

 54/64"
 975 psi
 14/64"
 3125 psi

 44/64"
 1200 psi
 4/64"
 3500 psi

 34/64"
 1600 psi
 SITP
 3600 psi

 24/64"
 2250 psi

SI @ 3 PM. Backed down w/5 bbls diesel. TP 3750 psi. Ran tendem bombs to 12,000'. Bombs on btm @ 4:45 PM. TP 4100 psi. Will pull bombs 3/24/73. MAR 2 2 1973

Shell- Gulf-Doyle 1-10B3 (D) 13,195' Wasatch Test 5" liner @ 13,195'

TD 13,195. PB 13,125. SI for BHP. MAR 2 3 1973

Shell-Gulf-Doyle 1-10B3 (D) 13,195' Wasatch Test 5" liner @ 13,195' TD 13,195. PB 13,125. SI, WO facilities. Pulled 72-hr BHP bomb, making stops @ 12,200 and 11,800. ISIP 3800 psi, press after bomb on btm 1½ hrs - 7380 psi; press after 60½ hrs - 8253 psi; press after 70½ hrs - 8253 psi. TP prior to pulling bomb 4779 psi. (RDUFA) MAR 2 6 1973

Shell-Gulf-Doyle 1-10B3 (D) 13,195' Wasatch Test 5" liner @ 13,195' TD 13,195. PB 13,125. (RRD 3/26/73) Flowing. On 12-hr test 6/11/73, flowed 374 BO, 57 BW and 520 MCF gas on 10/64" chk w/3900 psi FTP and zero CP.

Note: Shell acquired Chevron's 1.26672% interest in this well changing Shell's share to 93.75%. JUN 11 1973

Shell-Gulf-Doyle 1-10B3 (D) 13,195' Wasatch Test 5" liner @ 13,195'

TD 13,195. PB 13,125. Flowing. On 24-hr test, well flowed 851 BO, 4 BW and 949 MCF gas on 10/64" chk w/ 3400 psi FTP and 36 psi CP. JUN 12 1973

Shell-Gulf-Doyle 1-10B3 (D) 13,195' Wasatch Test 5" liner at 13,195'

TD 13,195. PB 13,125. Flowing. On 24-hr test, well flowed 765 BO, 3 EW, and 930 MCF on 10/64" chk w/3700 psi and 0 CP. JUN 10 1973

Shell-Gulf-Doyle 1-10B3 13,195' Wasatch Test 5" liner @ 13,195'

TD 13,195. PB 13,125. Flowing. On 24-hr test, well flowed 585 BO, 7 BW and 665 MCF gas on 10/64" chk w/ 3000 psi FTP and zero CP. JUN 14 1573

Shell-Gulf-Doyle 1-10B3 13,195' Wasatch Test 5" liner @ 13,195'

TD 13,195. PB 13,125. Flowing. On 24-hr test, well flowed 633 BO, 6 BW and 744 MCF gas on 10/64" chk w/ 2800 psi FTP and zero CP. JUN 15 1973

Shell-Gulf-Doyle 1-10B3 (D) 13,195' Wasatch Test 5" liner @ 13,195'

TD 13,195. PB 13,125. Flowing. On 24-hr tests, well JUN 18 1973 flowed as follows: Report CP FTP Chk MCF Gas BWво Date 10/64" 2800 0 7 470 576 6/16 0 10/64" 2600

10/64"

2600

0

704

689

7

8

6/17

6/18

619

541

Shell-Gulf-Doyle 1-10B3 (D) 13.195' Wasatch Test 5" liner @ 13,195'

TD 13,195. PB 13,125. Flowing. On 24-hr test, flowed 537 BO, 9 BW and 625 MCF gas on 10/64" chk w/2200 psi FTP and zero CP. JUN 19 1973

Shell-Gulf-Doyle 1-10B3 (D) 13,195' Wasatch Test 5" liner @ 13,195'

TD 13,195. PB 13,125. Flowing. On 24-hr test, flowed 483 BO, 8 BW and 596 MCF gas on 10/64" chk w/2100 psi FTP and zero CP. 13. 2 3 1973

Field _		ltamont		v	Vell	Doyle 1-10)B3	
Job: _	•		£25kng ∕Liner. F	Ran to	13,195	_ feet (KB)	on <u>2-13</u>	, 197 <u>3</u>
Jts.	Wt.	Grade	Thread	New	Feet	From	<u>To</u>	
					25.08	КВ	CHF	
15	18#	S00-95	Hydril	X	603	CHF		
48	18#	N-80	Hydril	X	2015			
63 jt	s Total							
Line	r top at	10,577						
CO t	0 13,125			·		-		
Cent	ralizer type a	and product num lled on the follow	wco diff floathber 13 B & wing joints 2 V. collar, etc.)	W shoe 28, 41,	2, 3, 4, 5, 43, 44			
Prefl First	: ush-Water _ stage, type :	5 bbls, and additives	other	Vol.	D-31 and .(_ bbls 04% R-5	lbs/gal, yiel	d
ft ³ /sl Cementi	k, volume _ ng Procedure	sx. Pum e:	pability			. Weight	lbs/gal, yield	t
	te/reciprocat acement rate	e e	3 bbls					
Bum	ped plug at	lbs on sl					$1\frac{1}{2}$ bbls	
			77 w/Burns ha					
			ns throughout m 10,307 RTTS					ass "G"
					•			
		• •		•				
				······································		**		•

Drilling Foreman Ken Crawford

Date 2-13-73

STATE OF UTAH DEPARTMENT OF NATURAL RESOURCES DIVISION OF OIL AND GAS CONSERVATION 1588 West North Temple Salt Lake City, Utah 84116

REPORT OF WATER ENCOUNTERED DURING DRILLING

Well Nam	e and Number	Shell-Chevron-Gu	ulf-Doyle 1-10B3		
Operator	W	Shell Oil Compar	ny (Rocky Mounta	<u>in Division I</u>	Production)
	Address	1700 Broadway, I	enver, Colorado	80202	
Contract	or	Brinkerhoff Dril	ling Company		
	Address	600 Denver Club	Building, Denve	r, Colorado 8	30202
Location	_SE_1/4,	NW 1/4, Sec. 10	, T. <u>2</u> 1, R.	3 <u>₹</u> .,	Duchesne County.
Water Sa					
Fr	Depth:	To -	Volume: Flow Rate or He	∋ad -	Quality: Fresh or Salty -
ı	No sands tes	ted or evaluated	and no water fl	ow encountere	ed
2	(GR log avai	lable from 300-TD)		
3,		-			
4		The section of the se			
5					
			(Continu	ue on Reverse	Side if Necessary)
Formation	Tops				

Formation lops:

NOTE: (a) Upon diminishing supply of forms, please inform this office.

- (b) Report on this form as provided for in Rule C-20, General Rules and Regulations and Rules of Practice and Procedure, (see back of this form)
- (c) If a water quality analysis has been made of the above reported zone, please forward a copy along with this form.

OGCC-1 b.		TATE OF UTAH NSERVATION COMI	MISSION	SUBMIT IN TRIE (Other instruction verse side)	ns on re-	5. LEASE DESIGNATION AND SER	IAL N
SUN (Do not use this	NDRY NO	OTICES AND REPO	ORTS ON	WELLS to a different reserve		Patented 3. IF INDIAN, ALLOTTEE OR TRII	SE NA!
OIL THE GAS		****				7. UNIT AGREEMENT NAME	
WELL WELL WELL 2. NAME OF OPERATOR		il Company (Rocky			ction) 8	3. FARM OR LEASE NAME	
ADDRESS OF OPERATO		Oil and Gulf Oil	Corpora	tion	9	Doyle	
		padway, Denver, Co	olorado	80202		1-10B3	
. LOCATION OF WELL (See also space 17 be At surface	elow.)	NL and 2157' FWL S		e requirements.	1	Altamont 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA SE/4 NW/4 Section T 2S-R 3W	
4. PERMIT NO.		15. ELEVATIONS (Show w	hether DF, RT,	gR, etc.)		1 20-f. JW 12. COUNTY OR PARISH 18. ST	ATE
			6058 KB			Duchesne Uta	<u>ah</u>
6.	Check	Appropriate Box To Ind	icate Natu	re of Notice, Rep	oort, or Oth	ier Data	
	NOTICE OF IN	TENTION TO:	_		SUBSEQUEN	T REPORT OF:	
TEST WATER SHUT- FRACTURE_TREAT	OFF	PULL OR ALTER CASING MULTIPLE COMPLETE		WATER SHUT-OFF FRACTURE TREATM	LENT	REPAIRING WELL ALTERING CASING	\dashv
	<u> </u>	Mediana comitant					
Reshoot on acidize	X	ABANDON*		SHOOTING OR ACID	DIZING	ABANDONMENT*	
Reshoot on acidize REPAIR WELL (Other)	OR COMPLETED	CHANGE PLANS	pertinent de ace locations	(Other)(Note: Rep('ompletion of tails, and give perting	ort results of	multiple completion on Well on Report and Log form.) cluding estimated date of star depths for all markers and zon	rting nes p
Reshoot on Acidize REPAIR WELL (Other) 7. DESCRIBE PROPOSED of proposed work.	OR COMPLETED	CHANGE PLANS OPERATIONS (Clearly state all ectionally drilled, give subsurf	ace locations	(Other) (NOTE: Rep ('ompletion of tails, and give perting and to the tails)	ort results of or Recompletion nent dates, in true vertical d	multiple completion on Well on Report and Log form.)	rting nes p
Reshoot on acidize REPAIR WELL (Other) 7. DESCRIBE PROPOSED of proposed work.	OR COMPLETED	CHANGE PLANS OPERATIONS (Clearly state all ectionally drilled, give subsurf	ace locations	(Other)(Note: Rep('ompletion of tails, and give perting	ort results of or Recompletion nent dates, in true vertical d	multiple completion on Well on Report and Log form.)	rting pes p
Reshoot on acidize REPAIR WELL (Other) 7. DESCRIBE PROPOSED of proposed work.	OR COMPLETED	CHANGE PLANS OPERATIONS (Clearly state all ectionally drilled, give subsurf	ace locations	(Other) (Note: Rep (Completion) tails, and give pertir and measured and t	ort results of or Recompletionent dates, intrue vertical d	multiple completion on Well on Report and Log form.)	ico p
REPAIR WELL (Other) 7. DESCRIBE PROPOSED proposed work. nent to this work. 18. hereby certified.	DR COMPLETED If well is dir	OPERATIONS (Clearly state all ectionally drilled, give subsurf	per atta	(Other) (Note: Rep (Completion) tails, and give pertir and measured and t	ort results of or Recompletionent dates, intrue vertical d	multiple completion on Well on Report and Log form.) cluding estimated date of standepths for all markers and zon depths for	ico y
REPAIR WELL (Other) 7. DESCRIBE PROPOSED proposed work. nent to this work.	DR COMPLETED If well is dir	OPERATIONS (Clearly state all ectionally drilled, give subsurf	per atta J. S. LE Divis	(Other) (Note: Rep (Completion) tails, and give pertir and measured and t	ort results of or Recompletionent dates, intrue vertical d	multiple completion on Well on Report and Log form.) cluding estimated date of standepths for all markers and zon depths for	ico p

REPERFORATION AND RESTIMULATION PROGNOSIS DOYLE 1-10B3 SECTION 10-T2S-R3W ALTAMONT FIELD DUCHESNE COUNTY, UTAH

PERTINENT DATA:

TD: 13,195' AFE NO.: 598007 (R&R) PBTD: 13,125' SHELL'S SHARE: 93.75%

ELEV KB: 6,058' KB-GL: 25'

CURRENT STATUS: Tubing leak being repaired. There are 66 existing perforations

over the gross interval 10,764 to 13,104.

PROPOSED WORK: Reperforate and restimulate the gross interval 10,763 to 13,104.

PROCEDURE:

1. Perforate, from bottom up if desired, one hole at each of the following depths (depths refer to BHCS/GR/Cal dated 2/11/73). Perforate unidirectional using magnetically decentralized 2" steel tube carrier guns. Use JRC "DP Sidewinder" or Schlumberger "Hyperjet" charges. Total of 120 additional perforations.

10,763	11,064	11,728	11,938	12,298	12,658
10,765	11,066	11,757	11,960	12,301	12,660
10,766	11,067	11,758	11,961	12,387	12,731
10,793	11,089	11,761	11,963	12,388	12,759
10,794	11,204	11,762	11,997	12,423	12,760
10,800	11,366	11,805	11,998	12,425	12,762
10,810	11,368	11,850	12,004	12,426	12,908
10,816	11,394	11,851	12,006	12,427	12,909
10,823	11,459	11,857	12,023	12,429	12,911
10,825	11,460	11,858	12,053	12,474	12,943
10,832	11,497	11,860	12,055	12,476	12,971
10,866	11,498	11,878	12,066	12,484	12,973
10,924	11,500	11,880	12,068	12,503	12,974
10,925	11,527	11,885	12,173	12,561	13,020
10,927	11,529	11,887	12,175	12,563	13,050
10,940	11,530	11,901	12,176	12,564	13,052
10,975	11,552	11,903	12,232	12,614	13,053
10,989	11,626	11,904	12,255	12,615	13,101
10,991	11,634	11,911	12,259	12,617	13,102
11,054	11,657	11,913	12,260	12,655	13,103
-	-	-	•		

2. Acid treat the gross perforated interval 10,763 to 13,104 with 90,750 gallons (2,161 bbls) 28% HCl-gelled Turbine Oil (TO) as follows:

- a. Pump 73 barrels (3,066 gal) 28% HCl-TO at a maximum rate of 8 BPM. Do not exceed 8,900 psi surface pressure.
- b. Drop one (1) 7/8" RCN ball sealer (S.G.-1.24) then pump 11 bbls 28% HCl-TO.
- c. Repeat Step b 185 more times for a total of 2,035 bbls of 28% HC1-TO and 185 ball sealers.
- d. Pump 42 barrels 28% HC1-TO.
- e. Flush w/4,326 gals (103 bbls) fresh water containing 165# NaCl and 3 gals G-10 per 1,000 gals.

NOTES:

- A. 28% acid TO is to be mixed as follows:
 - Acid Each 1,000 gal of 28% HCl to contain 48 lb G-5 (gel and friction reducer) and 6 gals of C-15 (corrosion inhibitor). (Total of 30,850 gal 28% HCl.)
 - Turbine Oil Each 1,000 gal of turbine oil to contain 10 gal of ENJAY 8596 Surfactant (Emulsifier). (Total of 59,900 gal of TO).

The turbine oil and acid will require separate tankage for mixing. To the blended Acid-Turbine Oil mixture (during pumping) add to each 1,000 gal, one (1) 1b of Iridium 192 treated Silica Flour and 30 1bs OS-160 wide range Unibeads and 30 1bs OS-160 Button Unibeads. The RA silica flour must be uniformly distributed throughout the entire treatment volume.

- B. If ballout occurs before all acid is injected into the formation, pressure tubing up to 9500 psi, hold for 3 minutes, bleed back and inject remainder of acid. Hold 3500 psi on tubing-casing annulus and heat all fluids to $75^{\circ}F$ Not warmer than $80^{\circ}F$ maximum.
- 3. Run GR log over the perforated interval.
- 4. Flow off for cleanup and return well to production.
- 5. Run BHP as required.

GPD:sp 12/12/73

Div O F

DIV. O.D.

Siam

3. L. Faulk

OGCC-1 b•		OURSE IN TRUIT IOATEN		
	STATE OF UTAH OIL AND GAS CONSERVATIO	SUBMIT IN TRIPLICATES (Other instructions on re ON verse side)	5. LEASE DESIGNATION AND SERIAL NO. Patented	
	OTICES AND REPORTS roposals to drill or to deepen or plug PLICATION FOR PERMIT—" for such		6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
OIL X GAS WELL OTHE	ER		7. UNIT AGREEMENT NAME	
2. NAME OF OPERATOR Shell	TO MATERIAL CONTRACTOR			
3. ADDRESS OF OPERATOR			8. WELL NO. 1-10B3	
1700 Broadway, Denver, Colorado 80202 4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. At surface			10. FIELD AND FOOL, OR WILDCAT Altamont	
2382	FNL and 2157' FWL Sect	ion 10	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA SE/4 NW/4 Section 10- T2S-R3W	
14. PERMIT NO.	15. BLEVATIONS (Show whether to	of RT, GR, etc.) 048 KB	12. COUNTY OR PARISH 18. STATE Duchesne Utah	
	Appropriate Box To Indicate	• • •		
NOTICE OF I	NTENTION TO:	SUBSEQ WATER SHUT-OFF	QUENT REPORT OF: REPAIRING WELL	
FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL	MULTIPLE COMPLETE ABANDON* CHANGE PLANS	Re shooting or acidizing (Other)	ALTERING CASING X ABANDONMENT*	
(Other)	D OUR PATIONS (Classely State all Docting	Completion or Recomp	s of multiple completion on Well pletion Report and Log form.) s. including estimated dute of starting any	
proposed work. If well is dinent to this work.) *	irectionally drilled, give subsurtace loc	ached report	cal depths for all markers and zones perti-	
	no per atte	zeneu report		

A				
SIGNED SIGNED SIGNED	TITLE .	For: J. S. Mize Division Operations Engr.	DATE	1/21/74
(This space for Federal or State office use)				The state of the s
APPROVED BY	TITLE	And the state of t	DATE	

REPERF & STIMULATE				ALTAMONT
SHELL OIL COMPANY-GULF-	LEASE	DOYLE	/ELL NO.	1-10B3
	DIVISION	ROCKY MOUNTAIN	ELEV	6048 KB
FROM: 12-11 - 12-28-73	COUNTY	DUCHESNE	STATE	UTAH

UTAH

ALTAMONT

Shell-Gulf-Doyle 1-10B3 (Reperf and restim)

"FR" TD 13,195. PB 13,125. Prep to RU. AFE #598007 provides funds to reperforate and restimulate gross perf'd interval 10,763-13,104. Cleaned location and MI Western Oilwell Service rig #17 on 12/10/73.

DEC 11 1973

Shell-Gulf-Doyle 1-10B3 (Reperf and restim)

TD 13,195. PB 13,125. Pulling tbg. Finished RU. Bled off tbg and csg. Installed BPV, removed tree and installed BOP. Press tested BOP to 5000 psi for 10 min, OK. Removed BPV. Latched onto tbg, pulling 20 pts over wt of string. On-off tool OK. Unlatched from on-off tool. Circ hole w/380 bbls 80°F. FW treated w/13 qts M-15C/50 bbls and 20# 3601/200 bbls. Started pulling tbg. 313 1873

Shell-Gulf-Doyle 1-10B3 (Reperf and restim)

TD 13,195. PB 13,125. Running prod eqmt. Finished pulling tbg. Laid down two Camco mandrels and on-off tool. Running tbg w/new on-off connector and seven new Camco mandrels. No visual damage to pulled mandrels. On-off seal connector that was pulled had several seals completely missing and several seals broken and pulled out of seal recess. 100 100 1973

Shell-Gulf- $\log |\epsilon|_{\ell-\ell_0}$ (Reperf and restim)

TD 13,195. PB 13,125. Well SI w/plug at 10,540. Completed rng prod equip and ran total of 340 jts 2 7/8" EUE 8rd N-80 tbg w/new on-off seal connector on btm, 10' tbg sub above seal connector. Ran seven Camco KRMG mandrels #18409-13 at 10,434, #17H09-12 at 9700, #15H09-19 at 8966, #13H09-12 at 8202, #7H09-12 at 7013, #3H09-19 at 5309, #2H09-12 at 2907. All mandrels w/durmy valves. Spaced tbg w/l point wt on pkr. Unlatched from on-off tool. Pmpd 58 bbls clean diesel down tbg. Latched on-off tool. Pmpd 58 bbls clean diesel down tbg. Latched on-off tool. Landed tbg on donut and locked in donut. Press tested tbg to 7500 for one hr, held ok. Press tested csg w/3,000 psi for 15 min w/6000 psi on tbg, held ok. Let off all press and installed BPV, removed BOP's, and installed 10,000 psi Xmas tree. Removed BPV and installed test plug. Press tested tree to 10,500 psi for 5 min, held ok. Removed test plug and press'd tbg to 2,000 psi, SI. Released rig 6 PM 12-13-73.010 14 1973

Shell-Gulf-Doyle 1-10B3 (Reperf and restim)

TD 13,195. PB 13,125. SI. DEC 14 1973

Shell-Gulf-Doyle 1-10B3 (Reperf and restim)

TD 13,195. PB 13,125. Prep to acdz. RU OWP and perf'd one hole at each of the following depths from bem up, perf'g unidirectionally using magnetic decentralized 2" steel tube carrier gun w/JRC-DP Sidewinder charges. Depths refer to BHCS-GR w/cal dated 2/11/73. **13,103, 13,102, 13,101, 13,053, 13,052, 13,050, 13,020,** 12,974, 12,973, 12,971, 12,943, 12,911, 12,909, 12,908, 12,762, 12,760, 12,759, 12,731, 12,660, 12,658, 12,655, 12,617, 12,615, 12,614, 12,564, 12,563, 12,561, 12,503, 12,484, 12,476, 12,474, 12,429, 12,427, 12,426, 12,425, 12,423, 12,388, 12,387, 12,301, 12,298, 12,260. Beginning and ending press 1700 psi. Run #2: 12,259, 12,255, 12,232, 12,176, 12,175, 12,173, 12,068, 12,066, 12,055, 12,053, 12,023, 12,006, 12,004, 11,998, 11,997, 11,963, 11,961, 11,960, 11,938, 11,913, 11,911, 11,904, 11,903, 11,901, 11,887, 11,885, 11,880, 11,878, 11,860, 11,858, 11,857, 11,851, 11,850, 11,805, 11,762, 11,761, 11,758, 11,757, 11,728, 11,657, 11,634. Beginning and ending press 1700 psi. Run #3: 11,626, 11,552, 11,530, 11,529, 11,527, 11,500, 11,498, 11,497, 11,460, 11,459, 11,394, 11,368, 11,366, 11,204, 11,089, 11,067, 11,066, 11,064, **11,054, 10,991, 10,989, 10,975, 10,940, 10,927, 10,925,** 10,924, 10,866, 10,832, 10,825, 10,823, 10,816, 10,810, 10,800, 10,794, 10,793, 10,766, 10,765, 10,763. Press from 1700 to 1750 psi. (Total of 120 perfs.)

Shell-Gulf-Doyle 1-10B3 (Reperf and restim)

TD 13,195. PB 13,125. Prep to run GR log. RU B-J and AT gross perfs from 10,763-13,104 w/90,750 gal 28% HC1-gelled Turbine Oil mixed as follows: Each 1000 gal 28% HCl contained 48# G-5 and 6 gal C-15 (30,850 gal total). Each 1000 gal Turbine Oil contained 10 gal Enjay 8596 surfactant (59,900 gal total). Mixed Turbine Oil and 28% acid on the fly. Each 1000 gal contained 1# Iridium 192 trtd silica flour and 30# OS-160 Wide Range Unibeads and 30# OS-160 Button Unibeads distributed evenly throughout trtmt. Pmpd trtmt as follows: 73 bbls, dropped one 7/8" ball sealer, pmpd 11 bbls. Repeated one ball sealer and 11 bbls 185 times. Pmpd 42 bbls trtmt. Flushed w/4326 gal FW w/each 1000 gal containing 165# NaCl and 3 gal G-10. Max press 10,000 psi, avg 8800 psi, min 6400 psi. Max rate 8 B/M, avg 6.8 B/M, min 2.5 B/M. ISIP 5550 psi decr to 5450 psi in 5 min to 5400 psi in 10 min to 5350 psi in 15 and 20 min. Balled out. SD 8 min. Press from 9600 to 8800 psi. Lack 20 bbls flush. Started to pump. Press 9900 psi, breaking to 5400 psi. Pmpd remainder of flush. RD B-J. DEC 19 1973 Shell-Gulf-Doyle 1-10B3 (Reperf and restim)

TD 13,195. PB 13,125. Flowing. TP 3500 psi. RU OWP and ran GR log from 13,095 to 10,400. Log indicated btm zn taking trtmt. Next 13 zns no trtmt. From 12,500 to 11,030, too much radioactive material to log. Remaining zns indicated taking trtmt. RD OWP. Installed BPV. Removed 10,000# tree. Installed 5000# tree. Removed BPV. Opened well to pit. Flwd off LW. Turned to tank battery. On 13-hr test, flwd 725 BO and Turbine Oil and 221 BW (GOR 463) on 18/64" chk w/1700-1400 psi FTP. Turned over to production.

DEC 20 1973

Shell-Gulf-Doyle 1-10B3 (Reperf and restim)

TD 13,195. PB 13,125. Flowing. On 18-hr test, flwd 834 BO, no wtr and 637 MCF gas on 16/64" chk w/1500 psi FTP and zero CP.

DEC 21 1973

Shell-Gulf-Doyle 1-10B3 (Reperf and restim)

Flowing. On various tests, DEC 2 6 1973 TD 13,195. PB 13,125. flwd as follows: Rpt Date Hrs MCF Gas Chk FTP 12/22 24 320 70 277 16-26/64 1600 0 12/23 24 193 50 346 16-24/64 1700 0 12/24 7 113 26 98 16-24/64 1600 0 12/25 1 42 10 14 16-24/64 1600 0 12/26 16 191 0 89 16-24/64 1600 0

Shell-Gulf-Doyle 1-10B3 (Reperf and restim)

TD 13,195. PB 13,125. Flowing. On 24-hr test, flwd 376 BO, 20 BW and 298 MCF gas on 16-24/64" chk w/1600 psi FTP and zero CP. DEC 2.7 1973

Shell-Gulf-Doyle 1-10B3 (Reperf and restim)

TD 13,195. PB 13,125. Flowing. REPERFORATION AND RESTIMULATION COMPLETE. On 24-hr test 10/27/73, prior to work, flwd 92 BO, no wtr and 150 MCF gas (GOR 1630) on 14/64" chk w/500 psi FTP from Wasatch perfs 10,764-13,104. On 24-hr test, 12/27/73, after reperforating and restimulating, flwd 506 BO, 49 BW and 357 MCF gas (GOR 705) on 16/64" chk w/1500 psi FTP and zero CP from Wasatch perfs 10,763-13,104.

BEC 28 1973

Correction to "FR": Proposed work was to reperf and restim instead of locating and repairing tbg leak and install gas lift mandrel.

Form/	OGCC-1	b.
LOTITE	CGTC-I	D١

AC BANK TANK

Law 15

<i>(</i>)	STATE OF UTAH	SUBMIT IN TRIPLICATE			
// OIL & GAS CO	NSERVATION COMMISS	(Other instructions on reverse side)	5. LEASE DESIGNATION AND SERIAL NO.		
<u> </u>			Patented		
SUNDRY N	OTICES AND REPORTS	ON WELLS	6. IF INDIAN, ALLOTTEE OR TRIBE NAME		
	roposals to drill or to deepen or plug PLICATION FOR PERMIT-" for such				
i.	LICATION FOR PERMIT— 10F BUCK	proposais.)	7. UNIT AGREEMENT NAME		
OIL TO GAS			1. UNII AGREEMENT NAME		
WELL WELL OTHI	;R		8. FARN OR LEASE NAME		
Shell Oil Company			Doyle		
3. ADDRESS OF OPERATOR			9. WELL NO.		
1700 Broadway, Denve	r. Colorado 80202		1-10B3		
4. LOCATION OF WELL (Report locat: See also space 17 below.)	ion clearly and in accordance with an	y State requirements.*	10. FIELD AND POOL, OR WILDCAT		
At surface			Altamont		
2382' FNL and 2157'	FWL Section 10		11. SEC., T., B., M., OR BLE. AND SURVEY OR AREA		
			SE/4 NW/4 Section 10-		
			T2S-R3W		
14. PERMIT NO.	15. BLEVATIONS (Show whether I	DF, RT, GR, etc.)	12. COUNTY OR PARISH 18. STATE		
	6058 KB		Duchesne Utah		
16. Check	Appropriate Box To Indicate	Nature of Notice, Report, or	Other Data		
	NTENTION TO:		QUENT REPORT OF:		
[]	L	_	- -		
TEST WATER SHUT-OFF FRACTURE TREAT	PULL OR ALTER CASING	WATER SHUT-OFF	REPAIRING WELL		
SHOOT O& ACIDIZE	MULTIPLE COMPLETE ABANDON*	FRACTURE TREATMENT SHOUTING OR ACIDIZING	ALTERING CASING ABANDONMENT®		
REPAIR WELL	CHANGE PLANS	(Other)	ABANDONMENT		
(Other)		(NOTE: Report result	s of multiple completion on Well pletion Report and Log form.)		
	As per attachment				
	Verbal approval receiv	ved from Mr. Pat Driso	coll 7/28/75.		
		** U	ED BY DIVISION OF AS CONSERVATION		
		DATE	American Commencer		
		8Y. 22	2 STATION		
18. I hereby certify that the foregoing	is true and porrect				
SIGNED J. W. J	numel title Di	v. Opers. Engr.	DATE _7/28/75		
(This space for Federal or State	office use)				
APPROVED BY	TITLE		DATE		
CONDITIONS OF APPROVAL, I	F ANY:				

cc: U. S. Geological Survey - Salt Lake City, Utah

- of) shot(s). This operation may result in flowing some formation fluids. Therefore, if oil is produced to the surface, back-down well with heated diesel prior to pulling spent gun(s).
- c. Note and record pressure changes during and after perforating.
- 17. Acid frac perforations 11,805-13,103' with 866 bbls of gelled 7% HCl acid pumping at maximum rate as follows:
 - a. Pump 3 bbls of acid and drop two 7/8" RCN ball sealers (S.G. 1.2).
 - b. Repeat step 16a 285 times for a total of 858 bbls of acid and 572 ball sealers.
 - c. Pump 6 bbls of acid without Unibeads.
 - d. Flush with 87 bbls of produced water containing 3 gals G-10 followed w/5 bbls diesel.
 - Note: 1) All acid except last 6 bbls (refer to step 16c) to contain the following additives per 1000 gals: 12 gal G-10, 3 gal C-15, 3 gal J-22, 40# OS-160 Wide-Range Unibeads, 40# OS-160 Button Unibeads, and 3# 20-40 mesh RA sand.
 - 2) Heat all fluids to 100°F
 - 3) Place and hold 3500 psi on tubing-casing annulus.
 - 4) Pump at maximum rate while not exceeding 10,000 psi WHP.
 - 5) "Balling-out" at maximum allowable surface pressure is the object of this treatment; therefore, if "ball-out" occurs before all acid is injected into the formation, hold 10,000 psi wellhead static pressure on formation for at least 10 minutes before bleeding back. Back-flow briefly, then recommence injecting remainder of acid and ball sealers. If subsequent "ball-out" occurs, repeat the preceding sequence. Do not cut balls from acid until several complete "ball-outs" have occurred.
 - 6) Record (instantaneous) shut-down pressure decline overnight with continuous pressure recorder.
- 18. Run GR log to locate accumulations of RA sand as soon after treatment as possible.
- 19. Open well and clean-up at maximum rate on 1" choke; record flowing pressures and any shut-in pressures. Keep record of load and ball sealer recovery.
- 20. Establish flow capacity after clean-up; flow for ± 3 days.

- 1^2 . Land tubing and pressure test tubing to 7500 psi with no pressure on annulus.
- 13. Pressure test tubing 7" csg annulus to 4000 psi.
- 14. Release completion rig.
- 15. Knock out plug from Model C plug holder and chase to bottom.
- 16. Perforate one hole at each of the following depths from bottom up. Depth reference is BHCS/GR/Cal dated 2/11/73.

11 0/0	10 110	10 001	10 / 50	10 ((0	10 041
11,843	12,113	12,291	12,458	12,663	12,864
11,848	12,125	12,297	12,471	12,671	12,866
11,868	12,128	12,312	12,486	12,675	12,878
11,871	12,133	12,316	12,489	12,680	12,883
11,873	12,140	12,334	12,500	12,685	12,887
11,895	12,145	12,338	12,509	12,687	12,894
11,899	12,152	12,342	12,513	12,702	12,897
11,918	12,160	12,346	12,516	12,708	12,903
11,923	12,166	12,351	12,519	12,738	12,924
11,927	12,169	12,353	12,523	12,742	12,930
11,932	12,171	12,357	12,528	12,746	12,936
11,946	12,177	12,364	12,533	12,750	12,939
11,951	12,182	12,374	12,536	12,755	12,956
11,957	12,184	12,380	12,541	12,765	12,985
11,969	12,202	12,383	12,559	12,770	12,989
11,974	12,206	12,389	12,572	12,774	12,992
11,979	12,213	12,393	12,580	12,777	12,997
11,988	12,218	12,397	12,584	12,786	12,015
12,011	12,221	12,400	12,591	12,789	13,030
12,015	12,226	12,403	12,593	12,802	13,038
12,030	12,228	12,405	12,597	12,823	13,042
12,034	12,239	12,410	12,602	12,827	13,058
12,044	12,249	12,413	12,608	12,831	13,066
12,061	12,252	12,417	12,622	12,833	13,072
12,072	12,267	12,421	12,628	12,838	13,076
12,084	12,271	12,430	12,631	12,844	13,081
12,091	12,276	12,435	12,636	12,848	13,097
12,093	12,282	12,441	12,642	12,855	13,077
12,108	12,287	12,448	12,647	12,851	
m 1 /-1 '		170 1 1 1 1 7 1 7 1 7 1 7 1 7 1 7 1 7 1	7 ۳ و ۵۰	12,001	

Total (this job): 172 holes in 172 zones.

Grand Total (below bottom packer): 286 holes in 210 zones.

- Note: a. Perforate unidirectionally with 2" steel, hollow-carrier, throughtubing gun decentralized with magnets at top, middle, and bottom of gun assembly. Use Harrison "RT" or Schlumberger Hyperjet 6.2 gm charges.
 - b. Attempt to maintain maximum pressure differential into wellbore by bleeding off any wellhead pressure (briefly) before each (group

REMEDIAL PROGNOSIS

(SELECTIVELY TEST CLASSES I, II AND III ROCK IN LOWER FLAGSTAFF)
SHELL ET AL DOYLE 1-10B3
SECTION 10-T2S-R3W
DUCHESNE COUNTY, UTAH

PERTINENT DATA:

Elevation: 6058' KB

KB-GL: 25'

AFE NO.: 520057 SHELL'S W.I.: 92.48

TD: 13,195'
PBTD: 13,125'

7" Csg 26# CF-95 and 29# CF-95 at 10,740'

5" Liner (hanger) at 10,560'

5" Liner 18# N-80 (shoe) at 13,195'

Packer (Baker Model "D") at 10,546'

2 7/8" Tbg (Baker "C" plug holder) at 10,579'

Perforations: 10,763-13,103' (186 holes in 65 zones)

Fluid in Borehole: Water, gas and oil

CURRENT STATUS:

Cumulative production (12/19/73 - 4/30/75) 53,488 B0 + 28,140 BW (34%). Current production rate (April 1975 average) F 29 BO/D + 55 BW/D (65%), GOR 2116, GLR 732, FTP 50 psi.

PREVIOUS STIMULATION:

3/20/73 (completion) at 32,000 gal 15% HCl w/BS and Unibeads. 12/18/73 (reperf and stimulate) at 90,750 gal 28% HCl/gelled turbine oil emulsion w/BS and Unibeads.

THIS OPERATION:

- 1) Remove Baker Model "D" packer from 7" csg.
- 2) Segregate lower Flagstaff (M-3, M-4, M-5, M-6) from upper Flagstaff and Wasatch with a permanent packer in the 5" liner (upper perfs and liner lap will be "scabbed-off" by a packer in 7" casing).
- 3) Perforate Class II and III rock in the interval below the bottom packer with one hole per zone. Acid treat <u>all</u> perforations (Classes I, II and III) below lower packer to ball out conditions at 10,000 psi WHP.

PROCEDURE:

- 1. Test casing to 3500 psi with water and hold for 15 minutes. If casing leaks, another prognosis will be issued to repair leak.
- 2. RUPU. Kill well with produced water (est. present BHP gradient is ±0.433 psi/ft).

- 3. Pull 2 7/8" tubing.
- 4. Pluck Baker Model "D" packer.
- 5. Clean out 7" casing to top of 5" liner (10,560') with 4 1/8" big & 7" scraper
- 6. Clean out 5" liner to PBTD (13,125').
- 7. Set permanent retainer production packer in 5" liner on wire line at 11,780' w/packer assembly as follows:
 - (a) Baker Model 32 FAB-30 Retainer Production Packer.
 - (b) 6' mill out extension and crossover sub.
 - (c) 6' pup joint (2 7/8" N-80 EUE tubing).
 - (d) Otis "N" Nipple (2.313" Seal Bore, 2.255" No-Go).
 - (e) Baker Model "C" plug holder w/pushout plug in place.

Note: Pressure test packer assembly to 7500 psi prior to going in the hole. Shop test is fine.

- 8. Set Baker Model 85-40 F1 Permanent Retainer Production Packer on wire line in 7" casing at 10,530'.
- 9. Run production equipment as follows:
 - a. Baker Model 20 FA 30 Anchor Tubing Seal Nipple.
 - b. 2.31" ID Baker Model "L" Sliding Sleve
 - c. Approximately 1230' of 2 7/8" P-105 X-line w/crossover from EUE 8rd to X-line
 - d. 3-Baker Model 80-40 Spacer Seal Assemblies (15' of seals w/middle assembly at 10,530') w/crossover from X-line to EUE 8rd.
 - e. Approximately 10,530' of 2 7/8" N-80 EUE 8 round tubing w/gas mandrels at original placement depths.
- 10 Space out tubing string for 5000# tension.
- 11. PU enough to clear F1 packer of seal assemblies and circulate annulus w/inhibited water (heated to 100° F) as per Oil Letter #1.

- 21. Run production logs (full-bore spinner, temperature, and Gradiomanometer surveys) as follows:
 - Well should have been flowed at a stabilized rate for at least
 72 hours prior to logging.
 - b. Cut paraffin to insure tubing is clear to 7000± feet.
 - c. MI&RU Schlumberger mast, lubricator, and production logging equipment; rig up lights to permit overnight operations.
 - d. SI well and back-down with diesel to 7000± feet.
 - e. Make dummy run with Schlumberger tools of equal or greater O.D., length and weight, recording drag each 1000 feet from surface to PBTD. If excessive drag is encountered, pressure up on tubing-casing annulus to 3000 psi.
 - f. Run production combination tool, make full-bore spinner calibrations (3 up and 3 down), and check tool performance. Make SI Gradiomanometer survey.
 - g. With tool approximately 150 feet below tubing tail, open well and stabilize at rate established in step 20a.
 - h. After well has stabilized, make a minimum of one pass with temperature log, two passes with full-bore spinner (1 up, 1 down), and one pass with Gradiomanometer. Make repeat passes or stationary readings as necessary to insure valid measurements, particularly with the Gradiomanometer.
 - i. Shut in well ±4 hours and repeat full-bore spinner (1 up and 1 down pass), one pass with Gradiomanometer, and one pass with temperature log.
 - j. SI well and pull combination tool.
 - k. Shell engineer to be on location during all production logging operations. Activity will be suspended if well conditions are such that meaningful data cannot be obtained.
- 22. Open well and flow for ±4 days; shut in for BHP build-up and gradient surveys as follows:
 - a. Collect produced oil and water samples.
 - b. Shut in well in order to run bombs.
 - c. Run randem bombs and maximum recording thermometer; 10,000 psi pressure elements and 72-hour clocks; $250^{\circ}F$ thermometer.
 - d. Run pressure bombs to 12,500'.

- e. Open well and flow for four hours at a rate equal to that prior to shut in; record rates and pressures. Shut in well and backdown with ±25 bbls of heated diesel.
- f. After ±64 hours, pull pressure bombs making nine 10-minute gradient stops 13,000', 12,000', 11,000', 10,000', 8,000', 6,000', 4,000', 2,000' and in lubricator (total elapsed time from start-up of clocks should not exceed 72 hours). Record tubing and casing pressures at time of shut in and at end of survey.
- 23. Return well to production.

EDM/GEK:	зy
7/22/75	•

DIV. O.E.

J. A. Stanzione

Form	OGCC-	1 Ł	•
------	-------	-----	---

K	ST	ATE OF UTAH	SUBMIT IN TRIPLICATE (Other instructions on r		
OIL & C	GAS CONS	SERVATION COMMISS	vorue elde)	5. LEASE DESIG	
		SAND REPORTS sals to drill or to deepen or plug ATION FOR PERMIT—" for such		6. IF INDIAN, A	LLOTTEE OR TRIBE NAME
OIL X GAS WELL	OTHER			7. UNIT AGREEM	CENT NAME
2. NAME OF OPERATOR				8. FARM OR LEA	ASE NAME
Shell Oil Comp	any			Dovle	
3. ADDRESS OF OPERATOR		 		9. WELL NO.	
1700 Broadway.	Denver.	Colorado 80202		1-10B3	
4. LOCATION OF WELL (R. See also space 17 belo At surface 2382 FNL and		clearly and in accordance with an	y State requirements.*	Altamon 11. SEC., T., B., SURVEY O	M., OR BLE. AND
				T2S-R3W	Ţ
14. PERMIT NO.		15. BLEVATIONS (Show whether D	OF, RT, GR, etc.)	12. COUNTY OR	PARISH 18. STATE
		6058 1	KB	Duchesn	ne Utah
16.	Check A	ppropriate Box To Indicate I	Nature of Notice, Report, or	Other Data	
N	OTICE OF INTER	TION TO:	SUBSE	QUENT REPORT OF:	
TEST WATER SHUT-OF	-	PULL OR ALTER CASING	WATER SHUT-OFF	REPA	AIRING WELL
FRACTURE TREAT		MULTIPLE COMPLETE	FRACTURE TREATMENT	ALTE	RING CASING
SHOOT OR ACIDIZE		ABANDON*	SHOOTING OR ACIDIZING	X ABAN	DONMENT*
REPAIR WELL		CHANGE PLANS	(Other)	<u> </u>	
(Other)			(Note: Report result	ts of multiple comp	letion on Well
17. DESCRIBE PROPOSED OR	COMPLETED OPI	CRATIONS (Clearly state all pertine	nt details, and give pertinent date		

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

See attachment

18. I hereby certify that the foregoing is true and correct		-
SIGNED J. W. Fruml	TITLE Div. Opers. Engr.	DATE 007 03 1975
(This space for Federal or State office use)		
APPROVED BYCONDITIONS OF APPROVAL, IF ANY:	TITLE	DATE

cc: U. S. Geological Survey - Salt Lake City, Utah

PERF & STIMULATE			ALTAMONT
SHELL-GULF	LEASE <u>DOYLE</u>	WELL NO.	1-10B3
	DIVISION WESTERN	ELEV	6048 KB
FROM: $7/25 - 8/27/75$	COUNTY <u>DUCHESNE</u>	STATE	UTAH

UTAH	
ALTAMONT	,

Shell-Gulf-Doyle 1-10B3 (Perf & stimulate)

"FR" TD 13,195. PB 13,125. RU Hot Oil Service to press test csg. Press'd to 2200# & developed pmp trouble. Sl csg for 20 mins, csg held ok.

Shell-Gulf-Doyle 1-10B3 (Perf & stimulate)

TD 13,195. PB 13,125. Flowing. On various tests, flwd: Rept Date MCF Gas Hrs BO BWChk 7/26: 1" 24 24 34 08 0 7/27: 1" 24 23 29 80 0 7/28: 24 26 29 03 1" JUL 28 😘

Shell-Gulf-Doyle 1-10B3 (Perf & stimulate)

TD 13,195. PB 13,125. Flowing. On 24-hr test, flwd 23 BO, 20 BW, 74 MCF gas thru 1" chk w/O psi FTP.

Shell-Gulf-Doyle 1-10B3 (Perf & stimulate)

TD 13,195. PB 13,125. Flowing. On 24-hr test, flwd 27 BO, 43 BW, 84 MCF gas thru 1" chk w/O psi FTP.

Shell-Gulf-Doyle 1-10B3 (Perf & stimulate)

TD 13,195. PB 13,125. AFE #520057 provides funds to recomplete in lower zones. MI&RU Western Rig #17. $_{\rm JUL~37.1437.5}$

Shell-Gulf-Doyle 1-10B3 (Perf & stimulate)

TD 13,195. PB 13,125. Pmp'd 80 bbls prod wtr down tbg; tbg on slight vacuum. Press tested csg to 4000 psi for 1/2 hr. Press dropped to 3800. Put back press valve in donut. PU tbg & after working pipe, unlatched from pkr. Tbg under balanced. Pmp'd 70 bbls prod wtr down tbg. Pulled 1 jt tbg to get above pkr & possibly shut flapper in pkr. Circ'd 300 bbls prod wtr in reverse to clean up tbg & well. POOH. Installed back press valve in 5-1/2 donut. Removed BOP's & tbg spools. Reinstalled & tested BOP's. SI overnight.

Shell-Gulf-Doyle 1-10B3 (Perf & stimulate)

TD 13,195. PB 13,125. 8/1 MI&RU csg crew. Pulled & LD '439' 5-1/2 csg heat string. RP'MO csg crew. PU Bkr ir picker & ran in on 2-7/3 tb. Well on slight vacuum. Filled hole w/prod wtr & established circ. RU power swivel & milled over 7" pkr. Pulled 1 jt tbg & SI overnight. 8/2 POOH w/tbg, pkr picker & pkr body. Left flapper valve guide in hole; apparently broke off. PU 4-1/8 mill & csg scraper & ran in on 2-7/8 tbg. Drld up flapper valve guide on top of liner hanger 1-1/2 hrs. Ran in 2 jts tbg. SI over Sunday.

Shell-Gulf-Doyle 1-10B3 (Perf & stimulate)

TD 13,195. PB 13,125. 36-hr SITP 250 psi. Bled off to pit; all gas. Reverse circ 100 bbls prod wtr & balanced tbg & csg. RIH to 11,400'; hit something solid - apparently scale. Drld thru & dropped free for 2 jts. Hit scale again. Working way into hole w/apparent scale buildup every jt to every 3 jts tbg. The bit is now @ 11,888. SI overnight.

Shell-Gulf-Doyle 1-10B3 (Perf & stimulate)

TD 13,195. PB 13,125. Cont'd working in w/mill. CO to 13,125. Circ'd hole clean. Cut sample of cuttings & cuttings very acid soluble. SI overnight.

AUG 0 6 1975

Shell-Gulf-Doyle 1-10B3 (Perf & stimulate)

TD 13,195. PB 13,125. Pulled tbg & stopped w/tail @ 5500 & circ'd 100 bbls hot prod wtr to clean up csg. POOH.

MI&RU OWP. RIH w/5" Bkr FA pkr & set in 5" liner w/top of pkr @ 11,782. POOH. RIH w/Bkr 7" F1 pkr & set top of pkr @ 10,530. POOH. RD&MO OWP. SI overnight.

AUG 0 7 13 E

Shell-Gulf-Doyle 1-10B3 (Perf & stimulate)

TD 13,195. PB 13,125. Installed donut in AP spool & back press valve in donut. Removed BOP's. Installed tbg spool & reinstated & tested BOP's. MI&RU hydrotest. Ran in w/prod equip while hydrotesting in; had difficulty testing P105X line tbg. SI overnight.

AUG 0.8 1975

Shell-Gulf-Doyle 1-10B3 (Perf & stimulate)

TD 13,195. PB 13,125. 8/8 Ran prod equip; hydretesting in. Gas making hydrotesting difficult. SI overnight. 8/9 Fin'd rum'g prod equip; details to follow. RD&MO hydrotest. Could not test last 5000' of 2-7/8" because of slight paraffin buildup in tbg. Latched into 5" pkr & marked for spacing out. Test esg to 4000 psi, which also test seals thru 7" pkr. Unlatched from 5" pkr. Pulled up & displaced esg as per 0il Letter #1. Latched into pkr & set tbg on donut w/3000# tension. Retest esg to 4000 psi. Installed back press valve in donut. SI over Sunday.

Shell-Gulf-Doyle 1-10B3 (Perf & stimulate)

TD 13,195. PB 13,125. Remove' BOP's. Installed 10,000 psi X-mas tree. Removed back ess valve. Test tree to 10,000 psi. Released Western Rig #17. MI&RU OWP to perf 11,843-13,097 (172 holes). Perf'd unidirectionally w/2" steel hollow carrier thru tbg gun decentralized w/magnets @ top, middle & btm. Used Harrison RT charges. Run #1 press before & after perf'g 940. Perf'd @ following depths: 13,097, 13,081, 13,076, 13,072, 13,066, 13,058, 13,042, 13,038, 13,030, 12,015, 12,997, 12,992, 12,989, 12,985, 12,956, 12,939, 12,936, 12,930, 12,924, 12,903, 12,897, 12,894, 12,887, 12,883, 12,878, 12,866, 12,864, 12,861, 12,855, 12,848, 12,844, 12,838, 12,833, 12,831, 12,827 (35 holes). Run #2 - press before & after perf'g 950. Perf'd @ following depths: 12,823, 12,802, 12,789, 12,786, 12,777, 12,774, 12,770, 12,765, 12,755, 12,750, 12,746, 12,742, 12,738, 12,708, 12,702, 12,687, 12,685, 12,680, 12,675, 12,671, 12,663, 12,647, 12,642, 12,636, 12,631, 12,628, 12,622, 12,608, 12,602, 12,597, 12,593, 12,591, 12,584, 12,580, 12,572 (35 holes). Run #3 - press before & after perf'g 1010. Perf'd @ following depths: 12,559, 12,541, 12,536, 12,533, 12,528, 12,523, 12,519, 12,516, 12,513, 12,509, 12,500, 12,489, 12,486, 12,471, 12,458, 12,448, 12,441, 12,435, 12,430, 12,421, 12,417, 12,413, 12,410, 12,405, 12,403, 12,400, 12,397 (27 holes). Depth reference is BHCS/GR/Cal dated 2/11/73. SI overnight.

Shell-Gulf-Doyle 1-10B3 (Perf & stimulate)

TD 13,195. PB 13,125. 12-hr SITP 1100 psi. Bled off to 500 psi. Ran back in w/OWP & cont'd perf'g job. Run #4 press before perf'g 700 psi. Perf'd @ each of the following depths: 12,393, 12,389, 12,383, 12,380, 12,374, 12,364, 12,357, 12,353, 12,351, 12,346, 12,342, 12,338, 12,334, 12,316, 12,312, 12,297, 12,291, 12,287, 12,282, 12,276, 12,271, 12,267, 12,252, 12,249, 12,239, 12,228, 12,226, 12,221, 12,218, 12,213, 12,206, 12,202, 12,184, 12,182, 12,177, 12,171, 12,169, 12,166 (38 holes). Press after perf'g 725 psi. Run #5 - press before perf'g 730 psi. Perf'd @ each of the following depths: 12,160, 12,152, 12,145, 12,140, 12,133, 12,128, 12,125, 12,113, 12,108, 12,093, 12,091, 12,084, 12,072, 12,061, 12,044, 12,034, 12,030, 12,015, 12,011, 11,988, 11,979, 11,974, 11,969, 11,957, 11,951, 11,946, 11,932, 11,927, 11,923, 11,918, 11,899, 11,895, 11,873, 11,871, 11,868, 11,848, 11,843 (37 holes). Press after perf'g 730 psi. POOH. RD&MO OWP. MI&RU BJ Serv & AT gross perf'd interval 11,805-13,103 w/866 bbls 7% gelled acid. All acid except last 6 bbls contained the following additives per 1000 gals: 12 gals G10, 3 gals G15, 3 gals J22, 40# OS-160 Wide Range Unibeads, 40# OS-160 Button Unibeads & 3# 20-40 mesh RA sd. Pmp'd 3 bbls acid & dropped 2 7/8" RCN ball sealers (1.18 spec grav). Repeated 185 times for a total of 554 bbls acid & 370 ball sealers. Stopped inj'g ball sealers & Unibeads. Pmp'd 304 bbls acid & flushed w/79 bbls prod wtr containing 3 gals G10/1000 gals wtr. Max press 10,000, min 5600, avg 8000. Max rate 12 B/M, min 2.4, avg 12. ISIP 5500 psi, 5-10-15-min SIP 5500. ĂUG 1 3 1975

Shell-Gulf-Doyle 1-10B3 (Perf & stimulate)

ID 13,195. PB 13,125. SITP O. MI&RU OWP to run GR Tracer log. 0 SITP indicated problem w/Unibeads. MI&RU H.O.S. Pmp'd 8 bbls prod wtr down tbg. 1000 psi max press. Opened well to pit. Tbg press to 0 & well flwd about 1 bbl. Pmp'd 10 bbls prod wtr down tbg. Max press 1500. SI well. SITP to 0 in 5 mins. RD&MO H.O.S. Ran in & obtained GR Tracer log. Log generally indicated no increase in RA below 12,500 to PBTD & showed considerable AUG 14 1975 increase in RA between pkrs. RD&MO OWP. SI overnight.

Shell-Gulf-Doyle 1-10B3 (Perf & stimulate)

TD 13,195. PB 13,125. 24-hr SITP 100 psi. MI&RU Nowsco. RIH w/1" CT & inj 250 cu ft of nitrogen/min. POOH. Well flwd about 1 hr & died. RIH w/1" tbg to 7500' using 250 cu ft nitrogen/min while run'g in. 600 cu ft/min @ 7500; well appeared to be stabilizing @ about 1/2 B/M. POOH. RD&MO Nowsco. Fluid rec'd est 250 BW, 75 BO. SI overnight. AUG 15 1975

Shell-Gulf-Doyle 1-10B3 (Perf & stimulate)

TD 13,195. PB 13,125. 8/15 14-hr SITP 800#. Opened well to pit & flwd est 75 BW & 25 BO in 2-1/2 hrs, FTP 0. SI well for 5 hrs, SITP to 500 psi. Opened well to pit &flwd est 20 BO, 20 BW in 2 hrs, FTP to 0. SI overnight. 8/16 SITP 1000%. Opened well to pit & flwd est 25 BO in 2-1/2 hrs, FTP 0. SI well for 5 hrs; SITP 600. Opened well to pit & flwd est 20 BO & 30 BW in 1/2 hr, FTP to 0. SI overnight. 8/17 14-hr SITP 1300. Flwd well intermittently for 13 hrs. Well prod est 150 BO, 225 BW to pit. Well would build up to 550 psi when SI for 1 hr. SI overnight. AUG 15 1315

Shell-Gulf-Doyle 1-10B3 (Perf & stimulate)

TD 13,195. PB 13,125. 12-hr SITP 1300#. Opened well to tank battery. Well flwd 94 BO, 135 BW, 269 MCF gas in 20 hrs on 18/64" chk w/225 psi FTP. Turned well over to prod. AHG 19 107E

Shell-Gulf-Doyle 1-10B3 (Perf & stimulate)

TD 13,195. PB 13,125. Flowing. On 24-hr test, flwd 132 BO, 171 BW, 88 MCF gas thru 19/64" chk w/200 psi FTP.

Shell-Gulf-Doyle 1-10B3 (Perf & stimulate)

TD 13,195. PB 13,125. Flowing. On 24-hr test, flwd 132 BO, 171 BW, 88 MCF gas thru 19/64" chk w/200 psi FTP the 2: 145

Shell-Gulf-Doyle 1-10B3 (Perf & stimulate)

TD 13,195. PB 13,125. Flowing. On 24-hr test, flwd 102 BO, 176 BW, 255 MCF gas thru 25/64" chk w/200 psi FTP.

Shell-Gulf-Doyle 1-10B3 (Perf & stimulate)

TD 13,195. PB 13,125. Flowing. On various tests, flwd: Rept Date Hrs BO MCF Gas BWChk FTP8/23: 24 92 145 243 25/64" 150 <u>8/24:</u> 24 95 167 284 25/64" 150 8/25: 24 98 138 297 25/64" 150

AUG 8 8 1975

Shell-Gulf-Doyle 1-10B3 (Perf & stimulate)

TD 13,195. PB 13,125. Flowing. On 24-hr test 7/29/75 before work prod 27 BO, 43 BW, 84 MCF gas thru 1" chk w/O psi FTP. On 24-hr test 8/25/75 after work prod 92 BO, 143 BW, 261 MCF gas thru 25/64" chk w/150 psi FTP. FINAL REPORT

AUG 27 1975

STATE OF UTAH

SUBMIT IN TRIPLICATES

OIL & GAS CONSERVAT			5. LEASE DESIGNATION AND SERIAL NO. Patented 6. IP INDIAN, ALLOTTEE OR TRIBE NAME
(Do not use this form for proposals to dri Use "APPLICATION FO	II or to deepen or plug bank R PERMIT—" for such pro	Ck to a different reservoir.	
OIL XX GAS OTHER			7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR			8. FARM OR LEASE NAME
Shell Oil Company 3. ADDRESS OF OPERATOR			Doy1e
1700 Broadway, Denver, Colorad	lo 80202		9. WELL NO.
4. LOCATION OF WELL (Report location clearly and See also space 17 below.)	in accordance with any Si	ate requirements.*	1-10B3 10. FIELD AND FOOL, OR WILDCAT
At surface	10		Altamont
2382' FNL and 2157' FWL Section	n 10		11. SEC., T., R., M., OR BLE. AND SURVEY OR AREA
			SE/4 NW/4 Section 10- T2S-R3W
14. PERMIT NO. 15. BLEV.	ATIONS (Show whether DF, R'	T, QR, etc.)	12. COUNTY OR PARISH 18. STATE
	60 4 8 KB		Duchesne Utah
16. Check Appropriate	Box To Indicate Nat	ture of Notice, Report, or C	Other Data
NOTICE OF INTENTION TO:	1		UENT REPORT OF:
TEST WATER SHUT-OFF PULL OR AL	TER CASING	WATER SHUT-OFF	REPAIRING WELL
FRACTURE TREAT MULTIPLE C SHOOT OR ACIDIZE Y ABANDON*	OMPLETE	FRACTURE TREATMENT	ALTERING CASING
REPAIR WELL CHANGE PLA	NS -	SHOOTING OR ACIDIZING X	ABANDONMENT*
(Other)		(Other)(Note: Report results	of multiple completion on Well etion Report and Log form.)
NOV 28 1975	See attachment	DATE: Nov.	THE DIVISION OF DIVING
18. I hereby certify that the foregoing is true and considered the foregoing is true	<i>[]</i>	Opers. Engr.	DATE
cc: USGS w/attachment			

ALTAMONT ACID TREAT **LEASE** WELL NO. SHELL-GULF 1-10B3 DOYLE 6048 KB DIVISION ELEV WESTERN UTAH FROM: COUNTY DUCHESNE STATE 10/9/75 - 11/26/75

UTAH

ALTAMONT

Shell-Gulf-Doyle 1-10B3 (AT)

"FR" TD 13,195. PB 13,125. Tbg press 600 psi. MI&RU Nowsco 1" CTU & BJ Serv to spt 24 bbls double-inh d 15% HCl acid on btm. Started run'g CT & hit gas lift mandrel @ 8977. POOH & put on centralizer. Started back in hole & could not pass thru gas lift mandrel @ 10,439. POOH & RD Nowsco. Shut in well w/O psi tbg press. RU BJ Serv to bullhead 34 bbls wt'd gelled 15% HCl acid to btm followed by 58 bbls prod wtr. Wt'd acid contained the following per 1000 gals: 4000# CaC12, 50# G26, 8 gals C15, 25 gals A5 & 3 gals J22. Max rate 4 B/M @ 4000 psi. Allowed acid to set on btm for 3 hrs & cont'd w/AT. RU BJ Serv to AT perfs 11,805-13,104 w/560 bbls gelled 7% HCl acid as follows: Placed 3500 psi on thg-csg annulus. Pmp'd I bbl acid & dropped 1 7/8 RCN ball sealer (sp gr 1.2) & after each 5 bbls dropped 1 add'1 ball. Repeated step 199 times for a total of 200 bbls acid & 240 ball sealers. Pmp'd 2 bbls acid & dropped 1 7/8" RCN ball sealer (sp gr 1.2) & dropped 1 add'1 ball every 20 bbls. Repeated step 175 times for a total of 350 bbls & 192 ball sealers. Remainder of trimt according to prog & acid made up according to prog. Ball out did occur during trtmt @ 635 bbls fluid in hole. Max rate 16.5 B/M, min 14.5, avg 15. Max press 10,000 psi. min 6000, avg 7700. ISIP 6200 psi. After 5 mins 5800 psi, 10 mins 5700 psi, 15 mins 5500 psi. RD&MO BJ Serv. Start tbg press 300 psi. MI&RU OWP to run GR to detect RA sd accumulation. RD&MO OWP. SI well; SITP 150 psi.

OCT 09 1975

Shell-Gulf-Doyle 1-10B3 (AT)

OCT 10 1975

TD 13,195. PB 13,125. Tbg press - vacuum. Attempted flw back & well on vacuum. Ran WL to 9000' to make sure tbg was open. Tbg was clear. RU Nowsco to pmp nitrogen down tbg. Pmp'd nitrogen down tbg & SI well for night to flw back on 10/10. Press'd tbg w/Nowsco to 4050 psi.

Shell-Gulf-Doyle 1-10B3 (AT) OCT 13 1975

TD 13,195. PB 13,125. 10/10: Tbg press 2750 psi. Bled to 0 psi in 1 h4. Swabbed approx 30 bbls (mostly water). Well still dead. Pmpd 75 bbls produced water down tbg. SI overnight. 10/11: Rig up Nowsco and treated to 9000'. pmpd in 70 bbls of diesel. Closed well in.

Shell-Gulf-Doyle 1-10B3 TD 13,195. PB 13,125. S.I. 367 14 15/3 (AT)

Shell-Gulf-Doyle 1-10B3 TD 13,195. PB 13,125. S.I. 00T 15 1875 (AT)

Shell-Gulf-Doyle 1-10B3 TD 13,195. PB 13,125. S.I. WET 1 6 1975 (AT)

Shell-Gulf-Doyle 1-10B3 TD 13,195. PB 13,125. Flowing. On 22 hrs test (AT) JOT 17 1975 flwd 74 BO, 1 BW, 95 MCF Gas on 62/64" chk - 500 FTP.

Shell-Gulf-Doyle 1-10B3 TD 13,195. PB 13,125. SI. 10/17 Start tbg press 500 psi. (AT) Flwd well & prod approx 22 BO in 1-1/2 hrs. Well died. RU Nowsco & ran to 13,000' to jet nitrogen. Started in hole pmp'g 400 CFM nitrogen. Made steps @ 5000', 10,000' & 12,000' & jetted hole dry. Total returns approx 80 BW. Went to 13,000' @ 600 CFM & got trace of wtr returns. Jetted hole dry. Total returns on job 30 BO, 85 BW. SI well w/100# press. 10/18 tbg press 800 psi. Flwd approx 10 bbls fluid & died. Repeated, SI & flwd back w/no success of flow. SI.

Shell-Gulf-Doyle 1-10B3 TD 13,195. PB 13,125. Flowing. On 7-hr test, flwd 0 BO, O BW, 19 MCF gas thru 20/64" chk w#O psi FTP. 1975 (AT)

OCT 2 0 1975

Shell-Gulf-Doyle 1-10B3 TD 13,195. PB 13,125. Flowing. On 7-hr test, flwd 23 BO, O BW, 84 MCF gas thru 20/64" chk w/50 psi FTP. (AT)

Shell-Gulf-Doyle 1-10B3 TD 13,195. PB 13,125. Flowing. On 6-hr test, flwd 31 BO, 0 BW, 41 MCF gas thru 20/64" chk w/50 psi FTP.OCT 23 1975 (AT)

TD 13,195. PB 13,125. Flowing. On 6-hr test, flwd 16 Shell-Gulf-Doyle 1-10B3 BO. O BW, 39 MCF gas thru 20/64" chk w/50 psi FTP. ncr 24 1975 (AT) Shell-Gulf-Doyle 1-10B3 TD 13,195. PB 13,125. Flowing. On various tests, flwd: (AT) Rept Date Hrs BO MCF Gas BW Chk FTP 10/25: 24 20 0 39 20/64" 50 10/26: SI OCT 27 1975 10/27: SI TD 13,195. PB 13,125. Flowing. On 6-hr test, flwd 22 Shell-Gulf-Doyle 1-10B3 BO, 1 BW, 38 MCF gas thru 20/64" chk w/50 psi FTP. (AT) TD 13,195. PB 13,125. SI to build press. OCT 29 1975 Shell-Gulf-Doyle 1-10B3 (AT) Shell-Gulf-Doyle 1-10B3 TD 13,195. PB 13,125. SI to build press. (AT) OCT 30 1975 Shell-Gulf-Doyle 1-10B3 TD 13,195. PB 13,125. Flowing. On 24-hr test, flwd 40 BO, 0 BW, 40 MCF gas thru 20/64" chk w/50 psi FTP. act 31 1975 (AT) Shell-Gulf-Doyle 1-10B3 TD 13,195. PB 13,125. Flowing. On various tests, flwd: (TA) Rept Date Hrs BO BWMCF Gas Chk FTP 11/1: SI 11/2: 24 16 0 39 20/64" 50 11/3: SI to build press NOV 0 3 1975 TD 13,195. PB 13,125. Flowing. On 8-hr test, flwd 16 BO, Shell-Gulf-Doyle 1-10B3 0 BW. 46 MCF gas thru 20/64" chk w/50 psi FTP. (AT) NOV 0 4 1975 TD 13,195. PB 13,125. Flowing. On 24-hr test, flwd 12 Shell-Gulf-Doyle 1-10B3 BO, O BW, 39 MCF gas thru 20/64" chk w/50 psi FTP.... 05 1975 (AT) TD 13,195. PB 13,125. SI to build press. ાં કે છી. Shell-Gulf-Doyle 1-10B3 (AT) Shell-Gulf-Doyle 1-10B3 TD 13,195. PB 13,125. Flowing. On 6-hr test, flwd 10 BO, 0 BW, 39 MCF gas thru 30/64" chk w/0 psi FTP_{NOV 0 7 1975} (AT) Shell-Gulf-Doyle 1-10B3 TD 13,195. PB 13,125. Flowing. On various tests, flwd: (AT) NOV 10 1915 Rept Date Hrs BO BWMCF Gas Chk FIE 11/8 8 14 0 43 30/64" 50 11/9 24 9 0 38 20/64" 53 11/10 Shut in to build pressure.

Shell-Gulf-Doyle 1-10B3 TD 13,195. PB 13,125. Flowing. On 8-hr test, flwd 13 (AT) BO, O BW, 38 MCF gas thru 20/64" chk w/50 psi FTP 11 1975 Shell-Gulf-Doyle 1-10B3 TD 13,195. PB 13,125. Flowing. On 8-hr test, flwd 9 BO, 0 BW, 38 MCF gas thru 20/64" chk w/50 psi FTP. NOV 12 1975 Shell-Gulf-Doyle 1-10B3 TD 13,195. PB 13,125. Flowing. On 8-br test, flwd 4 BO, 0 BW, 24 MCF gas thru 15/64" chk w/50 psi FTP. (AT) Shell-Culf-Doyle 1-10E3 TD 13,195. PB 13,125. SI to build press. (AT) NOV 1 4 1975 Shell-Gulf-Doyle 1-10B3 TD 13,195. PB 13,125. Flowing. On various tests, flwd: (AT) Rept Date Hrs BOBWMCF Gas Chk 11/15: SI 11/16: 24 10 0 38 20/64" 11/17: SI to build press NOV 1 7 1975. Shell-Gulf-Doyle 1-10B3 TD 13,195. PB 13,125. SI to build press. (AT) NOV 18 1975 Shell-Gulf-Doyle 1-10B3 TD 13,195. PB 13,125. Flowing. On 6-hr test, flwd 26 (AT) BO, O BW, 61 MCF gas thru 20/64" chk w/100 psi FTP. (24-hr rate is 104 BO, 0 BW & approx 244 MCF gas) Shell-Gulf-Doyle 1-10B3 TD 13,195. PB 13,125. Flowing. On 7-hr test, flwd 4 (AT) BO, 0 BW, 21 MCF gas thru 20/64" chk w/0 psi FTP. (24-hr rate is 13.6 BO, 0 BW, 71.4 MCF gas) NOV 20 1975 Shell-Gulf-Doyle 1-10B3 TD 13,195. PB 13,125. Flowing. On 24-hr test, flwd 12 (AT) BO, 0 BW, 21 MCF gas thru 30/64" chk w/100 psi FTP. NOV 21 1975 Shell-Gulf-Doyle 1-10B3 TD 13,195. PB 13,125. Flowing. On various tests, flwd: (AT) Rept Date Hrs BOMCF Gas BWChk 11/22: 24 6 0 17 30/64" 100 11/23: SI to build press 11/24: 17 15/64" 50 (24-hr rate 28 EO, 0 BW, 68 MCF gas) NOV 2 4 1975

Shell-Gulf-Doyle 1-10B3 (AT)

TD 13,195. PB 13,125. Flowing. On 6-hr test, flwd 8
BO, 0 BW, 17 MCF gas thru 15/64" chk w/50 psi FTP.

(24-hr rate 32 BO, 0 BW, 68 MCF gas)

NOV 2 5 1375

Shell-Gulf-Doyle 1-10B3 (AT)

TD 13,195. PB 13,125. AT COMPLETE. On 24-hr test 10/1/75 before work, prod 24 BO, O BW, 89 MCF gas thru 42/64" chk w/100 psi FTP. On 24-hr test 11/26/75 after work, prod 36 BO, O BW, 60 MCF gas thru 15/64" chk w/50 psi FTP.

FINAL REPORT

NOV 2 6 13/5

SHOOT OR ACIDIZE

	STA	TE OF UTAH	SUBMIT IN TRIPLICATE.		
-	OIL & GAS CONS	ERVATION COMMISSION	(Other Instructions on reverse side)	5. LEASE DESIGNATION Patented	AND SERIAL NO.
	(Do not use this form for propos	CES AND REPORTS ON alls to drill or to deepen or plug back to the total to the total		6. IF INDIAN, ALLOTTE	B OR TRIBE NAME
1.	OIL GAS OTHER			7. UNIT AGREEMBNT NA	МВ
2.	NAME OF OPERATOR			8. FARM OR LEASE NAM	(18)
	Shell Oil Company			Dov1e	
8.	ADDRESS OF OPERATOR		9. WELL NO.		
	1700 Broadway, Denver,	Colorado 80202		1-10B3	
4.	LOCATION OF WELL (Report location cle See also space 17 below.) At surface	early and in accordance with any State	requirements.*	10. FIELD AND POOL, OF	R WILDCAT
	2382' FNL & 2157' FWL S	ection 10		Altamont 11. sec., T., R., M., OR B SURVEY OR ARMA	
				SE/4 NW/4 Se	ection 10-
14.	PERMIT NO.	15. BLEVATIONS (Show whether DF, RT, G		T2S-R3W	
			R, etc. j	12. COUNTY OR PARISH	18. STATE
		6048 KB	P	Duchesne	Utah
16.	Check App	propriate Box To Indicate Nature	e of Notice, Report, or O	ither Data	
٠	NOTICE OF INTENT			ENT REPORT OF:	
		LL OR ALTER CASING	WATER SHUT-OFF FRACTURE TREATMENT	REFAIRING W	

(Other) Install gas lift equip X (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

ABANDONMENT*

Install gas lift equip

See attachment

ABANDON*

CHANGE PLANS

conditions of APPROVAL, IF ANY: cc: USGS w/attachment

· INSTAL	GAS LIFT EQUIP				
SHELL-	GULF	LEASE	DOYLE		ALTAMONT
				WELL NO	1-10B3
FROM:	7/16 - 8/2/76	DIVISION _	WESTERN	ELEV	6048 KB
	.720 0/2//0	COUNTY	DUCHESNE	STATE	UTAH

UTAH ALTAMONT

Shell-Gulf-Doyle 1-10B3 (Install gas lift equip)

"FR" TD 13,195. PB 13,125. AFE #419834 provides funds to equip well for gas lift. Well was SI w/O TP. Cut wax to 3350; could not get thru plug. Filled tbg w/diesel & SI well. 7/15 RU Nowsco & pmp'd diesel @ 1/2 B/M down to 3550 & hit hard wax plug. Jet'd on plug & got down to 4280. Pulled tbg. SD for night.

JUL † 6 1976

Shell-Gulf-Doyle 1-10B3 (Install gas lift equip)

TD 13,195. PB 13,125. SIP 0. Washed to 4360'. POOH, then washed to 4800'. Got thru plug @ 4800' & well started flw'g w/1000 psi on a 64/64 chk. Flwd 45 mins & died. Pulled Nowsco & backed well down w/20 bbls diesel. SI well for night. 7/17 SIP 1200 psi. Ran to 8936' to get collar stop. Had difficulty; pulled stop @ 4:30 p.m. Prep to run valves. SI well.

JUL 19 1978

Shell-Gulf-Doyle 1-10B3 (Install gas lift equip)

TD 13,195. PB 13.125. SITP 1200 psi. Pulled btm 2 dummy valves and tbg & csg press did not equalize. Pulled #3 valve & press started to equalize. Plug betwn 8977' & 9693'. Pulled rest of valves.

JUL 20 1976

Shell-Gulf-Doyle 1-10B3 (Install gas lift equip)

TD 13,195. PB 13,125. SIP 1000 psi. Ran valves. Left btm valve out. Circ'd 60 BW down @ 300 psi to clean plug out of csg. Ran last valve & pulled collar stop.

JUL 2 1 1976

Shell-Gulf-Doyle 1-10B3 (Install gas lift equip)

TD 13,195. PB 13,125. SIP 700 psi; bled to 0 in 30 mins. Inj'd gas to gas lift. Well flw'g to bty. Turned over to prod.

JUL 22 1976

Shell-Gulf-Doyle 1-10B3 (Install gas lift equip)

TD 13,195. PB 13,125. On 24 hr test, prod 213 BO, 871 BW, 365 MCF gas w/1300 psi. JUL 231973

Shell-Gulf-Doyle 1-10B3	TD 13,195.	PB	13,125.	On	various t	ests prod:
(Install gas lift equip)	Rept Date	Hrs	BO	BW	MCF Gas	FTP
JUL 26 1976	7/24	24	49	434	447	150
305 58 1976	7/25	24	162	434	494	150
	7/26	24	131	446	620	200

Shell-Gulf-Doyle 1-10B3 TD 13,195. PB 13,125. On 24 or test 101 BO, 371 BW, (Install gas lift equip) 482 MCF Gas w/200 FTP. JUL 27 1976

Shell-Gulf Doyle 1-10B3 TD 13,195. PB 13,125. On 24 hr test 189 BO, 463 BW, (Install gas lift equip) 578 MCF Gas w/300 FTP. JUL 28 1976

Shell-Gulf Doyle 1-10B3 TD 13,195. PB 13,125. On 24 hr test 235 BO, 484 BW, (Install gas lift equip) 578 MCF Gas w/400 FTP. JUL 29 1976

Shell-Gulf Doyle 1-10B3 TD 13,195. PB 13,125. On 24 hr test 237 BO, 435 BW, (Install gas lift equip) 620 MCF Gas w/300 FTP. JUL 3 0 1976

Shell-Gulf-Doyle 1-10B3 TD 13,195. PB 13,125. On 24-hr test 6/22 before work, prod (Install gas lift equip) 0 BO, 0 BW, 0 MCF gas. On 24-hr test dated 8/2 after work, prod 263 BO, 180 BW, 899 MCF gas w/300 psi. AUG 0 2 1975

STATE OF UTAH DEPARTMENT OF NATURAL RESOURCES

SUBMIT ARIPLICATE*
(Other cructions on reverse side)

OIL DIL COMPANY SHELL DIL COMPANY ADDRESS OF OPERATOR P.D. Box 831 Houston. Tx 77001 ATTN: P.G. Grung fm. L4461 Welk Location of well (Report location clearly and in accordance with any State requirements.* Location of well (Report location clearly and in accordance with any State requirements.* 2 382 FNL 7 ZIS7 FWL S68. /0 16. PERMIT NO. 16. BLEVATIONS (Show whether DF, RT, GR, etc.) LOCH 8 KB DUCHESNE LITAL DUCHESNE LITAL DUCHESNE LITAL DUCHESNE LITAL	DI	VISION OF OIL, GAS, AND	MINING	5. LEASE DESIGNATION AND SERIAL NO.
SUNDEY NOTICES AND REPORTS ON WELLS (Do sol use this form for proposals to drill to deeped or pile back to a different reservoir. WILL SOL WARLED OTHER TARROT GRAND OTHER TARROT GRAND TARROT GRAND TARROT GRAND TO STAND OTHER				
THE OF OF THE PROPERTY AND SERVICE OF THE STATE OF UTTAN WILL PROPERTY OF THE STATE OF UTTAN WILL PROPERTY OF THE STATE OF UTTAN OF	SUNDRY N (Do not use this form for Use "AP	OTICES AND REPORT proposals to drill or to deepen or publication for PERMIT—" for su	S ON WELLS lug back to a different reservoir.	6. IF INDIAN, ALLOTTER OR TRIBE NAME
P.D. Gov 831 Houston Trool Attribute State Plans P.D. Gov 831 Houston Trool Attribute State with any fluid requirements.* P.D. Gov 831 Houston Trool Attribute State with any fluid requirements.* P. Be also space 17 below? A LOCATION OF WILL (Report location State) and in accordance with any fluid requirements.* In state of organization of the property of the state of the property of th	I			7. UNIT AGREEMBNT NAME
Shell Oil Omany 72.0 Co. 83 Noustant 77001 ATTIVE Genue and Life we shall be contained with any State requirements. 1. Location of wells (Report location Startly and in accordance with any State requirements.) 1. Location of wells (Report location Startly and in accordance with any State requirements.) 1. Location of Wells (Report location Startly and in accordance with any State requirements.) 1. Location of Wells (Report location Startly and in accordance with any State requirements.) 1. Location of Wells (Report location Startly and in accordance with any State requirements.) 1. Location of Wells (Report location Startly and in accordance with any State requirements.) 1. Location of Wells (Report location Startly Cashy) 1. Locat	WELL LE WELL L. OTE	IBR		S TARM OR LEASE NAME
A STANDARY OF ORBACON P.O. COAR 63 HOLLSTORE TATOO! ATTIVITY G. SELLING EARTHOUGH LOOK LOCATION OF WELL RESPONDED COSTION Gleenly and in accordance with any state requirements. A SUPPLY CASHELT FO. 18. BLEVATIONS (Show whether Dr. M. of A.) 19. COUNT OR PALIER 13. FORT. 19	2, NAME OF OPERATOR			
P.O. Sox 831 Nources Transcol Attrices and a secondary with any flat requirements. 1. December of well, Report location delearly and in secondary with any flat requirements. At surface of the control of which are control with any flat requirements. 2 382 FALL T 2157 FML S6t. 0 11. BERTATIONS (Show whether BY, ET, OR, oth.) 12. PREMIT BO. 13. COUNTY OR PALLER [3]. STATE CHOCK Appropriate Box To Indicate Nature of Notice, Report, or Other Data SUBSECUENT REPORT OF THE STATE CHOCK Appropriate Box To Indicate Nature of Notice, Report, or Other Data SUBSECUENT REPORT OF THE STATE CHOCK Appropriate Box To Indicate Nature of Notice, Report, or Other Data SUBSECUENT REPORT OF THE STATE CHOCK Appropriate Box To Indicate Nature of Notice, Report, or Other Data SUBSECUENT REPORT OF THE STATE CHOCK THAN SUBJECT TRANSPORT OF THE STATE OF ULTARY OF ULTARY OF THE STATE OF ULTARY OF		ANY		
DEED ATTACHED APPROVED BY THE STATE OF UTAH DIVISION OF OIL, GAS, AND MINING DATE: APPROVED BY THE STATE OF UTAH DIVISION OF OIL, GAS, AND MINING DATE: APPROVED BY THE STATE OF UTAH DIVISION OF OIL, GAS, AND MINING DATE: APPROVED BY THE STATE OF UTAH DIVISION OF OIL, GAS, AND MINING DATE: APPROVED BY THE STATE OF UTAH DIVISION OF OIL, GAS, AND MINING DATE: APPROVED BY THE STATE OF UTAH DIVISION OF OIL, GAS, AND MINING DATE: BIOMED APPROVED BY THE STATE OF UTAH DIVISION OF OIL, GAS, AND MINING DATE: TITLE STAPP 7200. ENGINEERS THE STATE OF UTAH DIVISION OF OIL, GAS, AND MINING DATE: THE STATE OF UTAH DIVISION OF OIL, GAS, AND MINING DATE: THE STATE OF UTAH DIVISION OF OIL, GAS, AND MINING DATE: THE STATE OF UTAH DIVISION OF OIL, GAS, AND MINING DATE: THE STATE OF UTAH DIVISION OF OIL, GAS, AND MINING DATE: THE STATE OF UTAH DIVISION OF OIL, GAS, AND MINING DATE: THE STATE OF UTAH DIVISION OF OIL, GAS, AND MINING DATE: THE STATE OF UTAH DIVISION OF OIL, GAS, AND MINING DATE: THE STATE OF UTAH DIVISION OF OIL, GAS, AND MINING DATE: THE STATE OF UTAH DIVISION OF OIL, GAS, AND MINING DATE: THE STATE OF UTAH DIVISION OF OIL, GAS, AND MINING DATE: THE STAPP 7200. ENGINEERS THE STATE OF UTAH DIVISION OF OIL STATE OF UTAH DIVISION OF UTAH		T. T. DOS A ATT PA	Garriso en Al-Ula 120 h	1-1063
ACTAILDS 2 382' FNL > ZIS7' FWL S68. 10 11. SEC. 7. J.	4. LOCATION OF WELL (Report loca	tion clearly and in accordance with	any State requirements.	
16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data Notice of Interview to to: THET WATER SHUT-OFF PRACTURE TREAT SHOTO OR ACTIONE CARRING CHARGE PLANS (Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data NOTICE OF INTERVIEW TO TO: THET WATER SHUT-OFF PRACTURE TREAT SHOTO OR ACTIONE ARRING CHARGE PLANS (Cher) THE TWATER SHUT-OFF PRACTURE TREAT SHOTO OR ACTIONE ARRING CHARGE PLANS (Cher) TO PRECEDE TREAT SHOTO OR ACTIONE OR CHARLETTO OPPRATIONS (Cherily state all pertinent defails, and give principle on on Weal (Note) TO PRECEDE TREAT OF UTAH DIVISION OF OIL, GAS, AND MINING DATE: THE TREATMENT ARRINGS DIVISION OF OIL, GAS, AND MINING DATE: THE TREATMENT ARRINGS DIVISION OF OIL, GAS, AND MINING DATE: THE TREATMENT ARRINGS TITLE TREATMENT TITLE DATE DATE DATE DATE	Bee also space 17 below.)			ALTAMONT
18. ELYATON (BAOW Whether Dr. Nr. OR. ofc.) (C) Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data NOTICE OF INTERFECT TO: THEY WATER SHUT-OFF PRACTURE TREAT BHOOT OR ACTURED BY WATER CHIEF COMPLETE BHOOT OR ACTURED BHOOTH OR OR CHIEFIEL (CHANGE PLANS (CHANGE PLA	2382 FNL	- 2157 FWL 360	10	11. SBC., T., R., M., OR BLK. AND SURVEY OR ARBA
18. ELYATON (BAOW Whether Dr. Nr. OR. ofc.) (C) Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data NOTICE OF INTERFECT TO: THEY WATER SHUT-OFF PRACTURE TREAT BHOOT OR ACTURED BY WATER CHIEF COMPLETE BHOOT OR ACTURED BHOOTH OR OR CHIEFIEL (CHANGE PLANS (CHANGE PLA				
Check Appropriate Box To Indicate Notice, Report, or Other Data NOTICE OF INTERFEION TO: TEST WATER SHUT-OFF PRACTURE TREAT SHOOT OS ACTUBER				
Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: TREET WATER SHOT-OFF POLL OR ALTER CARING MELTIFLE COMPLETE ARRANDON* REPAIR WELL CHANGE PLANS CHANGE CARRIED ALL PLANS CHANGE PLANS CHANGE PLANS CHANGE PLANS CHANGE CARRIED ALL PLANS CHANGE PLANS CHANGE PLANS CHANGE PLANS CHANGE CARRIED ALL PLANS CHANGE PLANS CHANGE PLANS CHANGE PLANS CHANGE CARRIED ALL PLANS CHANGE PLANS CHANGE PLANS CHANGE PLANS CHANGE CARRIED ALL PLANS CHANGE PLANS CHANGE PLANS CHANGE PLANS CHANGE CARRIED ALL PLANS CHANGE PLANS CHANGE PLANS CHANGE PLANS CHANGE CARRIED ALL PLANS CHANGE PLANS CHANGE PLANS CHANGE PLANS CHANGE CARRIED ALL PLANS CHANGE PLANS CHANGE PLANS CHANGE PLANS CHANGE CARRIED ALL PLANS CHANGE PLANS CHANGE PLANS CHANGE PLANS CHANGE CARRIED CHANGE PLANS	14. PERMIT NO.		er DF, RT, GR, etc.)	
NOTICE OF INTENTION TO: TEST WATER SHUT-OFF PRACTURE TREAT SHOOT OR ACIDIER ADARDON'S CHANGE PLANS (Other)				
PULL OR ALTER CARING PRACTURE TREAT SHOOT OR ACIDIZE SEPARA MULTIPLE COMPLETE ANAMON'S SEPARATE ANAMON'S CHANGE PLANS SHOOTING OR ACIDIENG APPROVED BY CHANGE PLANS CHANGE PLANS CHANGE PLANS CHANGE PLANS CHANGE PLANS CHANGE PLANS SHOOTING OR ACIDIENG APPROVED BY THE STATE OF UTAH DIVISION OF OIL, GAS, AND MINING DATE:	16. Chec	k Appropriate Box To Indica	te Nature of Notice, Report, o	or Other Data
PRACTURE TREATMENT SHOOT OR ACIDIES REPAIR WILL CHANGE PLANS ABARDON** ABARDON** ABARDON** CHANGE PLANS CHANGE PLANS CHANGE PLANS CHANGE PLANS ABARDON** ABARDON** ABARDON** CHANGE PLANS CHANGE PLANS CHANGE PLANS ABARDON** ABARD	NOTICE OF	INTENTION TO:	#UBI	SEQUENT REPORT OF:
PRACTURE TREAT SHOOT OR ACTIDE REPAIR WELL (Other) 17. DESCRIBE PROPOSER OR COMPLETED OPERATIONS (Clearly state all) pertinent details, and give pertinent dates, including estimated date of starting an proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and some pertinent to this work.) APPROVED BY THE STATE OF UTAH DIVISION OF OIL, GAS, AND MINING DATE: 18. I Agreby certify that the foregoing is true and correct SIGNED Market of Pederal or State office use) (This space for Federal or State office use) APPROVED BY TITLE DATE	TEST WATER SHUT-OFF	PULL OR ALTER CASING	WATER SHUT-OFF	REPAIRING WELL
BEPAIR WELL (Other) (Note: Report results of multiple completion on Well (Other) (Other) (Other) (Note: Report results of multiple completion on Well (Other) (Other) (Other) (Note: Report results of multiple completion on Well (Other) (Other) (Note: Report results of multiple completion on Well (Other) (Note: Report results of multiple completion on Well (Other) (Note: Report results of multiple completion on Well (Other) (Note: Report results of multiple completion on Well (Other) (Note: Report results of multiple completion on Well (Other) (Note: Report results of multiple completion on Well (Other) (Note: Report results of multiple completion on Well (Other) (Other) (Note: Report results of existing and served and true vertical depths for salt of starting and served and true vertical depths for salt of starting and served and true vertical depths for salt of starting and served and true vertical depths for salt of starting and served and true vertical depths for salt of starting and served and true vertical depths for salt of sa		MULTIPLE COMPLETE	FRACTURE TREATMENT	ALTERING CASING
(Other) (Ot	SHOOT OR ACIDIZE	ABANDON*	SHOOTING OR ACIDIZING	ABANDONMENT*
JUN 2 APPROVED BY THE STATE OF UTAH DIVISION OF OIL, GAS, AND MINING DATE: BY: MINING DATE: TITLE TITLE PATE TITLE DATE Clearly state all pertinent details, and give pertinent dates, including estimated date of starting an proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and sones pertinent to this work.) **TITLE STAPP PROVED BY THE STATE OF UTAH DIVISION OF OIL, GAS, AND MINING DATE: ### Collaboration of the propertine of the theorem of the properties of t	REPAIR WELL	CHANGE PLANS	(Other)	when of multiple completion on Well
APPROVED BY THE STATE OF UTAH DIVISION OF OIL, GAS, AND MINING DATE: BY: MICH. March. TITLE STAPP PROCE DATE JUN 2 DIVISION OF OIL, GAS & M. V.I DIVISION OF OIL, GAS & M. V.I DIVISION OF OIL, GAS & M. V.I TITLE STAPP PROC. EMSINGER DATE DATE DATE DATE			Completion or Reco	ompletion Report and Log form.)
APPROVED BY THE STATE OF UTAH DIVISION OF OIL, GAS, AND MINING DATE: BY: BY: MINING DATE: TITLE STAPP PROD. ENGINGE DATE				
APPROVED BY THE STATE OF UTAH DIVISION OF OIL, GAS, AND MINING DATE: BY: BY: MINING DATE: TITLE STAPP PROD. ENGINGE DATE				
APPROVED BY THE STATE OF UTAH DIVISION OF OIL, GAS, AND MINING DATE: BY: BY: MINING DATE: TITLE STAPP PROD. ENGINGE DATE				;
APPROVED BY THE STATE OF UTAH DIVISION OF OIL, GAS, AND MINING DATE: 6-30-8/ BY: M.C. Mulling 18. I hereby certify that the foregoing is true and correct SIGNED No. 1 AMBLE TITLE STAFF 7200. ENGINGE2 (This space for Federal or State office use) APPROVED BY		SEE ATTI	Janeo . 1	UN 2 %
APPROVED BY THE STATE OF UTAH DIVISION OF OIL, GAS, AND MINING DATE: 6-30-8/ BY: M.C. Mulling 18. I hereby certify that the foregoing is true and correct SIGNED No. 1 AMBLE TITLE STAFF 7200. ENGINGE2 (This space for Federal or State office use) APPROVED BY				DIMICION OF
18. I hereby certify that the foregoing is true and correct BIGNED N-1. Plus D.A. LAMBIE TITLE STAPF 7200. ENGINGEL DATE 6-/6-81 (This space for Federal or State office use) APPROVED BY	OF OIL	UTAH DIVISION O , GAS, AND MININ 6 -30 -8/	NTE OIL F G	LIGAS & MITTIC
(This space for Federal or State office use) APPROVED BY	BY:	oing is true and correct		6-/4-81
APPROVED BY DATE			77A., 7 CON COUNTY	DATE - U
ALLEGATION DI	(This space for Federal or St	ate omce use)		
				DATE

REMEDIAL PROGNOSIS DOYLE 1-10B3 SECTION 10, T2S, R3W ALTAMONT FIELD, UTAH

Pertinent Data:

Shell's share: 93.75%

60481 Elevation (KB): 60331 Elevation (GL):

TD: 13195'

13125' PBTD:

13-3/8", 68#, K-55 to 306'; 9-5/8", 40#, K-55 to 6200'; 7", 26#, CF-95 Casing:

to 10740'.

5", 18#, N-80; top at 10577', bottom at 13195' Liner:

2-7/8", EUE, 6.5#, N-80 to 10,530' 7" Baker Model "D" at 10,530' Tubing: Packer:

Perforations: 10,763'-13104' (358 holes)

Artificial Lift: Gas lift.

CO, perforate, and stimulate the Wasatch. Objective:

Procedure:

- MIRU. Load hole with clean produced water. Remove tree. Install and test 1. BOPE as per field specs.
- Pull tubing and seals, laying down gas lift mandrels while coming out. 2.
- RIH and mill out Baker 7" Model "D" at 10,530'. CO 5" liner to 13,125' (PBTD). 3.
- Rig up perforators with lubricator (tested to 3000 psi) and perforate as 4. follows:
 - Perforate using a 3-1/8" O.D. casing gun with DML Densi-Jet XIV a. (14.0 gram) charges at 120° phasing.
 - Record and report wellhead pressure before and after each run. b.
 - Perforate (from bottom up) 3 shots per foot at depths shown on c. Attachment I. Depth reference is McCullough's GR/CBL dated 3/8/73.
- If well can be controlled with water after perforating, run a 5" fullbore 5 a. packer on tubing and set at + 11,820'. Test tubing to 6500 psi.
 - If well cannot be controlled with water after perforating, lubricate in a 5" Model "FA-1" packer with Model "B" expendable plug in place and set at \pm 11,820'. Run in with latch-in seal assembly. Latch into packer at + 11,820' and pressure test tubing to 6500 psi. Run in with sinker bars and jars on wireline and knock out expendable plug from packer at + 11,820'. Continue to Step 6.

- 6. Acid treat perfs 13106'-11842' (195 new, 280 old) with 30,000 gallons of 7-1/2% HCL as follows:
 - a. Pump 1000 gallons 7-1/2% HCL.
 - Pump 4000 gallons acid, dropping one ball sealer (7/8" RCN with 1.2 S.G.) every 65 gallons.
 - c. Pump 1000 gallons acid containing 1000# benzoic acid flakes.
 - d. Repeat Step (b) 5 more times and Step (c) 4 more times for a total of 6 stages acid and 5 of diverting material (total 30,000 gallons acid and 369 ball sealers).
 - e. Flush with 110 bbls of clean produced water.
 - Notes: 1. All acid and flush to contain 6 gallons G-10/1000 gallons HCL or equivalent for +70% friction reduction and 1.0# 20-40 mesh RA sand per 1000 gallons (no RA sand in flush).
 - 2. All acid to contain 3 gallons C-15/1000 gallons HCL for 4 hours exposure at 210°F and the necessary surfactant (tested for compatibility with formation fluids).
 - 3. Maintain 2500 psi surface casing pressure during treatment if possible.
 - Pumping rates: pump at maximum possible without exceeding 6500 psi differential pressure between tubing and annulus.
 - 5. Increase amount of diverting material if necessary to obtain a gradual increase in treating pressure and/or decrease in rate.
 - 6. Record ISIP and shut-in pressure decline for at least 20 minutes.
- 7. Run RA log from PBTD to \pm 11750' \pm .
- 8. a. If well flows, release rig and put on production. When well can be controlled with water, move in rig and proceed to Step 9.
 - b. If well does not flow, continue with Step 9.
- a. If a 5" fullbore packer was used in Step 5, POOH with tubing and packer. RIH with 5" RBP and 5" fullbore packer. Set RBP at 11,820'. Pressure test to 3000 psi. If okay, spot 1 sack of sand on plug (at field's discretion).
 - b. If a 5" Model "FA-1" packer was used in Step 5, POOH with tubing. RIH with Model "D latching" plug. Pressure test plug to 3000 psi. If okay, spot 1 sack of sand on plug (at field's discretion).
- 10. Rig up perforators with lubricator (tested to 3000 psi) and perforate as follows:

- a. Perforate using a 3-1/8" O.D. casing gun with DML Densi-Jet XIV (14.0 gram) charges at 120°F phasing.
- b. Record and report wellhead pressure before and after each run.
- c. Perforate (from bottom up) 3 shots per foot at depths shown on Attachment II. Depth reference is McCullough's GR/CBL dated 3/8/73.
- a. If well can be controlled with water after perforating, run a 7" fullbore packer on tubing and set at \pm 10,500'. Test tubing to 6500 psi.
 - b. If well cannot be controlled with water after perforating, lubricate in a 7" Model "D" packer (with flapper) and set at \pm 10,500'. Run tubing, latch into packer, and put well on production.
- 12. Acid treat perfs 11806'-10582' (180 new, 78 old) with 25,000 gallons of 7-1/2% HCL as follows:
 - a. Pump 1000 gallons 7-1/2% HCL.
 - b. Pump 4000 gallons acid, dropping one ball sealer (7/8" RCN with 1.2 S.G.) every 90 gallons.
 - c. Pump 1000 gallons acid containing 1000# benzoic acid flakes.
 - d. Repeat Step (b) 4 more times and Step (c) 3 more times for a total of 5 stages acid and 3 of diverting material (total 25,000 gallons acid and 222 ball sealers).
 - e. Flush with 110 bbls of clean produced water.
 - Notes: 1. All acid and flush to contain 6 gallons G-10/1000 gallons HCL or equivalent for ±70% friction reduction and 1.0# 20-40 mesh RA sand per 1000 gallons (no RA sand in flush).
 - 2. All acid to contain 3 gallons C-15/1000 gallons HCL for 4 hours exposure at 210°F and the necessary surfactant (tested for compatibility with formation fluids).
 - 3. Maintain 2500 psi surface casing pressure during treatment if possible.
 - 4. Pumping rates: pump at maximum possible without exceeding 6500 psi differential pressure between tubing and annulus.
 - 5. Increase amount of diverting material if necessary to obtain a gradual increase in treating pressure and/or decrease in rate.
 - 6. Record ISIP and shut-in pressure decline for at least 20 minutes.
- 13. Run RA log from \pm 11820' to \pm 10,450'.
- 14. a. If well flows, release rig and put on production. When well can be controlled with water, move in rig and proceed to Step 15.

- b. If well does not flow, continue with Step 15.
- 15. a. If a 7" fullbore packer was used in Step 11, POOH with tubing and packer.
 - b. If a 7" Model "D" packer was used in Step 11, POOH with tubing and seals. RIH and mill out 7" Model "D".
- 16. a. If an RBP was used in Step 9a, circulate sand (if necessary) and retrieve BP. Proceed to Step 17.
 - b. If a 5" Model "FA-1" packer with Model "D" latching plug was used in Step 9b, RIH and retrieve latching plug. RIH in and mill out 5" Model "FA-1" packer. Proceed to Step 17.
- 17. RIH with tubing, GL mandrels, and 7" packer. Set packer at \pm 10,500'. Install GL mandrels as shown in Attachment III.
- 18. Return well to production.
- 19. Report well tests on morning report until production stabilizes.

	G. L. Thompson
MEB: KW	
meb	Date
The state of the s	

2123/41

ATTACHMENT I

Depth reference is McCullough's CBL/GR dated 3-8-73.

13106	12614	12209
101	578	200
065	562	191
055	558	171
053	521	144
	518	137
12988	500	118
971	486	082
956	471	065
940	454	052
924	427	040
909	382	019
877	361	001
862	348	11994
786	332	958
757		948
732	298	935
700	288	929
674	263	911
657	256	900
641	250	868
620	231	
	223	856
	-	848

Total 198 perforations (3 JSPF at 66 depths).

ATTACHMENT II

Depth reference is McCullough's CBL/GR dated 3-8-73.

lepth reference is includiously s	0D2/ G	~
11802 790 778 755 732 724 708 694 652 630 621 596 550	11351 341 326 316 299 260 241 235 228 216 206 198 180	11021 10972 962 952 936 921 827 822 804 796 788 736 725
596	180	725

Total 180 perforations (3 JSPF at 60 depths).

SUBMI'1 ... TRIPLICATE* (Other instructions on reverse side)

STATE OF UTAH **DEPARTMENT OF NATURAL RESOURCES**

DIVIS	5. LEASE DESIGNATION AND SERIAL NO. PATENTED 6. IF INDIAN, ALLOTTER OR TRIBE NAME			
SUNDRY NOT				
OIL GAS GAS OTHER			7. UNIT AGREEMENT NA	MB
2. NAME OF OPERATOR Shew Oil Company			8. FARM OR LEASE NAME DOVIE	(3)
P.U. Box 831 Houston. T	X 72001 ATTAL P.G.G.E.	LING PM#6459 WCK	9. WELL NO.	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 7382 FNL + 2157 FWL Sec. 10			10. FIELD AND POOL, 0	•
			SEY NW/4	tzs R3W
14. PERMIT NO.	15. BLEVATIONS (Show whether DE	, RT, GR, etc.)	12. COUNTY OR PARISH	18. STATE
	6048 KB		DUCHESHE	Utah
		lature of Notice, Report, or C	Other Data	
NOTICE OF INTEN	ftion to:	Jonasus	ENT REPORT OF:	
TEST WATER SHUT-OFF	PULL OR ALTER CASING	WATER SHUT-OFF	REPAIRING W	PELL
FRACTURE TREAT	MULTIPLE COMPLETE	FRACTURE TREATMENT	ALTERING CA	SING
SHOOT OR ACIDIZE	ABANDON*	SHOOTING OR ACIDIZING	ABANDONMEN	T.
REPAIR WELL	CHANGE PLANS	(Other)	_	
(Other)		(NOTE: Report results Completion or Recompl	of multiple completion of multiple completion of the completion of	m Well
17. DESCRIBE PROPOSED OR COMPLETED OPE proposed work. If well is directic	CRATIONS (Clearly state all pertinen onally drilled, give subsurface locat	t details, and give pertinent dates, ions and measured and true vertica		

nent to this work.) *

SEE ATTACHED

18. I hereby certify that the foregoing is true and correct		
SIGNED W. F. N. KELLDORD	TITLE DIVISION PROD. ENGINEER	18-05-8 atad
(This space for Federal or State office use)		
APPROVED BY	TITLE	DATE

ALIAMONI OPERATIONS DAILY COMPLETIONS AND REMEDIALS REPORT WELL HISTORY FOR WELL 340 ISSUED 07/25/81

THE RESERVE AND ADDRESS OF THE RESERVE AND ADDRESS OF THE PARTY AND ADD	
I ADCL *	
LAREL:	340
DAILY COST:	340
CUM COST:	340
DATE:	340
WELL:	DSMIT 4 4400
LASEL:	DOYLE 1-10B3
AFE:	FIRST REPORT
FOREMAN:	514417
RIG:	K.C. LAPOSE
OBJECTIVE:	WOW #17
AUTH. ANNT:	CO - PERF. AND SIIM.
	143000
DAILY COST:	29∈ <u>0</u>
	2°50
DATE:	6-9-81
ACTIVITY:	6-9-01 STATUS: WO #514417 IS TO C.O PERF. AND
02	SILMA THE WASAICH FOR THE AMOUNT OF 143000.
03	G-9-81 ACTIVITY: MIRU - PUMPED WATER DOWN THRING
04	RILLED WELL - REMOVED 5000# PRODUCTION TREE -
* 0 5 *	INSTALLED BOPS - RELEASED SEAT ASSEMBLY - BOOK
05	SDEN.
	The state of the s
LABEL:	810611
DAILY COST:	3000
CUM COST:	5950
DATE:	6-10-81
ACTIVITY:	5-10-81 ACTIVITY: POOR TOOK OFF THE 51/2 IN. HEAT
02	STRING SPOOL AND DONUT INSTALLED THE 7 IN. SPOOL
03	AND BOPS PUT ON A PACKER PLUCKER IC MILL OUT 7 IN.
04	MODEL FA-1 PACKER RIH
<u>* () </u>	SOFN
LABFL:	810622
DAILY COST:	ZOED
CUM COST:	<u>25780</u>
DATE:	5-11-12-13-14-15-15-81
ACTIVITY:	6-11-81 ACTIVITY: DICKED UP DAVIS
* G 2' *	WATER DOWN OSE MILES OUT YOUR SWIVEL STARTED PUMPING
D3	TO THE STAR GOV BILLED OUT MODEL FALL DED TACCED LINES
04	THE DE LATE OF THE PER PUT ON 41/9 THE MILL OF THE PER PUT OF THE PUT OF
05	THE OF STRIVES MILL UP REST HE DES P.D. LINES
	6-12-81 ACTIVITY: RIH TAGGED A PEACE OF PKR & LINER TOP
According to the second	

PAGE

2

ALTAMONI OPERATIONS DAILY COMPLETIONS AND REMEDIALS REPORT WELL HISTORY FOR WELL 340 ISSUED 07/23/91

	130000 07723731
O6	MILLED ON DOWN TO 11790 FT. MILL PLUGGED UP STARTED OUT OF
07	HOLE SDEN
88	6-13-81 ACTIVITY: PULLED THE REST OF THE WAY OUT OF THE
00	HOLE HAD THE PEACE OF PKR ON MILL AND FULL JT OF SCALE RE-
16	PLACED MILL AND 1 JOINT 27/8 IN. TBG RIH SDFN
11	6-14-81 STATUS: SHUT DOWN SUNDAY
12	6-18-81 STATUS: C.O. LINER TO PBTD
13	6-15-81 ACTIVITY: RUN MILL INTO LINER PICKED UP POWER SWIVEL
*1 4 *	AND HOOKED UP PUMPED WIR REVERSED GOT CIRCULATION MILLED
15	DOWN TO 13113 FT. MILL KEPT PLUGGING OFF CIRCULATED FOR 30
16	MIN. TOOK POWER SWIVEL CEE POOR SOEN
<u>*17*</u>	5-16-81 STATUS: PERFORATED AND GET READY TO STIMULATE
18	6-16-81 ACTIVITY: RIG UP OWP RIH WITH 31/8 IN. GUN TAG-
1°	GED OUT 11300 FI. TRIED TO WORK GUN DOWN HOLE BUT WOULD
20	NOT SO POOH WITH 31/8 IN. GUN RIG DOWN OWP RIH WITH 41/8
<u>*21*</u>	IN. FLAT ROLTON MILL AND RUN IC BOILON (13113 ET.) WITH
22	NO PROBLEMS POCH RIG UP OWP RIH WITH 31/8 IN. GUN TAGGED
23	OUT & 11400 FT. COULD NOT GET GUN DOWN HOLE POOH WITH 31/P
24	IN. GUN SOON
	(-17-91 STATUS: OTH HITTH DESCH STOR AND DEDENDARY
25	6-17-81 STATUS: RIH WITH WASH PIPE AND PERFORATE
	TEST STATUS REM SITH WASH PIPE AND PERFORATE
LAGEL:	810623
LAGEL:	810623
LAGEL: DAILY COST: CUM COST: DATE:	810623 45750 92100 6-17-18-19-81
DAILY COST: CUM COST: DATE: ACIIVITY:	810623 45750 92100 6-17-19-19-81 6-17-81 ACTIVITY: RIH WITH WASH PIPE AND 41/8 IN. SHOE
LAGEL: DAILY COST: CUM COST: DATE: ACILVITY: +02+	810623 45750 92100 6-17-18-19-81 6-17-81 ACTIVITY: RIH WITH WASH PIPE AND 41/8 IN. SHOE TO BOTTOM (13113 FT.) CIRCULATE FOR A WHILE WITH WASH PIPE
LAGEL: DAILY COST: CUM COST: DATE: ACIIVITY: +02+ +03+	810623 45750 92100 6-17-18-19-81 6-17-81 ACTIVITY: RIH WITH WASH PIPE AND 41/8 IN. SHOE TO BOTTOM (13113 FT.) CIRCULATE FOR A WHILE WITH WASH PIPE ON BOTTOM BOUNCED WASH PIPE ON BOTTOM TO GRAP ANYTHING ON
LAREL: DAILY COST: CUM COST: DATE: ACTIVITY: +02+ +03+ +04+	810623 45750 92100 6-17-18-19-81 6-17-81 ACTIVITY: RIH WITH WASH PIPE AND 41/8 IN. SHOE TO BOTTOM (13113 FT.) CIRCULATE FOR A WHILE WITH WASH PIPE ON BOTTOM BOUNCED WASH PIPE ON BOTTOM TO GRAP ANYTHING ON BOTTOM POOH WITH PIPE AND WASH PIPE SDON
LARFI: DAILY COST: CUM COST: DATF: ACTIVITY: +02* +03* +04* +05*	810623 45750 92100 8-17-18-19-81 6-17-81 ACTIVITY: RIH WITH WASH PIPE AND 41/8 IN. SHOE TO BOTTOM (13113 FT.) CIRCULATE FOR A WHILE WITH WASH PIPE ON BOTTOM BOUNCED WASH PIPE ON BOTTOM TO GRAP ANYTHING ON BOTTOM POOH WITH PIPE AND WASH PIPE SDON 6-18-81 STATUS: PERFORATE
LARFI: DAILY COST: CUM COST: DATF: ACIIVITY: +02+ +03+ +04+ +05+	810623 45750 92100 6-17-18-19-81 6-17-81 ACTIVITY: RIH WITH WASH PIPE AND 41/8 IN. SHOE TO BOTTOM (13113 FT.) CIRCULATE FOR A WHILE WITH WASH PIPE ON BOTTOM BOUNCED WASH PIPE ON SOTTOM TO GRAP ANYTHING ON BOTTOM POOH WITH PIPE AND WASH PIPE SDON 6-18-81 STATUS: PERFORATE 6-18-81 ACTIVITY: RIG UP OWP MADE THREE RUNS WITH 31/8 IN.
LASEL: DAILY COST: CUM COST: DATE: ACIIVITY: +02* +03* +04* +05* +06*	810623 45750 92100 6-17-18-19-81 6-17-81 ACTIVITY: RIH WITH WASH PIPE AND 41/8 IN. SHOE TO BOTTOM (13113 FT.) CIRCULATE FOR A WHILE WITH WASH PIPE ON BOTTOM BOUNCED WASH PIPE ON SOTTOM TO GRAP ANYTHING ON BOTTOM POOH WITH PIPE AND WAGH PIPE SDON 6-18-81 STATUS: PERFORATE 6-18-81 ACTIVITY: RIG UP OWP MADE THREE RUNS WITH 31/8 IN. GUNS PERFORATED AS ATTACHED WITH PROG HAD PROBLEM GETTING
LAREL: DAILY COST: CUM COST: DATE: ACIIVITY: +02+ +03+ +04+ +05+ +06+ +07+ +08+	810623 45750 92100 6-17-18-19-81 6-17-81 ACTIVITY: RIH WITH WASH PIPE AND 41/8 IN. SHOE TO BOTTOM (13113 FT.) CIRCULATE FOR A WHILE WITH WASH PIPE ON BOTTOM BOUNCED WASH PIPE ON BOTTOM TO GRAP ANYTHING ON BOTTOM POOH WITH PIPE AND WASH PIPE SDON 6-18-81 STATUS: PERFORATE 6-18-81 ACTIVITY: RIG UP OWP MADE THREE RUNS WITH 31/8 IN. GUNS PERFORATED AS ATTACHED WITH PROS HAD PROBLEM GETTING DOWN HOLE WITH FIRST GUN HAD TO WORK GUN THROUGH TIGHT
LASEL: DAILY COST: CUM COST: DATE: ACTIVITY: +02+ +03+ +04+ +05+ +06+ +06+ +07+ +08+ +08+	810623 45750 92100 6-17-18-19-81 6-17-81 ACTIVITY: RIH WITH WASH PIPE AND 41/8 IN. SHOE TO BOTTOM (13113 FT.) CIRCULATE FOR A WHILE WITH WASH PIPE ON BOTTOM BOUNCED WASH PIPE ON BOTTOM TO GRAP ANYTHING ON BOTTOM POOH WITH PIPE AND WASH PIPE SDON 6-18-81 STATUS: PERFORATE 6-18-81 ACTIVITY: RIG UP OWP MADE THREE RUNS WITH 31/8 IN. GUNS PERFORATED AS ATTACHED WITH PROS HAD PROBLEM GETTING DOWN HOLE WITH FIRST GUN HAD TO WORK GUN THROUGH TIGHT SPOT BETWEEN 11400 FT 11900 FT. SECOND AND THIRD RUN NO
LAGEL: DAILY COST: CUM COST: DATE: ACTIVITY: *02* *03* *04* *05* *05* *07* *08* *10*	810623 45750 92100 6-17-18-19-81 6-17-81 ACTIVITY: RIH WITH WASH PIPE AND 41/8 IN- SHOE TO BOTTOM (13113 FT-) CIRCULATE FOR A WHILE WITH WASH PIPE ON BOTTOM BOUNCED WASH PIPE ON SCITIOM TO GRAP ANYTHING ON BOTTOM POOH WITH PIPE AND WASH PIPE SDON 6-18-81 SIATUS: PERFORATE 6-18-81 ACTIVITY: RIG UP OWP MADE THREE RUNS WITH 31/8 IN- GUNS PERFORATED AS ATTACHED WITH PROS HAD PROBLEM GETTING DOWN HOLE WITH FIRST GUN HAD TO WORK GUN THROUGH TIGHT SPOT BETWEEN 11400 FT 11900 FT- SECOND AND THIRD RUN NO PROBLEM NO PRESSURE AFTER ALL THREE RUNS AND COULD NOT TELL
LARFI: DAILY COST: CUM COST: DATF: ACTIVITY: +02* +03* +04* +05* +06* +06* +06* +10* +10*	810623 45750 92100 6-17-18-19-81 6-17-81 ACTIVITY: RIH WITH WASH PIPE AND 41/8 IN. SHOE TO BOTTOM (13113 FT.) CIRCULATE FOR A WHILE WITH WASH PIPE ON BOTTOM BOUNCED WASH PIPE ON BOTTOM TO GRAP ANYTHING ON BOTTOM POOH WITH PIPE AND WASH PIPE SDON 6-18-81 STATUS: PERFORATE 6-18-81 ACTIVITY: RIG UP OWP MADE THREE RUNS WITH 31/8 IN. GUNS PERFORATED AS ATTACHED WITH PROS HAD PROBLEM GETTING DOWN HOLE WITH FIRST GUN HAD TO WORK GUN THROUGH TIGHT SPOT BETWEEN 11400 FT 11900 FT. SECOND AND THIRD RUN NO PROBLEM NO PRESSURE AFTER ALL THREE RUNS AND COULD NOT TELL ELUID LEVEL 198 PERES AT 66 DEPTHS (13106 FT11848 FT.)
LARFI: DAILY COST: CUM COST: DATE: ACTIVITY: +02* +03* +04* +05* +06* +06* +10* +10* +11* +12*	810623 45750 92100 6-17-18-19-81 6-17-81 ACTIVITY: RIH WITH WASH PIPE AND 41/8 IN. SHOE TO BOTTOM (13113 FT.) CIRCULATE FOR A WHILE WITH WASH PIPE ON BOTTOM BOUNCED WASH PIPE ON BOTTOM TO GRAP ANYTHING ON BOTTOM POOH WITH PIPE AND WASH PIPE SDON 6-18-81 SIATUS: PERFORATE 6-18-81 ACTIVITY: RIG UP OWP MADE THREE RUNS WITH 31/8 IN. GUNS PERFORATED AS ATTACHED WITH PROS HAD PROBLEM GETTING DOWN HOLE WITH FIRST GUN HAD TO WORK GUN THROUGH TIGHT SPOT BETWEEN 11400 FT 11900 FT. SECOND AND THIRD RUN NO PROBLEM NO PRESSURE AFTER ALL THREE RUNS AND COULD NOT TELL ELUID LEVEL 198 PERES AT 66 DEPTHS (13106 FT11848 FT.) BIG DOWN OWP RIH WITH TBG AND 5 IN FULL-BORE PKR SET PKR &
LAGEL: DAILY COST: CUM COST: DATE: ACIIVITY: *00* *04* *05* *06* *07* *08* *10* *11* *12* *15*	810623 45750 90100 5-17-18-19-81 6-17-81 ACTIVITY: RIH WITH WASH PIPE AND 41/8 IN. SHOE TO BOTTOM (13113 FT.) CIRCULATE FOR A WHILE WITH WASH PIPE ON BOTTOM BOUNCED WASH PIPE ON BOTTOM TO GRAP ANYTHING ON BOTTOM POOH WITH PIPE AND WASH PIPE SDON 6-18-81 STATUS: PERFORATE 6-18-81 ACTIVITY: RIG UP OWP MADE THREE RUNS WITH 31/8 IN. GUNS PERFORATED AS ATTACHED WITH PROS HAD PROBLEM GETTING DOWN HOLE WITH FIRST GUN HAD TO WORK GUN THROUGH TIGHT SPOT BETWEEN 11400 FT 11900 FT. SECOND AND THIRD RUN NO PROBLEM NO PRESSURE AFTER ALL THREE RUNS AND COULD NOT TELL ELUID LEVEL 198 PERES AT 66 DEPTHS (13106 FT11848 FT.) RIG DOWN OWP RIH WITH TBG AND 5 IN FULL-BORE PKR SET PKR @
LARFI: DAILY COST: CUM COST: DATE: ACIIVITY: +02* +03* +04* +05* +06* +06* +10* +10* +11* +12* +13* +14*	810623 45750 92100 6-17-18-19-81 6-17-81 ACTIVITY: RIH WITH WASH PIPE AND 41/8 IN. SHOE TO BOTTOM (13113 FT.) CIRCULATE FOR A WHILE WITH WASH PIPE ON BOTTOM BOUNCED WASH PIPE ON BOTTOM TO GRAP ANYTHING ON BOTTOM POOH WITH PIPE AND WASH PIPE 5-18-81 STATUS: PERFORATE 6-18-81 ACTIVITY: RIG UP OWP MADE THREE RUNS WITH 31/8 IN. GUNS PERFORATED AS ATTACHED WITH PROS HAD PROBLEM GETTING DOWN HOLE WITH FIRST GUN HAD TO WORK GUN THROUGH TIGHT SPOT BETWEEN 11400 FT 11900 FT. SECOND AND THIRD RUN NO PROBLEM NO PRESSURE AFTER ALL THREE RUNS AND COULD NOT TELL ELUID LEVEL 198 PERES AT 66 DEPTHS (13106 FT11848 FT.) RIG DOWN OWP RIH WITH TBG AND 5 IN FULL-BORE PKR SFT PKR & 11828 FT. REMOVE BOP AND PUT ON 10000 PSI TREE PUMP DOWN BACK SIDE TO PRESSURE TEST COULD ONLY TEST TO 2000 PSI (TO
LASEL: DAILY COST; CUM COST; DATE: ACTIVITY: *02* *03* *04* *05* *06* *07* *10* *10* *11* *12* *13* *14* *15*	810623 45750 90100 8-17-18-19-81 6-17-81 ACTIVITY: RIH WITH WASH PIPE AND 41/8 IN. SHOE TO BOTTOM (13113 FT.) CIRCULATE FOR A WHILE WITH WASH PIPE ON BOILOM BOUNCED WASH PIPE ON BOILOM TO GRAP ANYTHING ON BOTIOM POOH WITH PIPE AND WASH PIPE SDON E-18-81 SIATUS: PERFORATE S-18-81 ACTIVITY: RIG UP OWP MADE THREE RUNS WITH 31/8 IN. GUNS PERFORATED AS ATTACHED WITH PROS HAD PROBLEM GETTING DOWN HOLE WITH FIRST GUN HAD TO WORK GUN THROUGH TIGHT SPOT BETWEEN 11400 FT 11900 FT. SECOND AND THIRD RUN NO PROBLEM NO PRESSURE AFTER ALL THREE RUNS AND COULD NOT TELL ELUID LEVEL 198 PERES AT 66 DEPTHS (13106 FT11848 FT.) RIG DOWN OWP RIH WITH TBG AND 5 IN FULL-BORE PKR SET PKR @ 11828 FT. REMOVE BOP AND PUT ON 10000 PSI TREE PUMP DOWN BACK SIDE TO PRESSURE TEST COULD ONLY TEST TO 2000 PSI (TO
LARFI: DAILY COST: CUM COST: DATE: ACIIVITY: +02* +03* +04* +05* +06* +06* +10* +10* +11* +12* +13* +14*	810623 45750 92100 6-17-18-19-81 6-17-81 ACTIVITY: RIH WITH WASH PIPE AND 41/8 IN. SHOE TO BOTTOM (13113 FT.) CIRCULATE FOR A WHILE WITH WASH PIPE ON BOTTOM BOUNCED WASH PIPE ON BOTTOM TO GRAP ANYTHING ON BOTTOM POOH WITH PIPE AND WASH PIPE 5-18-81 STATUS: PERFORATE 6-18-81 ACTIVITY: RIG UP OWP MADE THREE RUNS WITH 31/8 IN. GUNS PERFORATED AS ATTACHED WITH PROS HAD PROBLEM GETTING DOWN HOLE WITH FIRST GUN HAD TO WORK GUN THROUGH TIGHT SPOT BETWEEN 11400 FT 11900 FT. SECOND AND THIRD RUN NO PROBLEM NO PRESSURE AFTER ALL THREE RUNS AND COULD NOT TELL ELUID LEVEL 198 PERES AT 66 DEPTHS (13106 FT11848 FT.) RIG DOWN OWP RIH WITH TBG AND 5 IN FULL-BORE PKR SFT PKR & 11828 FT. REMOVE BOP AND PUT ON 10000 PSI TREE PUMP DOWN BACK SIDE TO PRESSURE TEST COULD ONLY TEST TO 2000 PSI (TO

DAILY COMPLETIONS AND REMEDIALS REPORT WELL HISTORY FOR WELL 340 ISSUED 07/29/81

18	8900 PSI-AVG PRESS 8400 PSI-MIN PRESS 7000 PSI-CSG PRESS
19	2500 PSI ACID 720 BBLS 71/2% HCL FLUSH 110 BBL TOTAL FLUID
20	830 88L ISIP-5000 PSI 5 MIN -4800 PSI 10 MIN-4600 PSI 15 MIN-
+21+	4200 PSI 20 MIN-3850 PSI HAD TO HOLD PUMP TRUCK ON BACK
22	SIDE TO HOLD 2500 PSI CSG PRESS RIG DOWN DOWELL RIG UP OWP
25	REMOVE 10000 PSI TREE AND INSTALL BOP POOH WITH PKR LAID
24	DOWN 44 JTS OF 27/8 IN. THE ON RACK SOON
25	6-20-81 STATUS: PERFORATE
LABEL:	
DAILY COST:	455.0
CUM COST:	161400
DATE:	5-24-81
ACTIVITY:	6-24-81 STATUS: RIH WITH TEG AND MANDRELS
02	6-24-81 ACTIVITY: FINISH COMING OUT OF HOLE WITH
03	IBG AND MILL. RIH WITH TBG MANDRELS AND 7 IN. FULLBORE
* C 4 *	PACKER. SET PACKER AT 10500 FT. HANG OFF TBG.
<u>*0</u> 5*	REMOVE BOP AND PUT ON WELLHEAD. RIG DOWN. FINAL
* 0 € *	REPORT ON THIS WELL.
0?	6-25-81 STATUS: MOVING TO 1-1885
98	SET PACKER AT 10500. REMOVE BOF. PUT ON 10000# TREE.
★ ()□ ★	SDON.
10	6-21-81 SDON
11	5-22-81 STATUS: ACIDIZE
10	6-22-81 ACTIVITY: FILL BACKSIDE WITH WATER AND
<u>*13*</u>	PRESSURE TEST CSG TO 2500#. RIG UP DOWELL. ACIDIZE
14	ACCORDING TO PROG. MAX RATE - 18 BBL AVG. RATE 168BL
*15 *	MIN. RAIF - 14 BBL. MAX PRESS - 8900# AVG. PRESS
16	8300# MIN. PRESS - 7500# CSG PRESS 2500#. ISIP
17	4700# 5 MIN - 4650# 10 MIN4500# 15 MIN 4250# 20
18	MIN 3900#. ACID 600 BBL FLUSH 110 BBL TOTAL 710
19	BRL. JOB WENT WELL. RIG DOWN DOWELL. RIG UP OWP.
20	RUN RA LOG 10510 FT TO 11815 FT. LOG SHOWS 90
21	PERCENT THEATMENT IN ALL PERES. RIG DOWN DWP.
22	REMOVE 10000# TREE. PUT ON BOP. START OUT OF HOLE
23	WITH THE AND PACKER. WELL WAS DEAD WHEN RELEASED FACKER
24	AND STARTED OUT OF HOLE. SOON.
25	E-23-81 ACTIVITY: FINISH COMING OUT OF HOLE WITH
*25+	PACKER AND TBG. RIH WITH 6 1/8 IN. MILL AND TBG.
27	TAGGED CIRP AND DRILLED OUT BP. PICKED UP 86 JIS.
28	OF THE AND PUSHED CIBP TO BOITOM OF HOLE (13125 FT).
25	STARY OUT OF HOLE WITH MILL AND THE LAID DOWN 86
	THE RIVER THE PARTY OF THE PART

PAGE

1

ALIAMONI OPERATIONS DAILY COMPLETIONS AND REMEDIALS REPORT WELL HISTORY FOR WELL 340 ISSUED 07/25/81

30	JIS OF TBG. SDON.
LABEL:	8107 05
DAILY COST:	810705
CUM COST:	161450
DATE:	6-26-30-81 AND 7-1-2-81
ACTIVITY:	6-26-81 ACTIVITY: HRS 21-01L 70-WTR 49-MCF GAS 369
02	CHOKE 35/64-FIP 300-CP 1200-INJ GAS 293
03	8-27-81 ACTIVITY: HRS 21-01L 80-WTR 92-MCF GAS 500
04	CHOKE 35/64-FIP 300-CP 1200-INJ GAS 213
★8 5★	6-28-81 ACTIVITY: HRS 24-01L 397-WTR 460-MCF GAS 1000
06	CHOKE 35/64-FTP 200-CP 1200-INU GAS 332
07	6-29-81 ACTIVITY: HRS 24-OIL 154-WTR 295-MCF GAS 900
D8	CHOKE 35/64-ETP 200-CP 1220-INJ GAS 270
* 05 *	6-30-81 ACTIVITY: HRS 24-DIL 151-WTR 261-MCF GAS 735
<u>*18*</u>	CHOKE 35/64-ETP 300-CP 1220-INJ GAS 365
11	7-1-81 ACTIVITY: HRS 24-01L 44-WTR 361-MCF GAS 700
12	CHOKE 35/64-FIP 300-CP 1220 INJ GAS 387
*1 3 *	7-2-81 ACTIVITY: ERS 24-01L 156-WIR 250-MCF GAS 761
*14+	CHOKE 35/64-FIP 150-CP 1230-INJ GAS 415

Shell Oil Company



P.O. Box 831 Houston, Texas 77001

December 30, 1983

Mr. Norm Stout State of Utah Natural Resources Division of Oil, Gas & Mining 4241 State Office Building Salt Lake City, UT 84114

Dear Mr. Stout:

TRANSFER OF OWNERSHIP AND ASSETS FROM SHELL OIL COMPANY TO SHELL WESTERN E&P INC. STATE OF UTAH

In accordance with our recent conversation, the purpose of this letter is to reduce to writing that Shell Western E&P Inc. ("SWEPI"), a subsidiary of Shell Oil Company, has been formed. Shell Western E&P Inc. is a Delaware corporation with its offices located at 200 North Dairy Ashford Road in Houston, Texas. The mailing address is P. O. Box 831, Houston, TX 77001.

Effective January 1, 1984, Shell Oil Company will transfer portions of its oil and gas operations to Shell Western E&P Inc. and Shell Western E&P Inc. will assume all of the rights, interests, obligations and duties which Shell Oil Company currently has as a result of its exploration, development and production operations in the State of Utah.

As you are aware, Shell Oil Company is currently the holder of various permits and agency authorizations. In view of the fact that Shell Western E&P Inc. will assume all of the liabilities and obligations of Shell Oil Company's exploration and production activities within the state, we respectfully request that you transfer all permits or other authorizations from Shell Oil Company to Shell Western E&P Inc., effective January 1, 1984.

To support this request, a copy of the power of attorney appointing the undersigned as Attorney-in-Fact for Shell Western E&P Inc. is enclosed. On behalf of Shell Western E&P Inc., enclosed are recently issued Bond No. Shell 1835 and Bond No. Shell 1841. The bonds were issued by the Insurance Company of North America. In the near future, I shall request that the existing Shell Oil Company bonds be released.

It is my understanding, pursuant to our prior discussion, that this letter will comply with your requirement regarding the change in the name of the permittee.

Sufficient copies of this letter are being provided to your office so that a copy can be placed in each appropriate file. A listing of active wells is enclosed. Thank you in advance for your cooperation in this matter.

Yours very truly,

8. m. Dobe

G. M. Jobe Administrator, Regulatory-Permits Rocky Mountain Division Western E&P Operations

GMJ:beb

Enclosures

* MIT IN TRIPLICATE: 010936 reverse side)

STATE OF UTAH DEPARTMENT OF NATURAL RESOURCES

D	5. LEASE DESIGNATION AND SERIAL NO.		
SUNDRY 1 (Do not use this form for Use "AF	NOTICES AND REPORTS proposals to drill or to deepen or plus PLICATION FOR PERMIT—" for such	ON WELLS r back to a different reservoir. proposals.)	6. IF INDIAN, ALLOTTER OR TRIBE NAME
OIL UAS OTI	122		7. UNIT AGREEMENT NAME
ANR Limited Inc	2.		8. PARM OR LEAGE NAME
	Denver, Colorado 80201-		1. WILL NO. J
4. LOCATION OF WELL (Report loca See also space 17 below.) At surface	tion clearly and in accordance with an	DEC 3 1 1986	10. FIELD AND FOOL, OR WILDCAT
See attached 1:	ist	DIVISION OF	11. BEC., T., B., M., OB BLK. AND BURYET OR LEEA SURVEY OF JEEA
14. PERMIT NO. 43.013.30187	15. BLEVATIONS (Show whether	DF, RT, GR, etc.)	12 COUNTY OR PARISM 18. STATE
16. Chec	k Appropriate Box To Indicate	Nature of Natice, Report, or	Other Data
NOTICE OF	: OT NOITHETHI	80388	QUENT ESPORT OF:
TEST WATER SEUT-OFF	PULL OR ALTER CASING	WATER SHUT-OFF	REPAIRING WELL
FRACTURE TREAT	MULTIPLE COMPLETE	PRACTURE TREATMENT	ALTERING CASING
SHOOT OR ACIDIZE	ABANDON®	SHOUTING OR ACIDIZING	ABANDONMENT®
(Other) - Change Opera	CHANGE PLANS		ts of multiple completion on Well
17. DESCRIBE PROPOSED OR COMPLET	ED OPERATIONS (Clearly state all pertine	ent details, and give pertinent dates actions and measured and true verti	s, including estimated date of starting any cal depths for all markers and zones perti-

ANR Limited has been elected successor Operator to Utex Oil Company on the oil wells described on the attached Exhibit 'A'.

18. I hereby certify that the foregoing is true and correct SIGNED M. K. Milion	TITLE Stat Tout Mas	DATE 12/24/86
(This space for Federal or State office use)		
APPROVED BY	TITLE	DATE

MONTHLY OIL AND GAS PRODUCTION REPORT

				Duchesm	
Operator name and address:	-}	% SHE	UTEX OIL CO. ELL WESTERN E&P I		11040
PO BOX 576 HOUSTON TX ATTN: P.T. KENT, OIL	77001		tor name	Report Period (Month Amended, Report	NO840
Well Name	Producing	1 .	Production Volume Oil (BBL)	Gas (MSCF)	Water (BBL)
API Number Entity/ Location 1URDOCK 1-3485 4301330230 01786 028 05W 34	WSTC	3/	. 1800	1010	381
ENKINS 1-183 301330175 01790 028 03W 1	GR-WS	31	1719	2901	8117
19448 - ETAL 1 2984/ 1301330246 01791 028 04W 29	WSTC	31	768	. 0	4270
301330221 01795 028 05W 32	WSTC	18	219	0	70
301330242 01796 025 04W 28	WSTC	30	486.	1169	1
TE TRIBAL 1-35A3V. 301330181 01800 015 03W 35	WSTC	31	. 1 2346	2125	506
301330247 01801 025 05W 25	WSTC	20	341	0	/3/2
301330201 01805 0ZS 03W 8	GR-WS	0	0	2000	- 5166
301330238 01806 02'S 05W 16 01LE 1-10B3 301330187 01810 02'S 03W 10	WSTC -	19	224	662	440
16 AGRER 151 1 0402 301330313 01811 025 02W 4	WSTC	31	1818	3214	
HELL BIE 1 2085 / +301330179 01815 028 05W 28	GR-WS		0	0	O
MEAGHER TRBL 1-0982 / 4301330325 01816 025 02W 9	WSTC	31	945	909	3214
et - 2		TOTAL	V 12130	14629	35553
Comments (attach separate sheet if nece	essary) ——		· ·		
have reviewed this report and certify the	e informatio	n to be	accurate and complete.	Date 9-28	-84
الدراني والرواية والمجهدة والمحافدة والمحافدة		in in the second	<u> </u>	Telephone	
Authorized signature	And the state of t				

ANR Production Company

012712

DIVISION OF ul Gas a minime

January 19, 1988

Natural Resources Oil, Gas & Mining 3 Triad Center, Suite 350 Salt Lake City, Utah 84180-1203

Attention: Ms. Lisha Romero

A NO 235

This letter includes the information you requested on January 12, 1988 concerning the recent merger of ANR'Limited, Inc. into ANR Not75 & Production Company. Effective December 31, 1987 (December, 1987 Production), ANR Limited, Inc. merged into ANR Production Company; and henceforth, will continue operations as ANR Production Company.

> ANR Production Company will begin reporting and remitting the Utah Conservation and Occupation Taxes effective December, 1987 production for leases previously reported by ANR Limited, Inc. (Utah Account No. N-7245). ANR Production Company will use the new Utah Account No. N-0675, as assigned by the State of Utah.

Please contact me at (713) 877-6167 if I can answer any questions on this matter.

The computer shows the ANR Limited wells listed under account no. NO235. 1-26-85

CTE:mmw

Lisha

Very truly yours,

Roger W. Sparks

Manager, Crude Revenue Accounting

CC: AWS

I don't see any priblem w/this.

I gave a copy to Ailene so

She could check on the bond

she could check on the bond situation. She didn't think this situation is the would affect their bond as the bond is set up for coastal
bond is set up for coastal
and its subsidiaries (ANR, etc.)
Allo Entity Number Changes are
necessary. DTS 1-26-88
astal Towar Min 7

Coastal Tower, Nine Greenway Plaza, Houston, Texas 77046-0995 • (713) 877-1400



355 West North Temple, 3 Triad Center, Suite 350, Salt Lake City, Ut 84180-1203. (801-538-5340)

_	6		10
Page		of	

MONTHLY OIL AND GAS PRODUCTION REPORT

NO235 th/Year) 11 / 87
th/Year) <u>11 / 87</u>
1
1
]
Water (BBL)
Water (BBC)

E TE OF UTAH

SUBMIT	TRIPLICATE:
(01	structions on
	Corse side)

ANR Production Company Ol. GAS. R. MINING 1. Doyle 1.		RTMENT OF NATURAL RESU ISION OF OIL, GAS, AND M		5. LEASE DESIGNATION AND SER	IAL NO
OTTO AND THE PROPERTY OF THE P	SUNDRY NO	OTICES AND REPORTS	ANS GISINVIEW		DE NAM
DIVISION OF PRIMARY FAME OF PRIMARY FAME OF PRIMARY AND PRODuction Company DIVISION OF CH. GAS & MINING DOYLE LODGE OF VILL CAPPET IDEATION (COLORADO 80201-0749 PERMIT PO. 2382' FNL & 2157' FWL (SENW) FIRMET PO. 43-013-30187 Check Appropries Box To Indicate Nature of Notice, Report, or Other Data SOUTCE OF DIVISION OF PRIMARY (COLORAD AND AND AND AND AND AND AND AND AND A	(De not use this form for pr Use "APP!	oposals to drill or to deepes or plus LICATION FOR PERMIT—" for such		7. UNIT AGAZEMBNT NAMB	
ANR Production Company Ol. GAS. R. MINING 1. Doyle 1.		.	JUN 6 1988 C	1	
ADDRESS OF OFFSLITED P.O. Box 749, Denver, Colorado 80201-0749 1-1083	AND Production Com	2207	DIVISION OF	8. PARM OR LEASE HAMB	
P.O. Box 749, Denver, Colorado 80201-0749 P.O. Box 749, Denver, Colorado 80201-0749 P.O. Box 749, Denver,		oany 	OIL, GAS & MINING		
Decide the property of the pro		r, Colorado 80201-0749)		
2382' FNL & 2157' FWL (SENW) 11. SECT. 1					AT
PREMITE FO. 43-013-30187 I. REVARIDES (Show whether St. H. Ch. sta.) I. COUNTY OF PARISE I. Section 10, T2S, R3W Check Appropriate Box To Indicate Nature of Notice, Raport, or Other Oats **TEST WATER SECTION INTERPEDENT TO: **TEST WATER SECTION INTERPEDENT TEST WATER SECTION **TEST WATER SECTION INTERPEDENT TES	At surface				
Section 10, T2S, R3W 43-013-30187 II. BLATATIONS (Show whether of, H. GL. sta.) II. COUNTY of Palling II. STATE A3-013-30187 II. BLATATIONS (Show whether of, H. GL. sta.) II. COUNTY of Palling II. STATE Duck Appropriate Box To Indicate Nature of Notice, Report, or Other Date NOTICE OF INTENTION TO: SOURCE O	2382' FNL & 21.	57' FWL (SENW)		11. SEC., T., B., M., OR BLE. AND SUBVET OR AREA	
Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data Poster of Internation to:	2002 2012 0 ==0	(2,		1	
Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data **TOTICE OF INTERPRETOR TO: **TOTICE TREAT MULTIPLE COMPLETE ALTREAMS ALTREAMS ALTREAMS CARING **SANCOUR CALIFORM COMPLETE ALTREAMS ALTREAMS ALTREAMS CARING **SANCOUR CHAPT ALTREAMS ALTREAMS ALTREAMS **Other) Convert Gas Lift to Rod Pump XX			F, RT, GR. etc.)		_
TEST WATER SEUT-OFF POLL OR ALTER CASING WATER SEUT-OFF REFARENCE WELL ALTERING CONTROL TRAINING CASING WELL ALTERING CONTROL TRAINING CASING ALTERING WELL ALTERING CONTROL TRAINING CASING ALTERING CONTROL TRAINING CASING ALTERING CONTROL TRAINING CASING ALTERING CONTROL TRAINING CASING ALTERING CONTROL TO ACCURATE TRAINING CASING ALTERING CONTROL TO ACCURATE TRAINING CONTROL TRAINING CONTROL TO ACCURATE TRAINING CONTROL TRAINING CONTROL TO ACCURATE TRAINING CONTROL TRAINING CONTROL TRAINING CONTROL TO ACCURATE TRAINING CONTROL	43-013-30107	0040 KB		Ducheshe Oca	11
TEST WATER SEUT-OFF PARCTURE TREAT MULTIPLE COMPLETE BROOTING OR ACTIDIES CHAPGE PLANE COMPOSE PLANE COMPOSE PLANE CONTROL FOR CONTROL OR ACTIDIES BEFAIR WELL COMPOSE PLANE CONTROL OR ACTIDIES CONTROL OR CONTROL OR ACTIONS CONTROL OR CONTROL OR ACTIONS CONTROL OR CONTROL OR ACTIONS CONTROL OR CONTROL OR CONTROL OR CONTROL OR CONTROL CONTROL	Check	Appropriate Box To Indicate I			
PRACTURE TREAT SMOOT OR ACIDIES GEVAIR WELL CHAPGE PLANS (Other) Convert Gas Lift to Rod Pump WX. (Other) Convert Gas Lift to Rod Pump SECRIES FROMTHE TO COMPLETE OF STATE OF OF ST	NOTICE OF IN		8036808	PART ESPOST OF:	
SHOOT OR ACIDES REPAIR WELL (Other) Convert Gas Lift to Rod Pump XX (Other) Convert Gas Lift to Rod Pump XX (Other) Convert of C	TEST WATER SEUT-OFF	PULL OR ALTER CASING	WATER SHUT-OFF	-	
SETAIR WELL (Other) Convert Gas Lift to Rod Pump XX (Other) Convert Gas Lift to Rod Pump XX (Other) Convert Gas Lift to Rod Pump XX (North Report results of multiple completion on Recognition Report and Log forth). Descript results resulted and convert for all pertinent details and give pertinent dates, including serimated date of starting best to this week.) ANR Production Company proposes to convert the above-referenced well from gas lift to rod pump to reduce lifting costs and to increase production. I hereby cartify that the foregoing is true and correct story cartify that the foregoing is true and correct story cartify that the foregoing is true and correct story. (This space for Federal or State office use)		MULTIPLE COMPLETE	1		-
(Other) Convert Gas Lift to Rod Pump			_	ABANDONAERT	\dashv
DESCRIBE PROVOSED FOR CONTRETTS OPERATIONS (Clearly state all pertinent details, and give pertinent dates. Including estimated date of starting proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and sonce pentito this week.)* ANR Production Company proposes to convert the above-referenced well from gas lift to rod pump to reduce lifting costs and to increase production. I hereby certify that the foregoing is true and correct growth that the for			(Nors: Report results	of multiple completion on Well	
(This space for Federal or State office use) APPROVED BY DATE DATE Date	gas lift to r	od pump to reduce lifti	ing costs and to increa	ase production.	
(This open for Federal or State office use) APPROVED BY DATE					
(This space for Federal or State office use)					
(This space for Federal or State office use) APPROVED BY DATE DATE	-				
(This space for Federal or State office use) APPROVED BY DATE DATE					
(This space for Federal or State office use) APPROVED BY DATE DATE					
(This space for Federal or State office use) APPROVED BY DATE DATE					
(This space for Federal or State office use) APPROVED BY DATE DATE					
(This space for Federal or State office use) APPROVED BY DATE DATE					
(This space for Federal or State office use) APPROVED BY DATE DATE					
(This space for Federal or State office use) APPROVED BY DATE DATE				•	
(This space for Federal or State office use) APPROVED BY DATE DATE					
(This space for Federal or State office use) APPROVED BY DATE DATE	•				
(This space for Federal or State office use) APPROVED BY DATE DATE	I hereby cartific that the foregoing	ag is true and corpect			
APPROVED BY DATE	Tillean (gulatory Analyst	June 1, 19	988
	(This space for Federal or State	office use)			
CUMPAL. IS OF APPROVAL, IF ANT:	APPROVED BY			DATE	

16.


	TE OF UTAH ERVATION COMMISSION	SUBMIT IN TRIPLICATE® (Other instructions on reverse side)	5. LEASE DESIGNATION Patented	AND SERIAL NO.
SUNDRY NOTI	CES AND REPORTS ON	WELLS	6. IF INDIAN, ALLOTTE	OR TRIBE NAME
OIL GAS OTHER		See a Sell	7. UNIT AGREEMENT NA	EM
2. NAME OF OPERATOR ANR Production Con	npany	UL 11 1988	8. FARM OR LEASE NAM Doyle	12
8. Address of Operator P.O. Box 749, Denv	ver, Colorado 80201-074	DIVISION OF	9. WELL NO. 1-10B3	
4. LOCATION OF WELL (Report location cle See also space 17 below.) At surface	arly and in accordance with any State	requirements.	Altamont	RWILDCAT
2382' FNL 8	§ 2157 FWL (SE NW)		Section 10,	
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, o	ir, etc.)	12. COUNTY OR PARISH	
43-013-30187	6048' KB		Duchesne	Utah

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: TEST WATER SHUT-OFF PULL OR ALTER CASING REPAIRING WELL WATER SHUT-OFF FRACTURE TREAT MULTIPLE COMPLETE FRACTURE TREATMENT ALTERING CASING SHOOTING OR ACIDIZING SHOOT OR ACIDIZE ABANDON* ABANDONMENT*

(Other) Convert gas lift to rod pump REPAIR WELL CHANGE PLANS (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) (Other)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

Converted above-referenced well from gas lift to rod pump 6-13-88.



18. I hereby certify that the foregoing is true and correct			
signed Eileen Danni Dey	TITLE	Regulatory Analyst	DATE July 7, 1988
(This space for Federal or State office use)	A TOTAL CONTRACTOR OF THE STATE		
APPROVED BYCONDITIONS OF APPROVAL, IF ANY:	TITLE		DATE

STATE OF UTAH DEPARTMENT OF NATURAL RESOURCES

SUB! IN TRIPLICATES

(G. ... instructions on reverse side)

SUNDRY NOTICES AND COMPANY OF THE PROPOSAL TO GILL OTHER COMPANY OF THE PROPOSAL TO GILL OTHER COMPANY OF THE PROPOSAL TO THE	DIVISION OF OIL, GAS & MINING 80201-0749 ce With any State requirements.*	6. IP INDIAN, ALLOTTED OR TRIBE NAME 7. UNIT AGREEMBNY NAME B. FARM OR LEASE NAME Doyle 9. WELL NO. 1-10B3 10. FIELD AND FOOL, OR WILDCAY Altamont
ANR Production Company P.O. Box 749, Denver, Colorado Atlor of Well (Report location clearly, and in accordang also apace 17 below.)	DIVISION OF OIL, GAS & MINING 80201-0749 ce With any State requirements.*	8. FARM OR LEASE NAME Doyle 9. WELL NO. 1-10B3 10. PIELD AND POOL, OR WILDCAT
ANR Production Company ANR Production Company P.O. Box 749, Denver, Colorado Atlow of Well (Report location clearly, and in accordan also space 17 below.)	OIL, GAS & MINING 80201-0749 ce with any State requirements.*	Doyle 9. WBLL NO. 1-10B3 10. FIBLD AND FOOL, OR WILDCAT
P.O. Box 749, Denver, Colorado ATION OF WELL (Report location clearly and in accordan also space 17 below.)	OIL, GAS & MINING 80201-0749 ce with any State requirements.*	9. WBLL NO. 1-10B3 10. PIBLD AND POOL, OR WILDCAT
P.O. Box 749, Denver, Colorado carion of well (Report location clearly and in accordan also space 17 below.)	ce with any State requirements.*	1-10B3 10. PIBLD AND POOL, OR WILDCAT
ATION OF WELL (Beport location clearly, and in accordan also space 17 below.)	ce with any State requirements.	10. PIBLD AND POOL, OR WILDCAT
SUFFECE		Altamont
2382 FNL & 2137 FWI	(SE NW)	11. 8BC., T., R., M., OR BLE. AND
		SURVEY OR ARBA
		Section 10, T2S-R3W
15. DLEVATIONS (5bo)	w whether DF, MT. GR. WG.) 6048 KB	Duchesne Utah
Check Appropriate Box To	Indicate Nature of Notice, Report	, or Other Data
NOTICE OF INTENTION TO:		UBSEQUENT REPORT OF:
SET WATER SHUT-OFF PULL OR ALTER CASING	WATER SHUT-OFF	REPAIRING WELL
MULTIPLE COMPLETE	PRACTURE TREATMENT	
HOUT OR ACIDISE X ABANDON* SPAIR WELL CHANGE PLANS	SHOUTING OR ACIDIZIN	
Other)	(NOTE: Report	results of multiple completion on Well recompletion Report and Log form.)
1. MIRU. NU BOPE. POOH w/ro	ed Procedure: od pump eqpt. & tbg.	
2. Clean out 5" liner to PBTI	(13,034' KB).	
3. RIH $w/7$ " treating pkr & se	et @ <u>+</u> 10,500'.	
4. Acidize perfs from 10,581-	-13,034' (706 holes) w/21	,500 gals 15% HCL + add.
5. Swab/flow back load.		
6. POOH w/pkr. RIH w/rod pur	np eqpt & tbg. Return we	11 to production.
nereby certify that the foregoing is true and correct		
GNED Cilcolling Cing	TITLE Regulatory Analyst	DATE November 7, 1
This space for Federal or State office use)		
	TITLE	DATE

*See Instructions on Revenue Side

SUBA N TRIPLICATES (Other instructions on reverse side)

STATE OF UTAH

DIVISION OF OIL, GAS, AND MINING			5. LEASE DESIGNATION AND SERIAL NO. Patented			
SUNDRY NC (Do not use this form for pro	OTICES AND REPOR	DEGERVEN	6. IF INDIAN, ALLOTTED OR TRIBE NAME			
OIL TT OAS	4	JAN 0 5 1989	7. UNIT AGREEMBNY NAMB			
WELL A WELL OTHER		***	8. FARM OR LEASE NAME			
ANR Production (Company '	DIVISION OF	Doyle			
ADDRESS OF OFSEATOR		U.L. GAS & MINING	9. WELL NO.			
	enver, Colorado 80		1-10B3			
LOCATION OF WELL (Report location See also space 17 below.) At surface	n clearly and in accordance with	h any State requirements.	Altamont			
2382' FNL 8	2157' FWL (SENW)		11. SEC., T., E., M., OR BLE. AND SURVEY OR ARBA			
			Section 10, T2S-R3W			
PERMIT WO. 43-013-30187	15. BLEVATIONS (Show wheth		Duchesne Utah			
Check /	Appropriate Box To Indica	ate Nature of Notice, Report,				
NOTICE OF INT	TENTION TO:	# U	BEBQUENT REPORT OF:			
TEST WATER SHUT-OFF	PULL OR ALTER CASING	WATER SHUT-OFF	REPAIRING WELL			
PRACTURE TREAT	MULTIPLE COMPLETE	PRACTURE TREATMENT	ALTERING CASING			
SHOOT OR ACIDIZE	ABANDON*	SHOUTING OR ACIDIZING	ABANDONMENT*			
REPAIR WELL	CHANGE PLANS	(Other)(Note: Report re	esults of multiple completion on Well			
(Other)		Completion or Rec	completion Report and Log form.) dates, including estimated date of starting an			
1. MIRU. NU BOPE.	POOH w/rod pump e	qpt. & tbg.				
2. RIH w/4-1/8" mi1	ll & CO tools. Tag	@ 12,983'. DO 5" line	er from 13,042-13,046'.			
3. RIH w/7" treating	ng pkr & set @ 10,45	50'.				
	perfs (10,581-13,0 TP 7850#, AIR 15.5		e & 21,500 gals 15% HCL			
5. Swab/flow back 1	Load.					
6. POOH w/pkr. RIH	H w/rod pump eqpt.	& tbg. Return well to	production.			
I hereby certify that the foregoin	ig is true and correct					
The said	anni Lagrithe	Regulatory Analyst	DATE January 3, 19			
Eileen Danni I	Dey					
(This space for Federal or State	office use)					

STATE OF UTAH DIVISION OF OIL, GAS AND MINING

SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this loam for presonals to duty or to decease or plate back to a different reservoir. Out "APPLICATION FOR PERMIT" for such proposation. Out "APPLICATION FOR PERMIT" for such proposation. NAME Production Company ON BOY 100 0 000 100 000 000 000 000 000 000				5. LEASE DESIGNATION Patented	& SERIAL NO.
ANNE OF OPERATOR ANNE OF OPERATOR ANNE OF OPERATOR ANNE OF OPERATOR P. O. BON 749, Detwer, Colorado 80201-0749 In FIELD AND 7500L, OR WILDCAT Altermort Altermort Altermort In FIELD AND 7500L, OR WILDCAT Altermort Altermort Altermort In FIELD AND 7500L, OR WILDCAT Altermort Altermort Altermort In FIELD AND 7500L, OR WILDCAT Altermort Altermort Altermort In FIELD AND 7500L, OR WILDCAT Altermort Altermort Altermort In FIELD AND 7500L, OR WILDCAT Altermort Altermort Altermort In FIELD AND 7500L, OR WILDCAT Altermort Altermort Altermort Bection 10, T25-R3W Utah Color Check Appropriate Box To Indicate Nature of Notice, Report or Other Bata NOTICE OF INTENTION TO: WATER SHUT-OFF FIRACTURE TREATMENT ANAMONISMENT ORDAN APARON. CATE MORK WILL START MORTH Color APARON. CATE MORK WILL START MORTH Color APARON. CATE MORK WILL START MORTH Color Color Color Color APARON. CATE MORK WILL START MORTH Color Color Color Color Color APARON. Late formal color APARON. CATE MORK WILL START MORTH Color APARON. CATE MORK WILL START MORTH Color APARON. CATE MORK WILL START MORTH Color APARON. Late formal color APARON. CATE MORE TRANS COLOR APARON. Late more APARON. Late more APARON. CATE MORE TRANS APARON. CATE MORE TRANS COLOR APARON. CATE MORE TRANS APARON. CATE MORE TRANS COLOR APARON. CATE MORE TRANS APARON. CATE MORE TRANS COLOR APARON. CATE MORE TRANS APARON. CATE MORE TRANS COLOR APARON. CATE MORE TRANS APARON. CATE M	(Do not use this form for	proposals to drill or to deepen or plu	g back to a different reservoir.	6. IF INDIAN, ALLOTTEE	OR TRIBE NAME
ANNE OF OPERATOR ANNE PRODUCTION COMPANY ADDITION P. O. BOX 749, Denver, Colorado 30201-0749 P. D. FERLANDO, Denver, Colorado 30201-0749 P. D. BOX 749, Denver, Colorado 30201-0749 P. D. BOX 74		APPEICATION FOR PERMIT - IN			ME
ANR Production Company ANR Production Company ANR Production Company P. O. Box 749, Denver, Colorado 30201-0749 P. O. Box 749, Denver, Colorado 30201-0749 1-1003	WELL Y WELL OT	HER		1	IE .
ADRESS OF PERSANCE P. O. BOX 749, Denver, Colorado 80201-0749 1. WELLNO 1. DESCRIBE PROPERATOR P. O. BOX 749, Denver, Colorado 80201-0749 1. TEST WATER SHUT-OFF PRACTURE TREAT SHOW TO CANADOM SHUT SHOWN SH			The Mine Or rage 10	- 1.	-
P. O. Box 749, Denver, Colorado 30201-0749 P. O. Box 749, Denver, Colorado 30201-0749 10. Decaración o recurso de composito en exerciones vian any Suis requirement. Section 10, T2S-R3W Al temposito procede recore pro		npany		· · · · · · · · · · · · · · · · · · ·	
DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all persinent details, and give persinent dates, including entired and operations to flush work.) 15. Elevations (Show water DF, RT, GR, sec.) 16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO. 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all persinent details, and give persinent dates, including entired date or stateing any prepared work. If well is directionally drulled, give submurined locations and measured and true vertical depths for all markers and conspecting and proposed work. If well is directionally drulled, give submurined locations and measured and true vertical depths for all markers and conspecting and proposed work. If well is directionally drulled, give submurined locations and measured and true vertical depths for all markers and conspecting and proposed work. If well is directionally drulled, give submurined locations and measured and true vertical depths for all markers and conspecting and proposed work. If well is directionally drulled, give submurined locations and measured and true vertical depths for all markers and conspecting and proposed work. If well is directionally drulled, give submurined locations and measured and true vertical depths for all markers and conspecting and proposed work. If well is directionally drulled, give submurined locations and measured and true vertical depths for all markers and conspecting and proposed work. If well is directionally drulled, give submurined locations and measured and true vertical depths for all markers and conspecting and proposed work. If well is directionally drulled, give submurined locations and measured and true vertical depths for all markers and conspecting and proposed work. If well is directionally drulled, give submurined locations and measured and true vertical depths for all markers and conspecting and proposed work. If the poses for Federal or State of Report and Complete and Complete and Complete and		Galamada 90201-0	740	1-10R3	
AL BATTON SURVEY OR AREA SOCIETY FALL (SENW) AL BATTON SURVEY OR AREA SOCIETY FALL SOLDER SURVEY OR AREA SOCIETY OF THE SURVEY OR AREA SURVE	P. O. Box 749, De	nver, Colorado 30201-0	requirements.		R WILDCAT
As preposed ored. Lone Check Appropriate Box To Indicate Nature of Notice, Report or Other Data Notice of intention to: TEST WATER SHUT-OFF PRACTURE TREAT SUBSEQUENT AEPORT OF: WATER SHUT-OFF PRACTURE TREAT SUBSEQUENT AEPORT OF: WATER SHUT-OFF PRACTURE TREAT SUBSEQUENT AEPORT OF: WATER SHUT-OFF PRACTURE TREATMENT ALTERING CASING ALTERING CASING SUBSEQUENT AEPORT OF: WATER SHUT-OFF PRACTURE TREATMENT SUBSEQUENT AEPORT OF: WATER SHUT-OFF PRACTURE TREATMENT ALTERING CASING ALTERING CASING ALTERING CASING ALTERING CASING (Other) SUBSEQUENT AEPORT OF: WATER SHUT-OFF PRACTURE TREATMENT ALTERING CASING	See also space 17 below.)			Altamont	
Section 10, T2S-R3W 43-013-30187 Check Appropriate Box To Indicate Nature of Notice, Report or Other Data Notice of intention to: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ALTER CASING NEPAIR WELL (Other) REPAIR WELL (Other) REPAIR WELL (Other) TO DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date or thating any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical deputs for all markers and zone pertinent to this work.) * Must be accompanied by a cement verification report See attached procedure to add perfs and acidize the referenced well. 18. Thereby certify that the foregoing is true are sogreet. Signed Imputity Section (This space for Federal or State office use)		& 2157' FWL (SENW)		11. SEC., T., R., M., OR B	
Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: TEST WATER SHUT-OFF PULL OR ALTER CASING MULTIPLE COMPLETE SHOOT OR ALTORIZE ASANDON (CHANGE PLANS	V. highard high com			Section 10,	T2S-R3W
Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: WATER SMUT-OFF PULL OR ALTER CASING STRACTURE TREAT SHOOT OR AUDITE ABANDON MULTIFLE COMPLETE SHOOT OR AUDITE ABANDON MILL CLANGE FLANS (Other) APPROX. DATE MORK WILL START MATCH: 26, 1990 DATE OF COMPLETION TO ESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent detail, and give partinent date, including estimated date of intention work.) * Must be accompanied by a cement verification report See attached procedure to add perfs and acidize the referenced well. This makes for Federal or State office use) TITLE Administrative Manager DATE DATE March 2, 1990 TITLE Administrative Manager DATE March 2, 1990 TITLE Administrative Manager DATE March 2, 1990	4. APT NO	15. ELEVATIONS (Show whether	er DF, RT, GR, etc.)		
SUBSPOUNT REPORT OF: TEST WATER SHUT-OFF FRACTURE TREAT WATER SHUT-OFF FRACTURE TREAT SHOOT TO A AUDIDIE AAANDON REPAIR WELL (Other) APPROX. DATE WORK WILL START MUST BE SHOOT TREATING OR ACIDIZING APPROX. DATE WORK WILL START APPROX. DATE WORK WILL START MIST DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of training any proposed work. If well is directionally drilled, give substracte locations and measured and true vertical deputs for all markers and zone pertinent to this work.) * Must be accompanied by a cement verification report See attached procedure to add perfs and acidize the referenced well. CHAPTURE TREATION ALTERNATION ALTERNATION ALTERNACION		6048'	KB	Duchesne	Utah
TEST WATER SHUT-OFF FINACTURE TREAT SHOOT OR ACIDIZE ABANDONNENT ALTERING CASING ABANDONNENT ALTERIOR CASING ABANDONNENT ALT	đ.	heck Appropriate Box To Indicat			
FRACTURE TREAT SHOOT OR ACIDIZE REFAIR WELL CHANGE PLANS DATE OF COMPLETION PAPROX. DATE HORK WILL START MATCH 26, 1990 DATE OF COMPLETION PAPROX. DATE HORK WILL START MATCH 26, 1990 DATE OF COMPLETION PAPROX. DATE HORK WILL START MATCH 26, 1990 DATE OF COMPLETION THAT HAVE A LIGHT TO PERATIONS (Clearly state all pertinent details and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical deputs for all markers and tone pertinent to this work.) * Must be accompanied by a cement verification report See attached procedure to add perfs and acidize the referenced well. CHANGE PLANS THE PLANS TITLE Administrative Manager DATE MATCH 2, 1990 TITLE March 2, 1990 CTHIS SPACE for Federal or State office use)	NOTICE O	FINTENTION TO:	SUBSEC	QUENT REPORT OF:	
SHACTURE TREAT SHOOT OR ALIDIZE REPAIR WELL CHANGE PLANS CHANGE PLANS CHANGE REPORT TERRIES of Multiple completion on Well Combletion or Recompletion Report and Log form.) APPROX. DATE WORK WILL START March 26, 1990 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well it directionally drilled, give subsurface locations and measured and true vertical depths for all markers and core pertinent to this work.) * Must be accompanied by a cement verification report See attached procedure to add perfs and acidize the referenced well. Characteristic proposed work that the foregoing is true and sorsect Signed Timuth F. See Da (This space for Federal or State office use)	TEST WATER SHUT-OFF	PULL OR ALTER CASING	WATER SHUT-OFF	REPAIRING	WELL
SHOOT OR ACIDIZE REFAIR WELL CHANGE PLANS CHANGE PLANS CHANGE PLANS (Other) APPROX. DATE WORK WILL START March 26, 1990 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well it directionally drilled, give subsurface locations and measured and true vertical depths for all markers and tone pertinent to this work.) * Must be accompanied by a cement verification report See attached procedure to add perfs and acidize the referenced well. CHANGE PLANCE PL	FRACTURE TREAT	MULTIPLE COMPLETE	FRACTURE TREATMENT		
(Other) APPROX. DATE WORK WILL START March 26, 1990 DATE OF COMPLETION 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give partinent dates, including estimated date of starting any proposed work. If well it directionally drilled, give subsurface locations and measured and true vertical deputs for all markers and cone pertinent to this work.) * Must be accompanied by a cement verification reporting the pertinent date of the referenced well. Characteristic that the foregoing is true and sorrect signed that the foregoing is t	3.7	ABANDON	SHOOTING OR ACIDIZING	ABANDONM	ENT*
NPPROX. DATE MORK WILL START March 26, 1990 DATE OF COMPLETION DATE OF COMPLETION STARTING May proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical deputs for all markers and some pertinent to this work.) * Must be accompanied by a cement verification report See attached procedure to add perfs and acidize the referenced well. Ch. Administrative Manager March 2, 1990 Title Administrative Manager DATE March 2, 1990 Title Administrative Manager DATE March 2, 1990	REPAIR WELL	CHANGE PLANS	(Other)	of multiple completion (n Well
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zone pertinent to this work.) * Must be accompanied by a cement verification report. See attached procedure to add perfs and acidize the referenced well. Characteristic proposed well. Characteristic pertinent to this work.) 18. I hereby certify that the foregoing is true and sorrect. SIGNED THIOUTHY To Septemble TITLE Administrative Manager (This space for Federal or State office use)			Completion or Reco	mpletion Report and Los	(form.)
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zone pertinent to this work.) * Must be accompanied by a cement verification report. See attached procedure to add perfs and acidize the referenced well. Characteristic proposed well. Characteristic pertinent to this work.) 18. I hereby certify that the foregoing is true and sorrect. SIGNED THIOUTHY To Septemble TITLE Administrative Manager (This space for Federal or State office use)	SORROY DATE WORK WILL	START March 26, 1990	DATE OF COMPLETION _		
CHANGE (This space for Federal or State office use)	·	ocedure to add perfs a			erification report
18. I hereby certify that the foregoing is true and correct SIGNED TIMOLITY F. SCHEDA (This space for Federal or State office use)	see attached pr	ocedure to add peris a	nd actuize the referen	CCC WCII.	
3. MICROSPLA 4. FILE SIGNED TIMOLITY T. SCHOOL (This space for Federal or State office use)				<u>O</u> L/	
3. MICROSPLA 4. FILE SIGNED TIMOLITY T. SCHOOL (This space for Federal or State office use)				1.	
18. I hereby certify that the foregoing is true and sorrect SIGNED TIMOTHY F. Sch Da (This space for Federal or State office use)				1	
18. I hereby certify that the foregoing is true and sorrect SIGNED TIMOTHY F. Sch Da (This space for Federal or State office use)					
18. I hereby certify that the foregoing is true and correct SIGNED TIMOLTY F. Sch Da (This space for Federal or State office use) Administrative Manager DATE March 2, 1990				2	
SIGNED TIMOTHY F. Scalba TITLE Administrative Manager DATE March 2, 1990 (This space for Federal or State office use)	18. I hereby certify that the fo	regoing is true and correct		And the second s	<u>-</u>
(This space for Federal or State office use)	·)(Irma	Que SCE TITLE	Administrative Mana	ger DATE Mar	ch 2, 1990
APPROVED BY TITLE DATE	(This space for Federal or			e se	Service Committee
	APPROVED BY	TITLE		DATE	<u> </u>

(3/89)

Wasatch Stimulation Procedure Doyle #1-10B3 Section 10, T2S, R3W Altamont Field Duchesne County, Utah

February 22, 1990

WELL DATA

Location:

2382' FNL and 2157' FWL, Section 10, T2S, R3W

Elevation:

6033' GL, 6048' KB

Total Depth:

13,195'

PBTD:

13,046'

Casing:

13-3/8" 68# K-55 ST&C set @ 306' w/275 sxs

9-5/8" 40# K-55 ST&C and LT&C set @ 6200' w/860 sxs 7" 26# & 29# CF-95 LT&C set @ 10,754' w/620 cu ft

5" 18# Hydril SFJ-P, SOO-95, N-80 liner set from 10,577'-13,195'

w/520 sxs

Tubing:

2-7/8" 6.5# N-80 EUE

TAC: Rods: Mountain States TAC @ 11,950'
1" 130 jts 3256' Norris 97

7/8" 125 jts 3125' Norris 97 3/4" 197 jts 4925' Norris 97 1-5/8" 12 jts 300' Sinker Bars

Hyland 2-1/2" x 1-1/2" x 24 x 26 RHBC Pump

Tubular Data:

Iubulai baca.		_			
Description	ID	Drift	Capacity	<u>Burst</u>	<u>Collapse</u>
	 -		(B/F)	(psi)	(psi)
9-5/8" 40# K-55 ST&C & LT&C	8.835"	8.679"	0.0758	3950	2570
7" 29# CF-95 LT&C	6.184"	6.059"	0.371	9690	7820
7" 26# CF-95 LT&C	6.276"	6.151"	0.382	8600	5870
5" 18# Hydril SFJ-P	4.276"	4.151"	0.0177	10140	10490
5" 18# SOO-95 LT&C	4.276"	4.151"	0.0177	12040	12010
5" 18# N-80 LT&C	4.276"	4.151"	0.0177	10140	10490
2-7/8" 6.5# N-80 EUE	2.441"	2.347"	0.00579	10570	11160
3-1/2" 6.5# N-80	2.992"	2.867"	0.00870	10160	10530

Present Status: Rod pumping 4 BOPD, 10 BWPD, 40 MCFPD

PROCEDURE

- 1. MIRU service rig. Kill well, NU BOPE. POOH w/rod pump equipment and 2-7/8" tubing.
- 2. RU wireline service company. RIH w/an EZ drill CIBP and set @ ±11,115'. Spot 2 sxs of cement on top (cmt top @ ±11,092').

Wasatch Stimulation procedure Doyle #1-10B3 February 22, 1990 Page Two

PROCEDURE (Cont.)

- 3. RIH w/3-1/8" csg gun, 120° phasing, 3 SPF and add infill perfs in the Upper Wasatch Transition from 10,584' to 11,031', 27 settings, 81 holes. POOH. RIH w/4" csg gun, 120° phasing, 3 SPF and perforate the upper and main pays of the Green River from 9213'-10,575', 95 settings, 285 holes (122 total settings and 366 total holes, see attached prog).
- 4. PU & RIH w/7" treating pkr w/ on/off tool and 3-1/2" 6.5# N-80 tubing. Set pkr @ ± 9180 '.
- 5. Acidize perforations from 9213' to 11,115' (366 new and 111 old) w/14,520 gals 15% HCl w/470 ball sealers and specified additives. Max treating pressure 8500 psi. Note: Acid job should be designed to include:
 - A) All fluids to be heated to 150°F.
 - B) Precede acid w/250 bbls 3% KCl w/10 gals per 1000 scale inhibitor and 500 gals Xylene.
 - C) All water to contain 3% KCl.
 - D) Acidize w/3 stages of 4840 gals each and 2 diverter stages of 1420 gelled saltwater with 1/2#/gal each Benzoic acid flakes and rock salt.
- 6. Flow/swab back acid load.
- 7. If well flows, drop standing valve and POOH w/3-1/2" tbg. RIH w/2-7/8" production string. Latch onto pkr, retrieve standing valve and return on line. When well dies proceed to Step 8.
- 8. Release pkr, POOH and lay down.
- 9. RIH w/production equipment and return on line.

SCP:cam

Perforation Schedule
Doyle #1-10B3
NW/4 Sec. 10, T2S-R3W
Duchesne County, Utah

Depth Reference: Schlumberger: BHC Sonic-GR 2/11/73, 1/18/73

11031	10892	10592	10250	9917	9620	9430
11021	10872	10584	10248	9912	9616	9428
11014	10856	10575	10246	9905	9603	9424
11000	10842	10570	10236	9899	9597	9414
10917	10786	10568	10232	9893	9586	9410
10917	10778	10557	10222	9885	9578	9406
10912	10773	10537	10167	9882	9574	9403
	10772	10534	10161	9877	9571	9384
	10742	10520	10159	9808	9555	9353
	10732	10512	10155	9785	9539	9327
	10732	10449	10150	9773	9514	9297
	10728	10439	10140	9770	9504	9282
	10717	01414	10132	9763	9502	9270
	10691	10412	10129	9755	9489	9260
	10661	10411	10121	9694	9470	9257
	10655	10351	10119	9678	9468	9250
	10635	10345	10086	9668	9450	9240
		10287	9931	9664	9449	9235
	10633	10275	9925	9662	9434	9230
	10599	102/3	3943	9002	9 7 3 7	9217
						9217
						7413


Recommended perforations 11,031'-9,213', total 122 feet, 44 zones.

PLR 7/21/87 REWISED 7/26/89 Doyle #1-1003

SECTION 10, T25, R3W

ALTAMONT FIELD - DUCHERUS CO

UTAH



STATE OF UTAH DIVISION OF OIL, GAS AND MINING

			Patented)n 4 serial no.
(Do not use this form for	HOTICES AND REPORTS proposals to drill or to deepen or plu APPLICATION FOR PERMIT—" for	g back to a different reservoir.	6. IF INDIAN. ALLOTT	EE OR TRIBE NAM
OIL X GAS OTH			7. UNIT AGREEMENT N/A	МАМЕ
AME OF OPERATOR		~ JUN 14 1 990 +	8. FARM OR LEASE N.	AME
ANR Production Com	pany		Doyle	
DDRESS OF OPERATOR	row Colomada 20201 07	7.0 Mar. 10.0 Ma	9. WELL NO.	
	ver, Colorado 80201-07		1-10B3	OR WILDCAT
ce also space i 7 below.)			Altamont	
2382 FNL &	2157' FWL (SENW)		11. SEC. T. R. M. OR SURVEY OR	
Same as abov	e			
API NO.	115. ELEVATIONS (Show whether	er DF. RT. GR. etc.)	Section 10,	125-K3W
43-013-30187	· ·	KB	Duchesne	Utah
	Look Appropriate Pay To Indian	o Matura of Marina Danast as	Other Date	
	eck Appropriate Box To Indicat	·	U (DET DATA SEQUENT REPORT OF:	
		50a.		
TEST WATER SHUT-OFF	PULL OR ALTER CASING	WATER SHUT-OFF	REPAIRIN	1—1
FRACTURE TREAT SHOOT OR ACIDIZE	MULTIPLE COMPLETE	FRACTURE TREATMENT SHOOTING OR ACIDIZING	X ABANDON	. I
	 	· -	L	
REPAIR WELL	CHANGE PLANS	(Other)	The second secon	
(Other)	CHANGEPLANS	(Note: Report rest	uits or multiple completion	og (orm.)
APPROX. DATE WORK WILL S DESCRIBE PROPOSED OR	STARTCOMPLETED OPERATIONS (Clear	(Note: Report rest Completion or Re DATE OF COMPLETION	May 26, 1990	og form.) ng estimated date
APPROX. DATE WORK WILL S DESCRIBE PROPOSED OR	START	(Note: Report rest Completion or Re- DATE OF COMPLETION by state all pertinent details, and gi	May 26, 1990	og (orm.) ng estimated date ll markers and zo
APPROX. DATE WORK WILL S DESCRIBE PROPOSED OR starting any proposed work. If Apertinent to this work.)	STARTCOMPLETED OPERATIONS (Clear f well is directionally drilled, give sub	(Note: Report rest Completion or Re- DATE OF COMPLETION by state all pertinent details, and gi	May 26, 1990 We pertinent dates, including true vertical depths for a	og (orm.) ng estimated date ll markers and zo
APPROX. DATE WORK WILL S DESCRIBE PROPOSED OR estarting any proposed work. If Appertinent to this work.) May 17-26, 1990: 1) MIRU. POOH w/re	STARTCOMPLETED OPERATIONS (Clear f well is directionally drilled, give sub	(Note: Report rest Completion or Re- DATE OF COMPLETION by state all pertinent details, and gi sturface locations and measured and * Must be accomp	May 26, 1990 We pertinent dates, including true vertical depths for a	og (orm.) ng estimated date ll markers and zo
APPROX. DATE WORK WILL S DESCRIBE PROPOSED OR estarting any proposed work. If Appertinent to this work.) May 17-26, 1990: 1) MIRU. POOH w/ro 2) RIH and set CII 3) RIH w/pkr. and	COMPLETED OPERATIONS (Clear f well is directionally drilled, give and ods and tubing BP @ 11,115'. Dumped 3-1/2" tbg. Perfed Up	(Note: Report rest Completion or Re DATE OF COMPLETION Ty state all persinent details, and give sturface locations and measured and * Must be accompacted and the sturface locations and the sturface locations and measured and the sturface locations and the sturface l	May 26, 1990 We pertinent dates, including true vertical depths for a companied by a cement	og form.) ng estimated date ill markers and zo verification rep
DESCRIBE PROPOSED OR starting any proposed work. If Appertinent to this work.) May 17-26, 1990: 1) MIRU. POOH w/ro 2) RIH and set CII 3) RIH w/pkr. and 3 SPF, 366 tota	COMPLETED OPERATIONS (Clear well is directionally drilled, give and ods and tubing BP @ 11,115'. Dumped 3-1/2" tbg. Perfed Up al holes. Set pkr. @ 9	(Note: Report rest Completion or Re DATE OF COMPLETION Ty state all pertinent details, and give sturface locations and measured and * Must be accompact 2 sx. cmt. on plug per Wasatch transition 167'. Press. test csg.	May 26, 1990 We pertinent dates, including true vertical depths for a companied by a cement on from 9213-11, to 2000 psi.	og form.) ng estimated date il markers and zo verification rep 031', OK
APPROX. DATE WORK WILL S DESCRIBE PROPOSED OR of starting any proposed work. If Apertinent to this work.) May 17-26, 1990: 1) MIRU. POOH w/ro. 2) RIH and set CII 3) RIH w/pkr. and 3 SPF, 366 tota 4) Acidized perfs	COMPLETED OPERATIONS (Clear well is directionally drilled, give and ods and tubing BP @ 11,115'. Dumped 3-1/2" tbg. Perfed Up at holes. Set pkr. @ 9 (9213-11,115') w/14,5 3-1/2" tbg. RIH w/row	(Note: Report rest Completion or Re DATE OF COMPLETION Ty state all pertinent details, and gis sourface locations and measured and * Must be accompact to the state of the st	May 26, 1990 We pertinent dates, including true vertical depths for a companied by a cement on from 9213-11, to 2000 psi. Idditives. Swab	og form.) ng estimated date ill markers and zo verification rep 031', OK dry.
APPROX. DATE WORK WILL S DESCRIBE PROPOSED OR STATEMENT OF PROPOSED OR STATEMENT OR STATEMENT OF PROPOSED OR STATEMENT OR STATEMENT OF PROPOSED OR STATEMENT OF PROPOSED OR STATEMENT OR STATEMENT OF PROPOSED OR STATEMENT OF PROPOSED OR STATEMENT OR STATEMENT OF PROPOSED OR STATEMENT OF PROPOSED OR STATEMENT OR STATEMEN	COMPLETED OPERATIONS (Clear f well is directionally drilled, give subtoods and tubing BP @ 11,115'. Dumped 3-1/2" tbg. Perfed Upal holes. Set pkr. @ 9 (9213-11,115') w/14,5 3-1/2" tbg. RIH w/rodd.	(Note: Report rest Completion or Re DATE OF COMPLETION Ty state all pertinent details, and gis sourface locations and measured and * Must be accompact to the state of the st	May 26, 1990 We pertinent dates, including true vertical depths for a companied by a cement on from 9213-11, to 2000 psi. Idditives. Swab	og form.) ng estimated date ill markers and zo verification rep 031', OK dry.
APPROX. DATE WORK WILL S DESCRIBE PROPOSED OR of starting any proposed work. If Apertinent to this work.) May 17-26, 1990: 1) MIRU. POOH w/ro. 2) RIH and set CII. 3) RIH w/pkr. and 3 SPF, 366 tota. 4) Acidized perfs 5) POOH w/pkr. on ND BOP's. NUWH.	COMPLETED OPERATIONS (Clear f well is directionally drilled, give subtoods and tubing BP @ 11,115'. Dumped 3-1/2" tbg. Perfed Upal holes. Set pkr. @ 9 (9213-11,115') w/14,5 3-1/2" tbg. RIH w/rodd.	(Note: Report rest Completion or Re DATE OF COMPLETION Ty state all pertinent details, and gis sourface locations and measured and * Must be accompact to the state of the st	May 26, 1990 We pertinent dates, including true vertical depths for a companied by a cement on from 9213-11, to 2000 psi. Idditives. Swab	og form.) ng estimated date ill markers and zo verification rep 031', OK dry.
APPROX. DATE WORK WILL S DESCRIBE PROPOSED OR (starting any proposed work.) May 17-26, 1990: 1) MIRU. POOH w/ro 2) RIH and set CII 3) RIH w/pkr. and 3 SPF, 366 tota 4) Acidized perfs 5) POOH w/pkr. on ND BOP's. NUWH 6) Return well to	COMPLETED OPERATIONS (Clear well is directionally drilled, give and ods and tubing BP @ 11,115'. Dumped 3-1/2" tbg. Perfed Up al holes. Set pkr. @ 9 (9213-11,115') w/14,5 3-1/2" tbg. RIH w/rowl. production.	(Note: Report rest Completion or Re DATE OF COMPLETION Ty state all pertinent details, and gis sourface locations and measured and * Must be accompact to the state of the st	May 26, 1990 We pertinent dates, including true vertical depths for a companied by a cement on from 9213-11, to 2000 psi. Idditives. Swab	og form.) ng estimated date ill markers and zo verification rep 031', OK dry.
APPROX. DATE WORK WILL S DESCRIBE PROPOSED OR of starting any proposed work. If Apertinent to this work.) May 17-26, 1990: 1) MIRU. POOH w/ro. 2) RIH and set CII. 3) RIH w/pkr. and 3 SPF, 366 tota. 4) Acidized perfs 5) POOH w/pkr. on ND BOP's. NUWH.	completed operations (Clear well is directionally drilled, give subsequently drilled, give subsequentl	(Note: Report rest Completion or Recompletion of Recompletion or Recompletion	May 26, 1990 Ive pertinent dates, including true vertical depths for a companied by a cement on from 9213-11, to 2000 psi. Idditives. Swab @ 10,522' w/20,	og form.) ng estimated date ill markers and zo verification rep 031', OK dry.

STALLE OF UTAH

DEPARTMENT OF NATURAL RESOU DIVISION OF OIL. GAS AND MI	NING Patented
SUNDRY NOTICES AND REPORTS So not use this form for proposals to drill new welfs; deeden existing welfs; or to Use APPLICATION FOR PERMIT— (or put)	
Use APPLICATION FOR PERMIT— for such pro	a. Unit or Communitization Agreement N/A
	9. Well Name and Number
ANR Production Company	Doyle #1-10B3 10. API Well Number 43-013-30187
P.O. Box 749 Denver, CO 80201-0749	4. Telephone Number (303) 573-4476 11. Field and Pool, or Wildcat Altamont
2382 FNL & 2157 FWL QQ. Sec. T. R. M.: SE/NW Section 10, T2S, R3W CHECK APPROPRIATE BOXES TO INDICATE I NOTICE OF INTENT (Submit in Outplicate)	County: Duchesne State: UTAH NATURE: OF NOTICE: REPORT, OR OTHER DATA SUBSCOLUTIONS
Abandonment New Construction Casing Repair Pull or Alter Casing Change of Plans Recompletion Conversion to Injection Shoot or Acidize Fracture Treat Vent or Flare Multiple Completion Water Shut-Off Other Paraffin Control Stimulation	SUBSEQUENT REPORT (Submit Original Form Only) Abandonment ' New Construction Casing Repair Pull or Alter Casing Change of Plans Shoot or Acidize Conversion to Injection Vent or Flare Fracture Treat Water Shut-Off Other
pproximate Date Work Will Start 11/15/92	Date of Work Completion Report results of Multiple Completions and Recompletions to different reservo on WELL COMPLETION OR RECOMPLETION AND LOG form. * Must be accompanied by a cement verification report. ment details, and give pertinent dates. If well is directionally drilled, give subsurfacement to this work.)

Please see the attached proposed paraffin control stimulation procedure to be performed on the abovereferenced well.

007 1 6 1992

ENROR CO. THE PARTY OF THE

. I hereby certify that the loregoing is true and correct

me & Signature

ate Use Only)

Title

GREEN RIVER STIMULATION PROCEDURE

Doyle #1-10B3 Section 10, T2S, R3W Altamont Field Duchesne County, Utah

WELL DATA

Location: 2382' FNL and 2157' FWL, Section 10, T2S, R3W

Elevation: 6033' GL, 6048' KB

Total Depth: 13,195' PBTD: 11,104'

Casing: 13-3/8" 68# K-55 ST&C set at 306' w/275 sxs

9-5/8" 40# K-55 ST&C and LT&C set @ 6200' w/860 sxs 7" 26# & 29# CF-95 LT&C set @ 10,754' w/620 cu ft

5" 18# Hydril SFJ-P, S00-95, N-80 liner set from 10,577'-13,195'

w/520 sxs

Tubular Data:

<u>Description</u>	ID	Drift	Capacity	Burst	Collapse
		<u> </u>			
0 F (0 !! 40 !! !! Em 0			(B/F)	(PSI)	(PSI)
9-5/8" 40# K-55 ST&C & LT&C	8.835"	8.679"	0.0758	3950	2570
7" 29# CF-95 LT&C	6.184"	6.059"	0.371	9690	7820
7" 26# CF-95 LT&C					. — .
	6.276"	6.151"	_• 0 y382	8600	5870
5" 18# Hydril SFJ-P	4.276"	4.151"	0.0177	10140	10490
5" 18# SOO-95 LT&C	4.276"	4.151"	0.0177	12040	
				12040	12010
5" 18# N-80 LT&C	4.276"	4.151"	0.0177	10140	10490
2-7/8' 6.5# N-80 EUE	2.441"	2.347"	0.00579	10570	11160
3-1/2" 6.5# N-80	2.992"	2.867"			
0 1/2 0.011 11 00	2.332	2.007	0.00870	10160	10530

Producing Perforations: 9213' to 11,115' (477 total holes)

Present Status: SI due to poor economics. On 56 day production cycle.

PROCEDURE

- MIRU service rig. Kill well, NU BOPE. POOH w/rod pump equipment and 2-7/8" tubing.
- 2. PU & RIH w/4-1/8" mill and CO tools. CO 5" liner to PBTD @ \pm 11,104'. POOH.
- 3. PU & RIH w/7" HD pkr and $3\frac{1}{2}$ " tbg. Set pkr @ \pm 9100'.
- 4. MIRU The Western Company. Perform 10,000 gallon condensate treatment of perforations 9213' to 11,115', 477 total holes, per the attached recommendation. Max treating pressure 8500 psi. NOTE: Condensate job should be designed to include:
 - A) Precede condensate w/250 bbls 3% KCl w/10 gals per 1000 gals scale inhibitor. Heat wtr to 110°F. Evenly space 100 1.3 s.g. BS's throughout.
 - B) Condensate will be divided into 4 equal stages of 2500 gals (1875 gals condensate, 625 gals diesel). There will be 3 diverter stages each containing 239 1.3 s.g. BS's and 2800 gals of fluid.

Green River Stimulation Procedure Doyle #1-10B3
Page Two

- C) 250 bbls KCl wtr pad (in A above) is the \underline{only} fluid which will be heated. No other fluids to be heated. Check w/pkr supplier for tbg stretch calculations. Tension packer may be required for this job.
- 5. Swab load back. Release pkr, POOH and LD 3½" tbg.
- 6. PU & RIH w/solid plug w/5-7/8" OD blades, 10' long $4\frac{1}{2}$ " PBGA, 4' 2-7/8" pup jt, + 45 SN, 7 jts 2-7/8" N-80 tbg, 7" TAC, and 2-7/8" tbg. Btm of down hole assembly should be 0 ± 9168 ' and SN should be 0 ± 9150 '.
- 7. PU & RIH w/1-3/4" or 1-1/2" pump (consult w/Denver office), depending on results of stimulation, 175' 1", 3025' 3/4", 3025' 7/8", 2925' 1". Return on line.

SCP:cam

Form 9

STATE OF UTAH

DEPARTMENT OF NATURAL RESOURCES 6. Lease Designation and Serial Number DIVISION OF OIL. GAS AND MINING Patented Indian Allottee or Tribe Name N/A SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to driff new-wells; deepen existing wells; or to reenter plugged and abandoned wells. 8. Unit or Communitization Agreement Use APPLICATION FOR PERMIT—(or such proposals N/AType of Well 3. Well Name and Number Well Well Gas Other (specify) Doyle #1-10B3 2. Name of Operator 10. API Well Number ANR Production Company 43-013-30187 I. Address of Operator Telephone Number (303) 573-4476 11. Field and Poot, or Wildow P.O. Box 749 Denver, CO 30201-0749 Altamont 5 Location of Well 2382' FNL & 2157' FWL Footage County : Duchesne QQ. Sec. T., R., M. ; SE/NW Section 10, T2S, R3W : UTAH State CHECK APPROPRIATE BOXES TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA NOTICE OF INTENT SUBSEQUENT REPORT (Submit in Duplicate) (Submit Original Form Only) Abandonment New Construction Abandonment ' **New Construction** Casing Repair Pull or Alter Casing Casing Repair Pull or Alter Casing Change of Plans Recompletion Change of Plans Shoot or Acidize Conversion to Injection Shoot or Acidize Conversion to Injection Vent or Flare Fracture Treat Vent or Flare Fracture Treat Water Shut-Off Multiple Completion Water Shut-Off Other Other Paraffin Control Stimulation Date of Work Completion Approximate Date Work Will Start Report results of Multiple Completions and Recompletions to different res ON WELL COMPLETION OR RECOMPLETION AND LOG FORTE Must be accompanied by a cament verification report. 1. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

> Please see the attached procedure for the paraffin control stimulation to be performed on the above-

referenced well.

OCT 2 9 1992

DIVISION OF OIL GAS & MINING

boson		<u> </u>				
or nereby centry that th	e loregeing is true and correct	1 11111111111				
ime & Signature	1/ Clean	Millel Clay	Title	Regulatory Analys	t	10/27/92
iate Use Only)	(Lileen Danni)	y 			Uate	20/27/32

12/92 Watkeus

GREEN RIVER STIMULATION PROCEDURE

Doyle #1-10B3 Section 10, T2S, R3W Altamont Field Duchesne County, Utah

WELL DATA

Location: 2382' FNL and 2157' FWL, Section 10, T2S, R3W

Elevation: 6033' GL, 6048' KB

Total Depth: 13,195' PBTD: 11,104'

Casing: 13-3/8" 68# K-55 ST&C set at 306' w/275 sxs

9-5/8" 40# K-55 ST&C and LT&C set @ 6200' w/860 sxs 7" 26# & 29# CF-95 LT&C set @ 10,754' w/620 cu ft

5" 18# Hydril SFJ-P, S00-95, N-80 liner set from 10,577'-13,195'

w/520 sxs

Tubular Data: <u>Description</u>	ID	Drift	Capacity (B/F)	<u>Burst</u> (PSI)	<u>Collapse</u> (PSI)
9-5/8" 40# K-55 ST&C & LT&C 7" 29# CF-95 LT&C 7" 26# CF-95 LT&C 5" 18# Hydril SFJ-P 5" 18# S00-95 LT&C 5" 18# N-80 LT&C 2-7/8' 6.5# N-80 EUE 3-1/2" 6.5# N-80	8.835"	8.679"	0.0758	3950	2570
	6.184"	6.059"	0.371	9690	7820
	6.276"	6.151"	0.382	8600	5870
	4.276"	4.151"	0.0177	10140	10490
	4.276"	4.151"	0.0177	12040	12010
	4.276"	4.151"	0.0177	10140	10490
	2.441"	2.347"	0.00579	10570	11160
	2.992"	2.867"	0.00870	10160	10530

Producing Perforations: 9213' to 11,115' (477 total holes)

Present Status: SI due to poor economics. On 56 day production cycle.

PROCEDURE

- 1. MIRU service rig. Kill well, NU BOPE. POOH w/rod pump equipment and 2-7/8" tubing.
- 2. PU & RIH w/4-1/8" mill and CO tools. CO 5" liner to PBTD @ \pm 11,104'. POOH.
- 3. PU & RIH w/7" HD pkr and 3½" tbg. Set pkr $@\pm$ 9100'.
- 4. MIRU The Western Company. Perform 10,000 gallon condensate treatment of perforations 9213' to 11,115', 477 total holes, per the attached recommendation. Max treating pressure 8500 psi. NOTE: Condensate job should be designed to include:
 - A) Precede condensate w/250 bbls 3% KCl w/10 gals per 1000 gals scale inhibitor. Heat wtr to $110^\circ F$. Evenly space 100 1.3 s.g. BS's throughout.
 - B) Condensate will be divided into 4 equal stages of 2500 gals (1875 gals condensate, 625 gals diesel). There will be 3 diverter stages each containing 239 1.3 s.g. BS's and 2800 gals of fluid.

Green River Stimulation Procedure Doyle #1-10B3
Page Two

- C) 250 bbls KCl wtr pad (in A above) is the <u>only</u> fluid which will be heated. No other fluids to be heated. Check w/pkr supplier for tbg stretch calculations. Tension packer may be required for this job.
- 5. Swab load back. Release pkr, POOH and LD 3½" tbg.
- 6. PU & RIH w/solid plug w/5-7/8" OD blades, 10 long 4 %" PBGA, 4 2-7/8" pup jt, + 45 SN, 7 jts 2-7/8" N-80 tbg, 7" TAC, and 2-7/8" tbg. Btm of down hole assembly should be @ \pm 9168' and SN should be @ \pm 9150'.
- 7. PU & RIH w/1-3/4" or 1-1/2" pump (consult w/Denver office), depending on results of stimulation, 175' 1", 3025' 3/4", 3025' 7/8", 2925' 1". Return on line.

SCP:cam

DEPARTMENT OF NATURAL RESOURCE DIVISION OF CIL. GAS AND MINII	NG Patented
SUNDRY NOTICES AND REPORTS C So not use this form for proposals to drill new welfs; deeden existing welfs; or to red Use APPEICATION FOR PERMIT—for such propo	ROLLER CHILDREN AND ADDRESS OF THE PARTY OF
Signature of Operator ANR Production Company	N/A 9. Well Name and Number Doyle #1-10B3
P.O. Box 749 Denver, CO 80201-0749	43-103-30187 4. Telephone Number (303) 573-4476 11. Field and Pool, or Wildest Altamont
QQ. Sec. T. R. M. : SE/NW Section 10. T2S-R3W	County: Duchesne State: UTAH ATURE OF NOTICE: REPORT, OR OTHER DATA
Abandonment New Construction	SUBSEQUENT REPORT (Submit Original Form Only) Abandonment New Construction Casing Repair Pull or Alter Casing Change of Plans Shoot or Acidize Conversion to Injection Vent or Flare Fracture Treat Water Shut-Off Cother Report of Spill (R615-3-32) Date of Work Completion
-	Report results of Multiple Completions and Recompletions to different reservoirs on WELL COMPLETION OR RECOVER STOWN

Must be accompanied by a cament verification report. 1. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Cleany state all pertinent details, and give pertinent dates. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

A spill was discovered approximately 400' from the Doyle #1-10B3 wellhead @ 11:00 a.m., 10/30/92. Leak occurred from a hole in the 2" disposal line which originates from the #1-11B3 well location (Section 11, T2S-R3W). Approximately 200 bbls of produced water & 5 bbls of oil was leaked onto the surrounding grounds. None of the spilled liquid was recovered, however the interface (oil) was cleaned up. The damaged section of disposal line was dug up and capped and the area then backfilled. It took 6 hours to control and cleanup this spill. There is no resultant damage known to the area affected by the spill. The only damage to equipment was the hole in the disposal line.

hereby certify that the loredoing is true and corfect

ime & Signature

ate Use Only)

Regulatory Analyst Oato 1-8-93

ATE OF UTAH DIVISION OF OIL, GAS AND MINING

			5. Lease Designation and Serial Number:
			Patented
SUNDRY	6. If Indian, Allottee or Tribe Name: N/A		
Do not use this form for proposals to drill new wells, deepen existing wells, or to reenter plugged and abandoned wells. Use APPLICATION FOR PERMIT TO DRILL OR DEEPEN form for such proposals.			7. Unit Agreement Name: N/A
1. Type of Well: OIL T GAS	OTHER:		8. Well Name and Number: Doyle #1-10B3
2. Name of Operator: ANR Production Co	nin anv		9. API Well Number:
3. Address and Telephone Number:	mparry		43-013-30187
•	ver, CO 80201-0749	(303) 573-4476	10. Field and Pool, or Wildcat: Altamont
4. Location of Well			
Footages: 23	82' FNL & 2157' FWL		county: Duchesne
QQ, Sec.,T.,R.,M.: (S	E/NW) Section 10, T2s-R3	W	state: Utah
11. CHECK APPRO	PRIATE BOXES TO INDICATE	NATURE OF NOTICE, REPO	ORT, OR OTHER DATA
	CE OF INTENT mit in Duplicate)	ì	EQUENT REPORT It Original Form Only)
☐ Abandonment	□ New Construction	☐ Abandonment *	☐ New Construction
Casing Repair	☐ Pull or Alter Casing	☐ Casing Repair	☐ Pull or Alter Casing
☐ Change of Plans	☐ Recompletion	☐ Change of Plans	Shoot or Acidize
☐ Conversion to Injection	☐ Shoot or Acidize	☐ Conversion to Injection	☐ Vent or Flare
☐ Fracture Treat	☐ Vent or Flare	Fracture Treat	☐ Water Shut-Off
☐ Multiple Completion	☐ Water Shut-Off	Other Cleanout, Par	_
☐ Other	_ water criation	Actie Creanout, ran	all in Control work
	· · · · · · · · · · · · · · · · · · ·	Date of work completion	_/31/93
Approximate date work will start		Report results of Multiple Completions COMPLETION OR RECOMPLETION AN	and Recompletions to different reservoirs on WELL D LOG form.
•		* Must be accompanied by a cement veri	fication report.
vertical depths for all markers and zones Please see ti	o operations (Clearly state all pertinent details, an pertinent to this work.) he attached chronological performed on the above r	l history for the clean	ed, give subsurface locations and measured and true
MAR 0 3 1993			
DIVISION OF OIL GAS & MINING			
Name & Signature: Eilleen Da	Man Dev	тны: <u>Regulatory</u>	Analyst Date: 2/26/93

(This space for State use only)

CHRONOLOGICAL HISTORY

DOYLE #1-10B3 (CLEANOUT, PARAFFIN CONTROL STIMULATE)
ALTAMONT FIELD
DUCHESNE COUNTY, UTAH
WI: 84.375% ANR AFE: 64351
TD: 13,195' PBTD: 11,104'
CSG: 5" LINER @ 10,577'-13,195'

PERFS: 9,213'-11,031' (GREEN RIVER)

CWC(M\$): 89.2

- 1/20/93 RU rig. Road rig, spot equip. SDFN @ 6:00 p.m. DC: \$1,325 TC: \$1.325
- 1/21/93 Cont POOH w/2-7/8" tbg. RU rig. Work rods & unseat pump. Re-seat pump. Fill tbg w/21 BW. PT tbg to 1000#, held. POOH w/120 1", 125 7/8", 145 3/4" and 24 1" rods. LD pump. ND prod "T". Tbg hanger stuck in WH. Work hanger free. NU BOP. Work 7" TAC free from 10,522'. POOH w/210 jts 2-7/8" tbg. SDFN @ 6:00 p.m. DC: \$4,892 TC: \$6,217
- 1/22/93 PU 7" treating pkr. Cont POOH w/122 jts 2-7/8" tbg. LD prod BHA. PU 4-1/8" mill, CO tools & 35 jts 2-3/8" tbg. Meas in hole on 2-7/8" tbg, tag 5" LT @ 10,577' WLM. Cont thru 5", tag fill @ 11,093'. CO 11' to 11,104' PBTD. POOH w/2-7/8" tbg, LD 35 jts 2-3/8" tbg & CO tools. 4-1/8" mill in good shape. Btm 2 jts 2-3/8" tbg had scale & cmt. SDFN @ 6:30 p.m. DC: \$5,497 TC: \$11,714
- 1/26/93 WO stimulation design.
- 1/27/93 WO stimulation equipment. Plan to stimulate Friday a.m., 1/29/93.
- 1/28/93 Prep to stimulate Green River. MIRU stimulation equipment.
- 1/29/93 LD 3-1/2" tbg. RU Western, stimulate Green River perfs 9,213-11,031' (477 holes) w/7500 gals #2 diesel & 2500 gals 15% HCl & additives w/717 1.1 BS's. Max rate 27.6 BPM, avg rate 25 BPM. Max press 8660 psi, avg press 8200 psi. ISIP 1800 psi, 15 min 0 psi. Good diversion. Total load 721 bbls. RD Western. SI 3-hrs. RU swab, IFL @ 6400', avg FL @ 5000', FFL @ 5900'. Rec'd 41 BW in 3-1/2 hrs. Well kicked off, would not buck HT press. Rls 7" HD pkr from 9096'. DC: \$42,299 TC: \$65,086
- 1/30/93 Cont RIH w/2-7/8" prod. LD 297 jts 3-1/2" tbg & 7" HD pkr. Change equip for 2-7/8" tbg. PU and RIH w/blank nipple, 5-3/4" No-Go, 10' 4-1/2" PBGA, 4' x 2-7/8" sub, PSN, 7 jts 2-7/8" tbg, 7" TAC & 195 jts 2-7/8" tbg. SDFN @ 6:00 p.m. DC: \$8,614 TC: \$73,700
- 1/31/93 Well producing. Cont in hole w/89 jts 2-7/8" tbg. Set 7" TAC @ 8931' in 20,000 tension. ND BOP. RIH with 1-1/2" pump, 7 1", 121 3/4" (LD 24 3/4"), 121 7/8" (LD 4 7/8") & 115 1" (LD 5 1"), seat pump. PT to 500#, held. RD. Start unit @ 5:00 p.m. DC: \$7,528 TC: \$81,228
- 1/31/93 Pmpd 51 BO, 151 BW, 127 MCF, 8 SPM/14 hrs.
- 2/1/93 Pmpd 145 BO, 119 BW, 94 MCF, 8 SPM.
- 2/2/93 Pmpd 82 BO, 182 BW, 88 MCF, 8 SPM.
- 2/3/93 Pmpd 41 BO, 91 BW, 67 MCF, 8.5 SPM.
- 2/4/93 Pmpd 42 BO, 37 BW, 54 MCF, 8.5 SPM.
 Prior prod: 0 BO, 0 BW, 0 MCF. <u>Final report</u>.

PAGE 1

DIVISION OF OIL, GAS AND MINING

			5. Lease Designation and Serial Number: Patented
SUNDRY NOTICES AND REPORTS ON WELLS			6. If Indian, Allottee or Tribe Name: N/A
Do not use this form for proposals to drill new wells, deepen existing wells, or to reenter plugged and abandoned wells. Use APPLICATION FOR PERMIT TO DRILL OR DEEPEN form for such proposals.			7. Unit Agreement Name: N/A
1. Type of Well: OIL \fbox{X} GAS \fbox{OT}	HER:		8. Well Name and Number: Doyle #1-10B3
2. Name of Operator: ANR Production Company			9. API Well Number: 43-013-30187
3. Address and Telephone Number: P.O. Box 749, Denver, CO 80201-07	49	(303) 573 – 4476	10. Field and Pool, or Wildcat: Altamont
4. Location of Well			
Footages: 2382' FNL & 2157' F	WL		County: Duchesne
QQ, Sec., T., R., M.: SE/NW Section 10-	Γ2S-R3W		State: Utah
" CHECK ADDRODDIATE	DOVEC TO INDICAT	E NATURE OF NOTICE DE	
		E NATURE OF NOTICE, RE	PORT, OR OTHER DATA
NOTICE OF INTENT (Submit In Duplicate)	•		UENT REPORT original Form Only)
Abandonment	New Construction	Abandonment *	New Construction
Casing Repair	Pull or Alter Casing	Casing Repair	Pull or Alter Casing
Change of Plans	Recompletion	Change of Plans	Shoot or Acidize
Conversion to Injection	Shoot or Acidize	Conversion to Injection	Vent or Flare
Fracture Treat	Vent or Flare	Fracture Treat	Water Shut-Off
Multiple Completion	Water Shut-Off	Other	
X Other Lower Seating Nipple			
		Date of work completion	
Approximate date work will start 9/9/94		Report results of Multiple Completions an	d Recompletions to different reservoirs on WELL
		COMPLETION OR RECOMPLETION AND	LOG form.
		Must be accompanied by a cement verific	eation report.
DESCRIBE PROPOSED OR COMPLETED OPERATIONS (CI vertical depths for all markers and zones pertinent to this wor Please see the attached workover proc	к.)		e subsurface locations and measured and true
	/1/99 Partheus	SEP - 6	
13. Name & Signature:	44	N.O. Shiflett Title: District Drilling	Manager Date: 09/02/94
(This space for State use only)	1		

WORKOVER PROCEDU.

DOYLE #1-10B3 ALTAMONT FIELD DUCHESNE COUNTY, UTAH

Well Data:

Location:

2382' FNL 2157' FWL Sec 10 6058' KB. 6033' GL 84.375% ANR

Elevation: W.I.:

Total Depth:

13,195

PBTD Perforations:

11.104' CIBP 9213-11.104

Casting

See Attached Wellbore Schematic

<u>Tubular Description:</u>

	ID	Drift	Capacity	Burst	Collapse
7" 26# C-95	6.276	6.151	. 0383	8600	5870
7" 29# C-95	6.184	6.059	. 0372	9690	7820
5" 18# N-80	4.276	4.151	.0178	10140	10490

Well History:

June 1973

First Production

Dec 1988

CO 5" liner to 13.046'. Acdz Wasatch perfs w/21.500 gals 15%

HC1.

Prior Production Rate:

13 BOPD

Post Production Rate:

25 BOPD

May 1990

G. R. Recompletion. Set CIBP @ 11.115'. Perf U. Wasatch transition. Upper & Main pays of Grn. Rvr. 9213' - 11.031', 366 holes (3 SPF 122 settings). Acdz 9213' to 11.115' (366 new & 111

old holes) w/14.520 gals 15% HCl. Prior Production Rate: 15 BOPD 170 BOPD

Jan 1993

AFE (CO, paraffin control stim.) CO 5" liner to 11,104' (found 11 of fill). Perform Diesel stimulation w/7500 gais #2 diesel & 2500 gals 15% HCl. Set TAC @ 8931 .

Prior Production Rate: 7 BOPD

Post Production Rate: 30 BOPD

PROCEDURE:

- MIRU service rig. ND/NU BOP's and test. POOH w/rods and pump. Rls AC and POOH w/ tbg.
- PU mill and CO tools. PU 2000' of 2-3/8" tubing. Crossover to 2-7/8" tbg. Hydrotest the 2-7/8" tubing during TIH. CO 5" liner to 11.104' (PBTD). 2.
- PU scraper for 5" 18# casing. Run scraper to $\pm 11,075$ '. POOH. 3.
- PU 5" AC, 2-3/8" solid plug. 1 perforated jt of 2-3/8" N-80 tbg. SN, and 1900' of 2-3/8" tbg. Crossover to 2-7/8" tbg and TIH. 4.
- 5. Set AC @ ± 11.050 and land tbg in hanger.
- PU & RIH w/1-1/4" pump. 78 3/4" rods w/regular couplings, 77 3/4" rods w/oversized couplings. 146 7/8" rods and 141 1" rods. The 3/4" rods w/regular couplings are required through the 2-3/8" tbg section. Hang well on beam maintaining SPM as before. 6.

Doyle #1-10B3 Altamont Field Duchesne Co., UT Current Schematic Pump Unit Description: Lufkin M912-365-168 Rod Design: 115 - 1" Nor 97's 121 - 7/8" Nor 97's 121 - 3/4" Nor 97's 7 - 1" EL Total 364 or 9100' Gas Anchor Description: PBGA 4-1/2"x10' N-80 Pump Description: National 1-1/2" bore 2-7/8" 6.5# N-80 EUE

Perfs 9213-11,031'
3 spf 366 holes 1/93

AC @ 8931" SN @ 9151"

EOT @ 9169'

KB: GL:

> Perfs 10,581-11,115' 111 holes

Perfs 11,115-13,106' 625 holes

7" 26 & 29# CF-95 LT&C @ 10,754 w/ 620 cu ft CIBP @ 11,115'

TOL @ 10,577'

5° 18# Hydril SFJ-P SOO-95 & N-80 liner 13,195' w/ 520 sx class G

TD 13,195'

TATE OF UTAH DIVISION OF OIL, GAS AND MINING

Dividion of the	ाटा 27	5. Lease Designation and Serial Number: Patented
SUNDRY NOTICES AND REP	ORTS ON WELLS	6. If Indian, Allottee or Tribe Name: N/A
Do not use this form for proposals to drill new wells, deepen existing w Use APPLICATION FOR PERMIT TO DRILL OR DEE	7. Unit Agreement Name: N/A	
Type of Well: OIL X GAS OTHER:		8. Well Name and Number: Doyle #1-10B3
2. Name of Operator: ANR Production Company		9. API Well Number: 43-013-30187
3. Address and Telephone Number: P.O. Box 749, Denver, CO 80201–0749	(303) 573 – 4476	10. Field and Pool, or Wildcat: Altamont
4. Location of Well Footages: 2382' FNL & 2157' FWL QQ, Sec., T., R., M.: SE/NW Section 10-T2S-R3W 11. CHECK APPROPRIATE BOXES TO	INDICATE NATURE OF NOTICE.	County: Duchesne State: Utah REPORT, OR OTHER DATA
NOTICE OF INTENT		EQUENT REPORT
Abandonment New Constru Casing Repair Pull or Alter C Change of Plans Recompletion Conversion to Injection Shoot or Acid Fracture Treat Vent or Flare Multiple Completion Water Shut— Other Approximate date work will start DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertine vertical depths for all markers and zones pertinent to this work.) Please see the attached chronological history for wo	Casing Casing Repair Change of Plans Clize Conversion to Injection Fracture Treat Off X Other Lower Seating Ni Date of work completion Report results of Multiple Completic COMPLETION OR RECOMPLETION * Must be accompanied by a cement	9/20/94 ons and Recompletions to different reservoirs on WELL NAND LOG form. verification report.
13. Name & Signature: (This space for State use only)	N.O. Shiflet Title: District Dril	
(1000)	(See Instructions on Reverse Side)	'

(See Instructions on Reverse Side)

(12/92)

ANR PRODUCTION COMPANY CHRONOLOGICAL HISTORY

DOYLE #1-10B3 (LOWER SN)

ALTAMONT FIELD

DUCHESNE COUNTY, UT

WI: 84.375% ANR AFE: 00353 TD: 13,195' PBTD: 11,104' (CIBP)

5" LINER @ 10,577'-13,195'

PERFS: 9,213'-11,104

CWC(M\$): 35.2

9/7/94 MIRU rig.

Move rig on location. CC: \$980

9/8/94 POH w/tbq.

RU rig. Unseat pump, POOH w/rods & pump. CC: \$4,819

9/9/94 RIH w/CO tool on tbg.

ND WH, NU BOP. Rls'd TAC. POOH w/tbg & BHA. RIH w/41/8" mill, Graco CO tool & 18 jts 23/8" tbg. RIH w/128 stds 27/8" tbg to 8732'. CC: \$8.374

9/10-11/94 SD for weekend.

9/12/94 RIH w/tba.

RIH, tagged fill @ 11,094'. CO fill to PBTD @ 11,104'. POOH w/23/8" tbg, CO tool & mill. RIH w/BHA & 18 jts 23/8" to 4518'. CC: \$13,459

9/13/94 Finish RIH w/tbg.

Unable to set TAC @ 11.054'. Tagged btm - still unable to set AC. POOH w/27/8" tbg. TAC was full of rubber off ball sealers & would not rotate. RIH w/new 5" B-2 TAC & BHA to 1735'. CC: \$16,766

9/14/94 RD rig, well on pump.

RIH w/tbg, set TAC @ 11,054' w/SN @ 11,012'. ND BOP. Landed tbg on hanger w/18,000# tension. NU WH. RIH w/1%" pump & rods. Space out & seat pump. PT tbg to 500#. Left well pmpg overnight. CC: \$27,338

9/14/94 Pmpd 4 BO, 59 BW, 1 MCF, 7 SPM, 12 hrs.

9/15/94 Pmpd 41 BO, 107 BW, 8 MCF, 7 SPM. RDMO. CC: \$30,275

9/16/94 Pmpd 29 BO, 103 BW, 12 MCF.

9/17/94 Pmpd 26 BO, 97 BW, 11 MCF.

9/18/94 Pmpd 27 BO, 100 BW, 13 MCF, 7 SPM. Will run dyno & check FL today.

9/19/94 Pmpd 19 BO, 106 BW, 15 MCF, 7 SPM. Ran dyno, FL @ 8600'. Will increase SPM to 8.

9/20/94 Pmpd 28 BO, 126 BW, 27 MCF, 8.5 SPM.

Prior prod: 16 BO, 20 BW, 11 MCF. Final report.

PAGE 2

TATE OF UTAH DIVISION OIL, GAS AND MINING

		5. Lease Designation and Serial Number: See Attached
SUNDRY NOTICES AND REPORTS C	N WELLS	6. If Indian, Alfottee or Tribe Name: See Attached
Do not use this form for proposals to drill new wells, deepen existing wells, or to reente Use APPLICATION FOR PERMIT TO DRILL OR DEEPEN form for su	ſ	7. Unit Agreement Name: See Attached
Type of Well: OIL X GAS OTHER:		8. Well Name and Number: See Attached
2. Name of Operator: Coastal Oil & Gas Corporation		9. API Well Number: See Attached
3. Address and Telephone Number: P.O. Box 749, Denver, CO 80201-0749	(303) 573 – 4455	10. Field and Pool, or Wildcat: See Attached
4. Location of Well		
Footages: See Attached		county: See Attached
QQ, Sec., T., R., M.: See Attached		State: Utah
CHECK APPROPRIATE ROYES TO INDICAT	E NATURE OF NOTICE PER	
11. CHECK APPROPRIATE BOXES TO INDICAT	NATURE OF NOTICE, REPO	ORT, OR OTHER DATA
NOTICE OF INTENT		ENT REPORT
(Submit In Duplicate)	(Submit Origi	inal Form Only)
Abandon New Construction	Abandon *	New Construction
Repair Casing Pull or Alter Casing	Repair Casing	Pull or Alter Casing
Change of Plans Recompletion	Change of Plans	Perforate
Convert to Injection Perforate	Convert to Injection	Vent or Flare
Fracture Treat or Acidize Vent or Flare	Fracture Treat or Acidize	Water Shut-Off
Multiple Completion Water Shut-Off	X Other Change of Operator	
Other		
Approximate date work will start	Date of work completion	
Approximate date work will start	Report results of Multiple Completions and COMPLETION OR RECOMPLETION REPOR	Recompletions to different reservoirs on WELL TAND LOG form.
	Must be accompanied by a cement verification	on report.
 DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and giver vertical depths for all markers and zones pertinent to this work.) 	e pertinent dates. If well is directionally drilled, give s	ubsurface locations and measured and true
Please be advised that effective December 27, 1995, ANR Procassumed operations for the subject wells (see attached). Bond provided by Coastal Oil & Gas Corporation under the followin #U605382-9, and BIA Nationwide Bond #11-40-66A. Coaunder the terms and conditions of the leases for the operations	coverage pursuant to 43 CFR 310 g bonds: State of Utah #102103, stal Oil & Gas Corporation, as or	14 for lease activities is being RI M Nationwide Bond
		GEIVE
Bonnie Carson, Sr. Environmental & Safety Analyst		MAR _ 8 1996
ANR Production Company OF CIL, GAS & MINING		
13.	Sheila Bremer	OIL, GRO & IVIINING
$\delta I_0 \cdot I_1 \rightarrow I_1$	Environmental & Sa	afety Analyst
Name & Signature: Dyula Dumey	Title: Coastal Oil & Gas C	Corporation Date: 03/07/96

(This space for State use only)

			If Indian,		LOCATION			
		Lease Designation	Allottee or			Section, Township		
Well Name & No.	API No.	& Serial Number	Tribe Name	CA No.	Footages	& Range	Field	County
			N//A	NI/A	820' FNL & 660' FEL	NENE, 33-1S-4W	Altamont	Duchesne
Brotherson 1-33A4	43-013-30272	Patented 680	N/A	N/A	1241' FSL & 1364' FWL	SESW, 10-2S-4W	Altamont	Duchesne
Brotherson 2-10B4	43-013-30443	Patented 1615	N/A	N/A			Altamont	Duchesne
Brotherson 2-14B4	43-013-30815	Fee 0450	N/A	N/A	2557' FSL & 1642' FWL	NESW, 14-2S-4W		Duchesne
Brotherson 2-15B4	43-013-31103	Fee [77]	N/A	N/A	996' FWL & 1069' FSL	SWSW, 15-2S-4W	Altamont	<u> </u>
Brotherson 2-22B4	43-013-31086	Fee 1792	N/A	N/A	1616' FWL & 1533' FSL	NESW, 22-2S-4W	Altamont	Duchesne
Brotherson 2-2B5	43-013-31302	Fee 1/342	N/A	N/A	1034' FSL & 2464' FEL	SWSE, 2-2S-5W	Altamont	Duchesne
Christensen 2-29A4	43-013-31303	Fee <i> 23</i> 5	N/A	N/A	1425' FSL & 2131' FEL	NWSE, 29-1S-4W	Altamont	Duchesne
Crook 1-6B4	43-013-30213	Patented 1825	N/A	N/A	2485' FNL & 1203' FEL	SENE, 6-2S-4W	Altamont	Duchesne
Dastrup 2-30A3	43-013-31320	Fee 1/253	N/A	N/A	1250' FSL & 1229' FWL	SWSW, 30-1S-3W	Altamont	Duchesne
Doyle 1-10B3	43-013-30187	Patented 80	N/A	N/A	2382' FNL & 2157' FWL	SENW, 10-2S3W	Bluebell	Duchesne
Duncan 2-9B5	43-013-30719	Fee 2410	N/A	N/A	1701' FWL & 1554' FSL	NESW, 9-2S-5W	Altamont	Duchesne
Ehrich 3-11B5	43-013-31080	Fee 1691	N/A	N/A	1654' FSL & 1754' FWL	NESW, 11-2S-5W	Altamont	Duchesne
Elder 1-13B2	43-013-30366	Patented 1905	N/A	N/A	1490' FNL & 1334' FEL	SWNE, 13-2S-2W	Bluebell	Duchesne
Ellsworth 1-17B4	43-013-30126	Patented 1695	N/A	N/A	763' FNL & 1189' FEL	NENE, 17-2S-4W	Altamont	Duchesne
Ellsworth 1-19B4	43-013-30183	Patented 1760	N/A	N/A	2043' FNL & 1764' FEL	SWNE, 19-2S-4W	Altamont	Duchesne
Ellsworth 1-20B4	43-013-30351	Patented 1900 Fee 1055	N/A	N/A	1744' FNL & 1342' FEL	SWNE, 20-2S-4W	Altamont	Duchesne
Ellsworth 1-8B4	43-013-30112	Fee 1655	N/A	N/A	1755' FNL & 2377' FEL	SWNE, 8-2S-4W	Altamont	Duchesne
Ellsworth 2-17B4	43-013-31089	Fee jle gle		N/A	1355' FWL & 1362' FSL	NESW, 17-2S-4W	Altamont	Duchesne
Ellsworth 2-19B4	43-013-31105	Fee 1761	N/A	N/A	1402' FSL & 1810' FWL	NESW, 19 -2S-4W	Altamont	Duchesne
Ellsworth 2-20B4	43-013-31090	Fee 1902	N/A	N/A	677' FWL & 1611' FSL	NWSW, 20-2S-4W	Altamont	Duchesne
Ellsworth 3-20B4	43-013-31389	Fee 11489		N/A	1500' FNL & 1203' FWL	SWNW, 20-2S-4W	Altamont	Duchesne
Farnsworth 1-12B5	43-013-31024	30/24 Patented 1645		N/A	2479' FNL & 1503' FEL	SWNE, 12-2S-5W	Altamont	Duchesne
Farnsworth 1-13B5	43-013-30092	Patented 1610		N/A	670' FNL & 1520' FEL	NWNE, 13-2S-5W	Altamont	Duchesne
Farnsworth 1-7B4	43-013-30097	Patented 600		N/A	1923' FNL & 1095' FEL	SENE, 7-2S-4W	Altamont	Duchesne
Farnsworth 2-12B5	43-013-31115	Fee (المال)	N/A	N/A	993' FSL & 768' FWL	SWSW, 12-2S-5W	Altamont	Duchesne
Farnsworth 2-7B4	43-013-30470	Patented 1935	N/A	N/A	1292' FSL & 1500' FWL	SESW, 7-2S-4W	Altamont	Duchesne
Fieldstead 2-28A4	43-013-31293	Fee ///7/7	N/A	N/A	2431' FSL & 2212' FWL	NESW, 28-1S-4W	Altamont	Duchesne
Galloway 1-18B1	43-013-30575	Fee 2365	N/A	N/A	1519' FNL & 1565' FEL	SWNE, 18-2S-1W	Bluebell	Duchesne
Hanskutt 2-23B5	43-013-30917	Fee 9600	N/A	N/A	951' FSL & 761' FWL	SWSW, 23-2S-5W	Altamont	Duchesne
Hanson 1-24B3	43-013-30629	Fee 2370	N/A	N/A	1354' FNL & 1540' FWL	NENW, 24-2S-3W	Bluebell	Duchesne
Hanson 2-9B3	43-013-31136	Fee 10,455	N/A	N/A	1461' FWL & 1531' FSL	NESW, 9-2S-3W	Altamont	Duchesne
Hanson Trust 1-32A3	43-013-30141	Patented 1646		N/A	671' FNL & 1710' FEL	NWNE, 32-1S-3W	Altamont	Duchesne
Hanson Trust 1-5B3	43-013-30109	Patented 1635		N/A	1200' FNL & 1140' FWL	NENE, 5-2S-3W	Altamont	Duchesne
Hanson Trust 2-29A3	43-013-31043	Fee 10205	N/A	N/A	1857' FWL & 1394' FSL	NESW, 29-1S-3W	Altamont	Duchesne
Hanson Trust 2-32A3	43-013-31072	Fee 1641	N/A	N/A	1141' FWL & 1602' FSL	NWSW, 32-1S-3W	Altamont	Duchesne
Hanson Trust 2-5B3	43-013-31079	Fee 1636		N/A	1606' FSL & 1482' FWL	NESW, 5-2S-3W	Altamont	Duchesne
Hartman 1-31A3	43-013-30093	Fee 5725	N/A	N/A	1019' FNL & 1024' FEL	NENE, 31-1S-3W	Altamont	Duchesne
Hartman 2-31A3	43-013-31243	Fee 1/02/	N/A	N/A	2437' FSL & 1505' FWL	SWSW, 31-1S-3W	Altamont	Duchesne
Hunt 1-21B4	43-013-30214	Patented 1840		N/A	1701' FNL & 782' FEL	SENE, 21-2S-4W	Altamont	Duchesne
Hunt 2-21B4	43-013-31114	Fee /839		N/A	1512' FWL & 664' FSL	NESW, 21-2S-4W	Altamont	Duchesne
lorg 2-10B3	43-013-31388	Fee 1/482	N/A	N/A	738' FNL & 660' FEL	NENE, 10-2S-3W	Altamont	Duchesne
Lake Fork 3-15B4	43-013-31358	Fee //378	N/A	N/A	1300' FNL & 1450' FWL	NENW, 15-2S-4W	Altamont	Duchesne
Lawrence 1-30B4	43-013-31330	Fee /845		N/A	919' FNL & 1622' FEL	NWNE, 30-2S-4W	Altamont	Duchesne
Lawson 1-28A1	43-013-30358	Fee /845 Fee /90	N/A	N/A	2275' FSL & 1802' FEL	NWSE, 28-1S-1W	Bluebell	Duchesne
Lazy K 2-14B3	43-013-30354	Fee 1/452	N/A	N/A	1670' FSL & 1488' FEL	NWSE, 14-2S-3W	Bluebell	Duchesne
Lindsay 2-33A4	43-013-31334	Fee 10457	N/A	N/A	1499' FWL & 663' FSL	SESW, 33-1S-4W	Altamont	Duchesne
Lotridge Gates 1-3B3	43-013-31141	Patented 1670		N/A	965' FNL & 750' FEL	NENE, 3-2S-3W	Altamont	
Matthews 2-13B2	43-013-30117	Fee //374 Fee //489	N/A	N/A	858' FNL & 1098' FWL	NWNW, 13-2S-2W	Bluebell	Duchesne
Maillews Z-13DZ	43-013-31377	Fee 11489	N/A	N/A	1065' FNL & 1124' FWL	NWNW, 8-2S-3W	Altamont	Duchesne

OPERATOR CHANGE HORKSHEET Attach all documentation received by the division regarding this change. Initial each listed item when completed. Write N/A if item is not applicable. A Change of Operator (well sold)	LE
Hell(s) (attach additional page if needed): Name: **SEE ATTACHED** API: 0/3-30/87 Entity: Sec_Twp_Rng_Lease Type:	
Name: API: Entity: SecTwpRngLease Type:	
1. (Rule R615-8-10) Sundry or other legal documentation has been received from form operator (Attach to this form). (Led 3.8-96) 2. (Rule R615-8-10) Sundry or other legal documentation has been received from new operator (Attach to this form). (Red 3-8-96) 3. The Department of Commerce has been contacted if the new operator above is not currently operating any wells in Utah. Is company registered with the state? (yes/no) I	or ly If
4. (For Indian and Federal Hells ONLY) The BLM has been contacted regarding this chang (attach Telephone Documentation Form to this report). Make note of BLM status i changes should take place prior to completion of steps 5 through 9 below.	r
25. Changes have been entered in the Oil and Gas_Information System (Wang/IBM) for each well listed above. (3-11-96)(4-3-96/Indian)(4-15-96/Fee C.A.'s) (8-20-96/Indian C.A.'s)	1
201. Well file labels have been updated for each well listed above.	
28. Changes have been included on the monthly "Operator, Address, and Account Changes" memo for distribution to State Lands and the Tax Commission. (3-11-96) 29. A folder has been set up for the Operator Change file, and a copy of this page has been placed there for reference during routing and processing of the opinion.	
placed there for reference during routing and processing of the original documents.	

Division of Oil, Gas and Mining

OPERATOR CH	NANGE WORKSHEET (CONTINUED) Initial each item when completed. Write N/A if item is not applicable.
ENTITY RE	ZVIEH
Le 1. (R en Fo	cule R615-8-7) Entity assignments have been reviewed for all wells listed above. Were tity changes made? (yes/ho) (If entity assignments were changed, attach <u>copies</u> of the copies
NA 2. Sta	ate Lands and the Tax Commission have been notified through normal procedures of tity changes.
BOND VERIE	FICATION (Fee wells only) Surely No. Ulo5382-1 (480,000) United Pacific Ins. Co.
Lec 1. (Ru pro	ule R615-3-1) The new operator of any fee lease well listed above has furnished a oper bond.
2. A c	copy of this form has been placed in the super Compl. of routing.
LC 3. The Tod dat	former operator has requested a release of liability from their bond (yes no) lay's datemarch , 19 96. If yes, division response was made by letter led 19 (Same Bond 45 (b4sfel)
LEASE INTE	REST OWNER NOTIFICATION RESPONSIBILITY
NA 1. (Ru not pers	le R615-2-10) The former operator/lessee of any fee lease well listed above has been ified by letter dated
2. Copi	ies of documents have been sent to State Lands for changes involving State leases.
CTI MTNO	
6 1. A11	attachments to this form have been microfilmed. Date: 1997 .
FILING	
1. <u>Copi</u>	es of all attachments to this form have been filed in each well file.
2. The Chan	original of this form and the <u>original</u> attachments have been filed in the Operator ge file.
OMMENTS	
960311 This	change involves Fee lease from C.A. wells and state lease wells.
9/0412 81	in 151 April C.A.'s 4-11-9/e.
	BIA aprv. CA'S 8-16-96.
9/20329	RIA (1 1: 1
71/34-35	BIA apri. Indian Lesse wells 3-26-96. * 96/107 Limicy 2-582/43-013-30784 under review at this time; no dy. yet!
	101101 coming 2-562/43-013-30 784 under review at this time; no chy, yet!

TATE OF UTAH DIVISION OIL, GAS AND MINING

		5. Lease Designation and Serial Number: See Attached
SUNDRY NOTICES AND REPORTS O	6. If Indian, Allottee or Tribe Name: See Attached	
Do not use this form for proposals to drill new wells, deepen existing wells, or to reente Use APPLICATION FOR PERMIT TO DRILL OR DEEPEN form for su	7. Unit Agreement Name: See Attached	
1. Type of Well: OIL X GAS OTHER:		8. Well Name and Number: See Attached
2. Name of Operator: Coastal Oil & Gas Corporation		9. API Well Number: See Attached
3. Address and Telephone Number: P.O. Box 749, Denver, CO 80201-0749	(303) 573 – 4455	10. Field and Pool, or Wildcat: See Attached
Location of Well		
Footages: See Attached		County: See Attached
QQ, Sec., T., R., M.: See Attached		State: Utah
11. CHECK APPROPRIATE BOXES TO INDICAT	E NATURE OF NOTICE, RE	EPORT, OR OTHER DATA
NOTICE OF INTENT		QUENT REPORT
(Submit In Duplicate)		Original Form Only)
Abandon New Construction	Abandon *	New Construction
Repair Casing Pull or Alter Casing	Repair Casing	Pull or Alter Casing
Change of Plans Recompletion	Change of Plans	Perforate
Convert to Injection Perforate Fracture Treat or Acidize Vent or Flare	Convert to Injection	Vent or Flare
	Fracture Treat or Acidize	Water Shut-Off
Multiple Completion Water Shut-Off Other	X Other Change of Operator	
	Date of work completion	
Approximate date work will start	Report results of Multiple Completions COMPLETION OR RECOMPLETION REF	and Recompletions to different reservoirs on WELL
	* Must be accompanied by a cement verifi	ication report.
 DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give vertical depths for all markers and zones pertinent to this work.) 	e pertinent dates. If well is directionally drilled, gi	ive subsurface locations and measured and true
Please be advised that effective December 27, 1995, ANR Prod assumed operations for the subject wells (see attached). Bond provided by Coastal Oil & Gas Corporation under the followin #U605382-9, and BIA Nationwide Bond #11-40-66A. Coasunder the terms and conditions of the leases for the operations	g bonds: State of Utah #10210	3104 for lease activities is being
Bonnie Carson, Sr. Environmental & Safety Analyst ANR Production Company		MAR _ 8 1996 PFOIL, GAS & MINING
8/- 1/ ==	Sheila Bremer Environmental &	Safety Analyst
Name & Signature: Dulla Sommer	Title: Coastal Oil & Gas	Safety Analyst S Corporation Date: 03/07/96
in concess for Direct		

is space for State use only)

STATE OF UTAH

	DEPARTMENT OF NATURAL RESOU DIVISION OF OIL, GAS AND MI		5. LEASE DESIGNATION AND SERIAL NUMBER:
SUNDR	6. IF INDIAN, ALLOTTEE OR TRIBE NAME:		
Do not use this form for proposals to drift drift horizontal	7. UNIT or CA AGREEMENT NAME:		
1. TYPE OF WELL OIL WELL			8. WELL NAME and NUMBER: Exhibit "A"
3. ADDRESS OF OPERATOR:	o Production Oil & Gas (PHONE NUMBER:	9. API NUMBER: 10. FIELD AND POOL, OR WILDCAT:
4. LOCATION OF WELL FOOTAGES AT SURFACE:			COUNTY:
QTR/QTR, SECTION, TOWNSHIP, RAI	NGE, MERIDIAN:		STATE: UTAH
11. CHECK APP	ROPRIATE BOXES TO INDICAT	TE NATURE OF NOTICE, REPO	ORT, OR OTHER DATA
TYPE OF SUBMISSION		TYPE OF ACTION	DEDECTORATE CURRENT FORMATION
NOTICE OF INTENT (Submit in Duplicate)	ACIDIZE ALTER CASING	DEEPEN FRACTURE TREAT	REPERFORATE CURRENT FORMATION SIDETRACK TO REPAIR WELL
Approximate date work will start:	CASING REPAIR	NEW CONSTRUCTION	TEMPORARILY ABANDON
	CHANGE TO PREVIOUS PLANS	OPERATOR CHANGE	TUBING REPAIR
CURCEOUSN'T REPORT	CHANGE TUBING	PLUG AND ABANDON	VENT OR FLARE
SUBSEQUENT REPORT (Submit Original Form Only)	CHANGE WELL NAME CHANGE WELL STATUS	PLUG BACK PRODUCTION (START/RESUME)	WATER DISPOSAL WATER SHUT-OFF
Date of work completion:	COMMINGLE PRODUCING FORMATIONS	RECLAMATION OF WELL.SITE	X OTHER: Name Change
	CONVERT WELL TYPE	RECOMPLETE - DIFFERENT FORMATION	
As a result of subsidary of El	the merger between The C	Coastal Corporation and	l a wholly owned Oil & Gas Corporation
has been change	ed to El Paso Production See E	whibit "A"	ective march 9, 2001.
Bond # 400JU070			
NAME (PLEASE PRINT) John	al Oil & Gas Corporatio T <i>(</i> Elzner	n Vice Presio	lent
SIGNATURE	' -	DATE 06-15-01	
E1 Pa	so Production Oil & Gas T Blzner	Company TITLE Vice President	dent
SIGNATURE		DATE 06-15-01	
(This space for State use only)			RECEIVED

JUN 19 2001

Office of the Secretary of State

I, HARRIET SMITH WINDSOR, SECRETARY OF STATE OF THE STATE OF DELAWARE, DO HEREBY CERTIFY THE ATTACHED IS A TRUE AND CORRECT COPY OF THE CERTIFICATE OF AMENDMENT OF "COASTAL OIL & GAS CORPORATION", CHANGING ITS NAME FROM "COASTAL OIL & GAS CORPORATION" TO "EL PASO PRODUCTION OIL & GAS COMPANY", FILED IN THIS OFFICE ON THE NINTH DAY OF MARCH, A.D. 2001, AT 11 O'CLOCK A.M.



11 IN 1 - 7001

DIVISION OF OIL, GAS AND MINING



Darriet Smith Windson Harriet Smith Windson, Secretary of State

AUTHENTICATION: 1061007

DATE: 04-03-01

0610204 8100

010162788

CERTIFICATE OF AMENDMENT

OF

CERTIFICATE OF INCORPORATION

COASTAL OIL & GAS CORPORATION (the "Company"), a corporation organized and existing under and by virtue of the General Corporation Law of the State of Delaware, DOES HEREBY CERTIFY:

FIRST: That the Board of Directors of the Company, by the unanimous written consent of its members, filed with the minutes of the Board, adopted a resolution proposing and declaring advisable the following amendment to the Certificate of Incorporation of the Company:

RESOLVED that it is deemed advisable that the Certificate of Incorporation of this Company be amended, and that said Certificate of Incorporation be so amended, by changing the Article thereof numbered "FIRST." so that, as amended, said Article shall be and read as follows:

"FIRST. The name of the corporation is El Paso Production Oil & Gas Company."

SECOND: That in lieu of a meeting and vote of stockholders, the stockholders entitled to vote have given unanimous written consent to said amendment in accordance with the provisions of Section 228 of the General Corporation Law of the State of Delaware.

THIRD: That the aforesaid amendment was duly adopted in accordance with the applicable provisions of Sections 242 and 228 of the General Corporation Law of the State of Delaware.

IN WITNESS WHEREOF, said COASTAL OIL & GAS CORPORATION has caused this certificate to be signed on its behalf by a Vice President and attested by an Assistant Secretary, this 9th day of March 2001.

COASTAL OIL & GAS CORPORATION

David L. Siddall Vice President

Attest:

et E. Roark, Assistant Secretary

STATE OF DELAWARE
SECRETARY OF STATE
DIVISION OF CORPORATIONS
FILED 11:00 AM 03/09/2001
010118394 - 0610204

TUN 19 2001

OPERATOR CHANGE WORKSHEET

ROUTING

1. GLH	4-KAS
2. CDW >	5-LP 1
3. JLT	6-FILE

Enter date after each listed item is completed

Change of Operator (Well Sold)

Designation of Agent

Operator Name Change (Only)

X Merger

The operator of the well(s) listed belo	w has change	d, effective:	3-09-200)1	_		
FROM: (Old Operator):			TO: (Ne	w Operator):			
COASTAL OIL & GAS CORPORATION	******		EL PASO	PRODUCTIO	N OIL & G	AS COMI	PANY
Address: 9 GREENWAY PLAZA STE 2721			Address: 9 GREENWAY PLAZA STE 2721 RM				RM 2975
HOUSTON, TX 77046-0995			HOUSTO	N, TX 77046-0)995		
Phone: 1-(713)-418-4635			Phone: 1-(832)-676-4721				
Account N0230			Account	N1845		·	
****	CA No.		Unit:	· · · · · · · · · · · · · · · · · · ·			
WELL(S)							
	F	API	ENTITY	SEC TWN	LEASE	WELL	WELL
NAME		NO	NO	RNG	TYPE	TYPE	STATUS
MILES 2-3B3	4	13-013-31261	11102	03-02S-03W	FEE	OW	P
RUST 1-4B3	4	13-013-30063	1575	04-02S-03W	FEE	OW	P
DIJOR 3 AD 3			 		1		†

		ALI	TOTAL T	DEC I WIT	LEASE	WELL	TARREST I
NAME		NO	NO	RNG	TYPE	TYPE	STATUS
MILES 2-3B3		43-013-31261	11102	03-02S-03W	FEE	OW	P
RUST 1-4B3		43-013-30063	1575	04-02S-03W	FEE	OW	P
RUST 3-4B3		43-013-31070	1576	04-02S-03W	FEE	OW	P
HANSON TRUST 1-5B3		43-013-30109	1635	05-02S-03W	FEE	OW	P
HANSON TRUST 2-5B3		43-013-31079	1636	05-02S-03W	FEE	OW	P
CHRISTENSEN 2-8B3		43-013-30780	9355	08-02S-03W	FEE	OW	P
MEEKS 3-8B3		43-013-31377	11489	08-02S-03W	FEE	OW	P
HANSON 2-9B3		43-013-31136	10455	09-02S-03W	FEE	OW	P
DOYLE 1-10B3		43-013-30187	1810	10-02S-03W	FEE	OW	P
IORG 2-10B3		43-013-31388	11482	10-02S-03W	FEE	OW	P
RUDY 1-11B3		43-013-30204	1820	11-02S-03W	FEE	OW	P
LAZY K 2-11B3		43-013-31352	11362	11-02S-03W	FEE	OW	P
JENKINS 2-12B3	(CA 96-79)	43-013-31121	10459	12-02S-03W	FEE	OW	P
FLYING DIAMOND ROPER 1-14B3		43-013-30217	1850	14-02S-03W	FEE	OW	P
LAZY K 2-14B3		43-013-31354	11452	14-02S-03W	FEE	OW	P
BODRERO 1-15B3		43-013-30565	2360	15-02S-03W	FEE	OW	S
LINMAR HANSON 1-16B3		43-013-30617	9124	16-02S-03W	FEE	OW	P
EVANS UTE 2-17B3	(CA 96-104)	43-013-31056	5336	17-02S-03W	FEE	OW	P
MYRIN 2-18B3	(CA 70814)	43-013-31297	11475	18-02S-03W	FEE	OW	P
EVANS 1-19B3	(CA 96-78)	43-013-30265	1776	19-02S-03W	FEE	OW	P

OPERATOR CHANGES DOCUMENTATION

1.	(R649-8-10) Sundry or legal documentation was received from the FORMER operator on:	06/19/2001	
2.	(R649-8-10) Sundry or legal documentation was received from the NEW operator on:	06/19/2001	
_	The new company has been checked through the Department of Commerce, Division of Corpo	rations Database on:	06/21/2001

4. Is the new operator registered in the State of Utah:

YES

Business Number: 608186-0143

5.	If NO , the operator was contacted contacted on: N/A
6.	Federal and Indian Lease Wells: The BLM and or the BIA has approved the (merger, name change, or operator change for all wells listed on Federal or Indian leases on: N/A
7.	Federal and Indian Units: The BLM or BIA has approved the successor of unit operator for wells listed on: N/A
8.	
9.	Underground Injection Control ("UIC") The Division has approved UIC Form 5, Transfer of Authority to Inject, for the enhanced/secondary recovery unit/project for the water disposal well(s) listed on: N/A
D	ATA ENTRY:
1.	Changes entered in the Oil and Gas Database on: 07/03/2001
2.	Changes have been entered on the Monthly Operator Change Spread Sheet on: 07/03/2001
3.	Bond information entered in RBDMS on: $06/20/2001$
4.	Fee wells attached to bond in RBDMS on: 07/03/2001
S	TATE BOND VERIFICATION:
1.	State well(s) covered by Bond No.: N/A
F	EE WELLS - BOND VERIFICATION/LEASE INTEREST OWNER NOTIFICATION:
	(R649-3-1) The NEW operator of any fee well(s) listed has furnished a bond: 400JU0708
2.	The FORMER operator has requested a release of liability from their bond on: The Division sent response by letter on: OMPLETION OF OPERATOR CHANGE N/A
	(R649-2-10) The FORMER operator of the Fee wells has been contacted and informed by a letter from the Division of their responsibility to notify all interest owners of this change on: COMPLETION OF OPERATOR CHANGE
	LMING: All attachments to this form have been MICROFILMED on: \$ 15.01
FI	LING:
	ORIGINALS/COPIES of all attachments pertaining to each individual well have been filled in each well file on:
CC	MMENTS: Master list of all wells involved in operator change from Coastal Oil & Gas Corporation to El Paso
Pr	oduction Oil and Gas Company shall be retained in the "Operator Change File".

Division of Oil, Gas and Mining OPERATOR CHANGE WORKSHEET

ROUTING 1. DJJ 2. CDW

Change of Operator (Well Sold)

X Operator Name Change

The operator of the well(s) listed below has changed, effective:	7/1/2006							
FROM: (Old Operator):	TO: (New Operator):							
N1845-El Paso Production O&G Company	N3065-El Paso E&P Company, LP							
1001 Louisiana Street	1001 Louisiana Street							
Houston, TX 77002	Houston, TX 77002							
Phone: 1 (713) 420-2300	Phone: 1 (713) 420-2131							
CA No.	Unit:							
OPERATOR CHANGES DOCUMENTATION								
Enter date after each listed item is completed	7/5/2007							
1. (R649-8-10) Sundry or legal documentation was received from the								
2. (R649-8-10) Sundry or legal documentation was received from the								
3. The new company was checked on the Department of Commerce	ce, Division of Corporations Database on: 3/30/2006							
4. Is the new operator registered in the State of Utah: YES	Business Number: 2114377-0181							
5. If NO , the operator was contacted contacted on:	7							
6a. (R649-9-2)Waste Management Plan has been received on:	requested 7/18/06							
6b. Inspections of LA PA state/fee well sites complete on:	ok							
6c. Reports current for Production/Disposition & Sundries on:								
7. Federal and Indian Lease Wells: The BLM and or the	BIA has approved the merger, name change,							
or operator change for all wells listed on Federal or Indian leases								
8. Federal and Indian Units:								
The BLM or BIA has approved the successor of unit operator f	for wells listed on:not yet							
9. Federal and Indian Communization Agreements (
The BLM or BIA has approved the operator for all wells listed within a CA on:								
10. Underground Injection Control ("UIC") The Division has approved UIC Form 5, Transfer of Authority to								
Inject, for the enhanced/secondary recovery unit/project for the	water disposal well(s) listed on: 7/14/2006							
DATA ENTRY:	7/10/2007							
1. Changes entered in the Oil and Gas Database on:	7/19/2006 Spread Sheet on: 7/19/2006							
2. Changes have been entered on the Monthly Operator Change S								
3. Bond information entered in RBDMS on:	7/19/2006							
4. Fee/State wells attached to bond in RBDMS on:	<u>7/19/2006</u> <u>7/19/2006</u>							
5. Injection Projects to new operator in RBDMS on:	7/5/2006							
6. Receipt of Acceptance of Drilling Procedures for APD/New on:	173/2000							
BOND VERIFICATION:								
1. Federal well(s) covered by Bond Number:	103601420							
2. Indian well(s) covered by Bond Number:	103601473							
3. (R649-3-1) The NEW operator of any fee well(s) listed covered	by Bond Number 400JU0708							
a. The FORMER operator has requested a release of liability from their bond on:a applicable wells moved								
The Division sent response by letter on:	n/a							
LEASE INTEREST OWNER NOTIFICATION:								
4. (R649-2-10) The FORMER operator of the fee wells has been co	ontacted and informed by a letter from the Division							
of their responsibility to notify all interest owners of this change	on: <u>7/20/2006</u>							
COMMENTS:								

STATE OF UTAH DEPARTMENT OF NATURAL RESOURCES

	DEPAR IMENT OF NATURAL RESCU	NOLO			
	5, LEASE DESIGNATION AND SERIAL NUMBER: MULTIPLE LEASES				
SUNDRY	6, IF INDIAN, ALLOTTEE OR TRIBE NAME:				
Do not use this form for proposals to drill a	new wells, significantly deepen existing wells below curleterals. Use APPLICATION FOR PERMIT TO DRILL!	rrent bottom-hole dept form for such propose	h, reenter plugged wells, or to	7. UNIT or	CA AGREEMENT NAME:
TYPE OF WELL OIL WELL					IAME and NUMBER:
2. NAME OF OPERATOR:	= = = = = = = = = = = = = = = = = = = =	11015		9. API NUI	
	OIL AND GAS COMPANY	N1845	GHOAT AN INDER:	10 EIELD	AND POOL, OR WILDCAT:
3, ADDRESS OF OPERATOR: 1339 EL SEGUNDO AVE NE	ALBUQUERQUE NM	87113	PHONE NUMBER: (505) 344-9380	1000	ATTACHED
4, LOCATION OF WELL FOOTAGES AT SURFACE: SEE	ATTACHED	7		COUNTY:	UINTAH & DUCHESNE
QTR/QTR, SECTION, TOWNSHIP, RAP	NGE, MERIDIAN:			STATE:	UTAH
11. CHECK APP	ROPRIATE BOXES TO INDICAT	TE NATURE	OF NOTICE, REPO	RT, OR	OTHER DATA
TYPE OF SUBMISSION			YPE OF ACTION	eser .	
NOTICE OF INTENT	ACIDIZE	DEEPEN		R	EPERFORATE CURRENT FORMATION
(Submit in Duplicate)	ALTER CASING	FRACTURE	TREAT	=	DETRACK TO REPAIR WELL
Approximate date work will start:	CASING REPAIR	☐ NEW CONS		=	EMPORARILY ABANDON
	CHANGE TO PREVIOUS PLANS	OPERATOR			UBING REPAIR
SUBSEQUENT REPORT	CHANGE TUBING	PLUG AND			ENT OR FLARE (ATER DISPOSAL
(Submit Original Form Only)	CHANGE WELL NAME CHANGE WELL STATUS		ON (START/RESUME)		ATER SHUT-OFF
Date of work completion:	COMMINGLE PRODUCING FORMATIONS		ION OF WELL SITE		THER: CHANGE OF
	CONVERT WELL TYPE	<u> </u>	TE - DIFFERENT FORMATION		OPERATOR
12. DESCRIBE PROPOSED OR C	COMPLETED OPERATIONS. Clearly show all	pertinent details inc	cluding dates, depths, volume	es, etc.	
TRANSFERRED ITS OP	HAT EL PASO PRODUCTION O ERATORSHIP TO EL PASO E&F SO E&P COMPANY, L.P. IS CON ATIONS.	COMPANY,	L.P. (NEW OPERA	TOR) EI	FFECTIVE JUNE 30, July
FOR THE OPERATIONS OF UTAH STATEWIDE	IY, L.P. IS RESPONSIBLE UNDE CONDUCTED UPON LEASED I BLANKET BOND NO. 400JU0705 JREAU OF INDIAN AFFAIRS NA	LANDS. BON 5, BUREAU C	ID COVERAGE IS F F LAND MANAGEM	PROVIDI	ED BY THE STATE
1001 Louisiana Houston, TX 77002	any, L. P. N3065				
William M. Griffi	n, Sr. Vice President				
NAME (PLEASE PRINT) CHERYL	CAMERON	TITL	AUTHORIZED R	EGULA	TORY AGENT
SIGNATURE Sharper	James	DAT	6/20/2006		
This space for State use only) APPROV	ED 71/9106				RECEIVED

APPROVED 7/19/06
Carline Russell

Division of Oil, Gas and Mining
Earlene Russell, Engineering Technician (See Instructions on Reverse Side)

RECEIVED
JUL 0 5 2006

DIV. OF OIL, GAS & MINING

Division of Oil, Gas and Mining OPERATOR CHANGE WORKSHEET (for state use only)

ROUTING	
CDW	

X - Change of Operator (Well Sold)				Operator Na	ame Chang	ge/Merger		
The operator of the well(s) listed below has chan	ged, e	effective	:			6/1/2012		
FROM: (Old Operator):				TO: (New O	perator):			
N3065- El Paso E&P Company, L.P.				N3850- EP En		ompany, L.P.		
1001 Louisiana Street				1001 Louisiana		,		
Houston, TX. 77002				Houston, TX. 7				
				, ,				
Phone: 1 (713) 997-5038				Phone: 1 (713)	997-5038			
CA No.				Unit:		N/A		<u>-</u>
WELL NAME	SEC	TWN	RNG	API NO	ENTITY NO	LEASE TYPE	WELL TYPE	WELL STATUS
See Attached List				<u> </u>				
OPERATOR CHANGES DOCUMENT Enter date after each listed item is completed 1. (R649-8-10) Sundry or legal documentation was 2. (R649-8-10) Sundry or legal documentation was 3. The new company was checked on the Depart 4a. Is the new operator registered in the State of Usa. (R649-9-2) Waste Management Plan has been re 5b. Inspections of LA PA state/fee well sites comp 5c. Reports current for Production/Disposition & State Plan has been re 5c. Reports current for Production/Disposition & State Plan has been re 5c. Reports current for Production/Disposition & State Plan has been re 5c. Reports current for Production/Disposition & State Plan has been reports current for Production/Disposition & State Plan has been reports current for Production/Disposition & State Plan has been reports current for Production/Disposition & State Plan has been reports current for Production/Disposition & State Plan has been reports current for Production/Disposition & State Plan has been reports current for Production/Disposition & State Plan has been reports current for Production/Disposition & State Plan has been reports current for Production/Disposition & State Plan has been reports current for Production/Disposition & State Plan has been reports current for Production/Disposition & State Plan has been reports current for Production/Disposition & State Plan has been reports current for Production/Disposition & State Plan has been reports current for Production/Disposition & State Plan has been reports current for Production/Disposition & State Plan has been reports current for Production Plan has been reports current for	as receas recement Jtah: ecceive	eived from eived from of Com ed on:	m the	NEW operator	on: orporations	6/25/2012 6/25/2012 Database on: 2114377-0181	· ·	6/27/2012
6. Federal and Indian Lease Wells: The BI			BIA I		- e merger, na	me change.		
or operator change for all wells listed on Feder					BLM	N/A	BIA	Not Received
7. Federal and Indian Units:	u 1 01 .				22311	-		
The BLM or BIA has approved the successor	r of m	nit oners	tor fo	r wells listed on		N/A		
					•		-	
-		-		•		N/A		
The BLM or BIA has approved the operator					own 5 Teor		- -	
9. Underground Injection Control ("UIC"				_				C1
Inject, for the enhanced/secondary recovery un	nit/pro	oject for	the wa	ater disposal we	ii(s) listed o	n: Se	cond Oper	Cng
DATA ENTRY:								
1. Changes entered in the Oil and Gas Database			_	6/29/2012	_			
2. Changes have been entered on the Monthly O	perat	or Chan	ige Sp			6/29/2012	-	
3. Bond information entered in RBDMS on:				6/29/2012	-			
4. Fee/State wells attached to bond in RBDMS or				6/29/2012	-			
5. Injection Projects to new operator in RBDMS				6/29/2012	-			
6. Receipt of Acceptance of Drilling Procedures	tor Al	PD/New	on:		N/A	-		
BOND VERIFICATION:								
1. Federal well(s) covered by Bond Number:				103601420	_			
2. Indian well(s) covered by Bond Number:				103601473				
3a. (R649-3-1) The NEW operator of any state/fe	ee we	ll(s) liste	d cov	ered by Bond N	umber	400JU0705	_	
3b. The FORMER operator has requested a release	se of l	iability f	from t	heir bond on:	N/A			
LEASE INTEREST OWNER NOTIFIC 4. (R649-2-10) The NEW operator of the fee well	s has	been con						
of their responsibility to notify all interest owner	ers of	this char	nge on	ı:	6/29/2012			
COMMENTS:		10.5:						
Disposal and Injections wells will be moved wh	ien U	11C 5 IS I	receil	/ea .				

STATE OF UTAH PARTMENT OF NATURAL RESOURCES

	DIVISION OF OIL				5. LEASE DESIGNATION AND SERIAL	NUMBER:
CUNDDY	/ NOTICES AN	ID BEDODI	TO ON WEL	1.6	Multiple Leases 6. IF INDIAN, ALLOTTEE OR TRIBE NA	ME:
SUNDKI	Y NOTICES AN	ND REPUR	12 ON WEL	LS	7 LINUT CA ACREEMENT NAME.	
Do not use this form for proposals to drill r drill horizontal k	new wells, significantly deepe aterals. Use APPLICATION	en existing wells below of FOR PERMIT TO DRILL	current bottom-hole dept L form for such proposa	th, reenter plugged wells, or to is.	7. UNIT or CA AGREEMENT NAME:	
1. TYPE OF WELL OIL WELL	☑ GAS WELI	OTHER			WELL NAME and NUMBER: See Attached	
2. NAME OF OPERATOR:			· · · ·		9. API NUMBER:	<u> </u>
El Paso E&P Company, L	P.	A	Attn: Maria Go	···-		
3. ADDRESS OF OPERATOR: 1001 Louisiana	y Houston	STATE TX Z	_{1P} 77002	PHONE NUMBER: (713) 997-5038	10. FIELD AND POOL, OR WILDCAT: See Attached	
4. LOCATION OF WELL		0.771 <u>g</u>				
FOOTAGES AT SURFACE: See A	Attached				COUNTY:	
QTR/QTR, SECTION, TOWNSHIP, RAN	NGE, MERIDIAN:				STATE: UTAH	
11. CHECK APP	ROPRIATE BOXI	ES TO INDICA	TE NATURE	OF NOTICE, REPO	ORT, OR OTHER DATA	
TYPE OF SUBMISSION			T	YPE OF ACTION		
NOTICE OF INTENT	ACIDIZE		DEEPEN		REPERFORATE CURRENT FO	PRMATION
(Submit in Duplicate)	ALTER CASING		FRACTURE	TREAT	SIDETRACK TO REPAIR WEL	L
Approximate date work will start:	CASING REPAIR		MEW CONS		TEMPORARILY ABANDON	
	CHANGE TO PRE	VIOUS PLANS	☐ OPERATOR		TUBING REPAIR	
SUBSEQUENT REPORT	CHANGE TUBING CHANGE WELL N	A B4E	PLUG AND			
(Submit Original Form Only)	CHANGE WELL ST		_	ON (START/RESUME)	WATER SHUT-OFF	
Date of work completion:		DUCING FORMATIONS	=	ION OF WELL SITE	OTHER: Change of	
	CONVERT WELL		=	TE - DIFFERENT FORMATION	Nomo/Onoro	tor
12. DESCRIBE PROPOSED OR CO	OMPLETED OPERATIO	NS. Clearly show al	l pertinent details inc	cluding dates, depths, volum	mes, etc.	
					es to EP Energy E&P Comp	anv. L.P.
					ed the new operator of the	
ED E	D :	المطافعة المسادمة		ditions of the lease	(a) fan tha an antiona aond.	ام مغم
					(s) for the operations condund No. 400JU0705, Bureau	
Management Nationwide						
4 .	_			1		
March 10	2			Luci	2/10	
Frank W. Faller				Frank W. Falleri		
Vice President				Sr. Vice President		
El Paso E&P Company, L	P.			EP Energy E&P C	company, L.P.	
						
NAME (PLEASE PRINT) Maria S. (Gomez		TITU	Frincipal Regula	atory Analyst	
SIGNATURE MAYOR	H. Borrer	S	DAYI	6/22/2012		
This space for State use only)				RE	CEIVED	
APPROVED _	, /29/201	2			. 2 5 2012	
7	حر غنب عدلا			JUN	2 5 2012	

Division of Oil, Gas and Mining

Earlene Russell, Engineering Technician

Rachel Medim

(See Instructions on Reverse Side)

DIV. OF OIL, GAS & MINING

							Well	Well	
Well Name	Sec	TWP	RNG	API Number	Entity	Lease Type	Type	Status	Conf
DWR 3-17C6	17	0308	060W	4301350070		14204621118	OW	APD	С
LAKEWOOD ESTATES 3-33C6	33	0308	060W	4301350127		1420H621328	OW	APD	С
YOUNG 3-15A3	15	I		4301350122		FEE	OW	APD	С
WHITING 4-1A2	01			4301350424		Fee	OW	APD	С
EL PASO 4-34A4	34			4301350720		Fee	ow	APD	C
YOUNG 2-2B1	02			4304751180		FEE	ow	APD	C
LAKE FORK RANCH 3-10B4	10			4301350712	19221		OW	DRL	C
LAKE FORK RANCH 4-26B4	26			4301350712			OW	DRL	C
							OW	DRL	C
LAKE FORK RANCH 4-24B4	24	1		4301350717					
Cook 4-14B3	14			4301351162			OW	DRL	C
Peterson 4-22C6	22			4301351163			OW	DRL	С
Lake Fork Ranch 4-14B4	14			4301351240			OW	DRL	С
Melesco 4-20C6	20			4301351241			OW	DRL	С
Peck 3-13B5	13			4301351364			OW	DRL	С
Jensen 2-9C4	09			4301351375			OW	DRL	С
El Paso 3-5C4	05	030S	040W	4301351376	18563	Fee	OW	DRL	С
ULT 6-31	31	030S	020E	4304740033		FEE	OW	LA	
OBERHANSLY 2-2A1	02	0108	010W	4304740164		FEE	OW	LA	
DWR 3-15C6	15			4301351433		14-20-H62-4724		NEW	С
Lake Fork Ranch 5-23B4	23			4301350739		Fee	ow	NEW	
Duchesne Land 4-10C5	10			4301351262		Fee	OW	NEW	С
Cabinland 4-9B3	09			4301351374		Fee	OW	NEW	C
			<u> </u>	4301351374		Fee	OW	NEW	C
Layton 4-2B3	02								C
Golinski 4-24B5	24			4301351404		Fee	OW	NEW	
Alba 1-21C4	21			4301351460		Fee	OW	NEW	С
Allison 4-19C5	19			4301351466		Fee	OW	NEW	С
Seeley 4-3B3	03			4301351486		Fee	OW	NEW	С
Allen 4-25B5	25			4301351487		Fee	OW	NEW	С
Hewett 2-6C4	06	0308	040W	4301351489		Fee	OW	NEW	С
Young 2-7C4	07	0308	040W	4301351500		Fee	OW	NEW	С
Brighton 3-31A1E	31	0108	010E	4304752471		Fee	OW	NEW	С
Hamaker 3-25A1	25			4304752491		Fee	OW	NEW	С
Bolton 3-29A1E	29			4304752871		Fee	OW	NEW	С
HORROCKS 5-20A1	20			4301334280	17378		OW	OPS	C
DWR 3-19C6	19					14-20-462-1120		P	
						14-20-462-1131		P	
DWR 3-22C6						14-20-462-1323		P	
DWR 3-28C6								P	+
UTE 1-7A2						14-20-462-811	OW		
UTE 2-17C6	17	I				14-20-H62-1118		P	
WLR TRIBAL 2-19C6	19	L		1		14-20-H62-1120		Р	
CEDAR RIM 10-A-15C6	15					14-20-H62-1128		Р	
CEDAR RIM 12A	28	0308	060W	4301331173	10672	14-20-H62-1323	OW	Р	
UTE-FEE 2-33C6	33	030S	060W	4301331123	10365	14-20-H62-1328	OW	Р	
TAYLOR 3-34C6	34	0308	060W	4301350200	17572	1420H621329	OW	P	
BAKER UTE 2-34C6	34					14-20-H62-1329	OW	Р	
UTE 3-35Z2 K						14-20-H62-1614		Р	1
UTE 1-32Z2	32					14-20-H62-1702		Р	
UTE TRIBAL 1-33Z2	33			4301330334		14-20-H62-1703		P	+
						14-20-H62-1703		P	
UTE 2-33Z2								P	
UTE TRIBAL 2-34Z2	34	4		<u> </u>		14-20-H62-1704			+
LAKE FORK RANCH 3-13B4	13					14-20-H62-1743		P	
UTE 1-28B4	28			4301330242		14-20-H62-1745		P	<u> </u>
UTE 1-34A4	34	·		4301330076		14-20-H62-1774		Р	
	26	0108	04010	4301330069	1580	14-20-H62-1793	OW	Р	
UTE 1-36A4	36	0103	OTOVV	730 1330003	1000	11 LO 1102 1700	<u> </u>		
UTE 1-36A4 UTE 1-1B4	01			4301330129		14-20-H62-1798		P	

LITE 4 OFAO	25	0400	02014	4204220270	1000	44 00 HG2 4902	OVA	Р	
UTE 1-25A3 UTE 2-25A3	25 25			4301330370		14-20-H62-1802 14-20-H62-1802	<u> </u>	P	
UTE 1-26A3	26	 		4301331343		14-20-H62-1803	}	P	
UTE 2-26A3	26					14-20-H62-1803		P	
UTE TRIBAL 4-35A3		1	1			1420H621804	OW	P	С
	35			L	i	14-20-H62-1804		P	<u></u>
UTE 2-35A3	35								
UTE 3-35A3	35					14-20-H62-1804		Р	ļ
UTE 1-6B2	06			4301330349		14-20-H62-1807		P	
UTE 2-6B2	06					14-20-H62-1807		P	
UTE TRIBAL 3-6B2	06					14-20-H62-1807		P	С
POWELL 4-19A1	19			4301330071		14-20-H62-1847		Р	ļ
COLTHARP 1-27Z1	27			4301330151		14-20-H62-1933		P	ļ
UTE 1-8A1E	08		L	4304730173		14-20-H62-2147		Р	
UTE TRIBE 1-31	31			4301330278		14-20-H62-2421		Ρ	ļ
UTE 1-28B6X	28					14-20-H62-2492		Р	
RINKER 2-21B5	21					14-20-H62-2508		Р	
MURDOCK 2-34B5	34					14-20-H62-2511		Р	
UTE 1-35B6	35			4301330507		14-20-H62-2531		Р	
UTE TRIBAL 1-17A1E	17	1 -		4304730829	1	14-20-H62-2658		Р	
UTE 2-17A1E	17	0108	010E	4304737831	16709	14-20-H62-2658	OW	Р	
UTE TRIBAL 1-27A1E	27	0108	010E	4304730421	800	14-20-H62-2662	OW	Р	
UTE TRIBAL 1-35A1E	35	0108	010E	4304730286	795	14-20-H62-2665	OW	P	
UTE TRIBAL 1-15A1E	15	0108	010E	4304730820	850	14-20-H62-2717	OW	Р	ļ ·
UTE TRIBAL P-3B1E	03			4304730190		14-20-H62-2873		Р	
UTE TRIBAL 1-22A1E	22			4304730429		14-20-H62-3103		Р	ļ
B H UTE 1-35C6	35					14-20-H62-3436		Р	<u> </u>
BH UTE 2-35C6	35					14-20-H62-3436		Р	<u></u>
MCFARLANE 1-4D6	04					14-20-H62-3452		Р	
UTE TRIBAL 1-11D6	11			4301330482		14-20-H62-3454		P	ļ
CARSON 2-36A1	36			4304731407	4	14-20-H62-3806		P	
UTE 2-14C6	14			4301330775		14-20-H62-3809	+	P	
DWR 3-14C6	14				1	14-20-H62-3809		P	
THE PERFECT "10" 1-10A1	10		L	4301330935		14-20-H62-3855		P	ļ
BADGER-SAM H U MONGUS 1-15A1	15			4301330949		14-20-H62-3860		P	
MAXIMILLIAN-UTE 14-1	14			4301330726		14-20-H62-3868		<u>.</u> Р	-
FRED BASSETT 1-22A1	22			4301330781		14-20-H62-3880	1	P	t
UTE TRIBAL 1-30Z1	30					14-20-H62-3910		P	
UTE LB 1-13A3	13			4301330894		14-20-H62-3980		P	
	22					14-20-H62-4614		P	ļ
UTE 2-22B6 UINTA OURAY 1-1A3						14-20-H62-4664		P	
	01					14-20-H62-4752		P	<u> </u>
UTE 1-6D6	06					1420H624801		P	
UTE 2-11D6	11						OW		
UTE 1-15D6	15					14-20-H62-4824		P	<u> </u>
UTE 2-15D6	15					14-20-H62-4824		P	
HILL 3-24C6	24					1420H624866	OW	Р	С
BARCLAY UTE 2-24C6R	24			L		14-20-H62-4866		P	
BROTHERSON 1-2B4	02			4301330062		FEE	OW	P	ļ
BOREN 1-24A2	24			4301330084		FEE	OW	Р	
FARNSWORTH 1-13B5	13			4301330092		FEE	OW	Р	
BROADHEAD 1-21B6	21			4301330100		FEE	OW	P	
ASAY E J 1-20A1	20	- 		4301330102		FEE	OW	Р	ļ
HANSON TRUST 1-5B3	05			4301330109		FEE	OW	P	
ELLSWORTH 1-8B4	08			4301330112		FEE	OW	Р	L
ELLSWORTH 1-9B4	09			4301330118		FEE	OW	Р	
ELLSWORTH 1-17B4	17			4301330126		FEE	OW	Р	
CHANDLER 1-5B4	05	0208	040W	4301330140	1685	FEE	OW	Р	
HANSON 1-32A3	32	0108	030W	4301330141	1640	FEE	OW	Р	
JESSEN 1-17A4	17			4301330173		FEE	OW	P	T

LIENIKINO 4 4DO	04	0200	020\4/	4204220475	4700	ree	OW	Р
JENKINS 1-1B3	01	<u> </u>		4301330175	I	FEE FEE	OW	P
GOODRICH 1-2B3	02			4301330182	<u> </u>	FEE	OW	P
ELLSWORTH 1-19B4	19			4301330183			OW	P
DOYLE 1-10B3	10			4301330187		FEE		P
JOS. SMITH 1-17C5	17			4301330188		FEE	OW	
RUDY 1-11B3	11			4301330204		FEE	OW	P
CROOK 1-6B4	06			4301330213		FEE	OW	P
HUNT 1-21B4	21			4301330214		FEE	OW	P
LAWRENCE 1-30B4	30			4301330220	1	FEE	OW	P
YOUNG 1-29B4	29			4301330246		FEE	OW	P
GRIFFITHS 1-33B4	33	1		4301330288		FEE	OW	P
POTTER 1-2B5	02	h		4301330293		FEE	OW	P
BROTHERSON 1-26B4	26			4301330336		FEE	OW	P
SADIE BLANK 1-33Z1	33			4301330355		FEE	OW	Р
POTTER 1-24B5	24	I		4301330356		FEE	OW	P
WHITEHEAD 1-22A3	22			4301330357		FEE	OW	Р
CHASEL MILLER 2-1A2	01	1	L	4301330360		FEE	OW	Р
ELDER 1-13B2	13			4301330366	<u> </u>	FEE	OW	P
BROTHERSON 2-10B4	10			4301330443		FEE	OW	Р
FARNSWORTH 2-7B4	07	t		4301330470		FEE	OW	Р
TEW 1-15A3	15			4301330529		FEE	OW	Р
UTE FEE 2-20C5	20			4301330550	L	FEE	OW	P
HOUSTON 1-34Z1	34			4301330566		FEE	OW	Р
GALLOWAY 1-18B1	18			4301330575		FEE	OW	Р
SMITH 1-31B5	31	1		4301330577		FEE	OW	P
LEBEAU 1-34A1	34			4301330590		FEE	OW	Р
LINMAR 1-19B2	19	020S	020W	4301330600	9350	FEE	OW	Р
WISSE 1-28Z1	28	010N	010W	4301330609	905	FEE	OW	Р
POWELL 1-21B1	21	0208	010W	4301330621	910	FEE	OW	Р
HANSEN 1-24B3	24	0208	030W	4301330629	2390	FEE	OW	P
OMAN 2-4B4	04	0208	040W	4301330645	9125	FEE	OW	P
DYE 1-25Z2	25			4301330659		FEE	OW	Р
H MARTIN 1-21Z1	21	010N	010W	4301330707	925	FEE	OW	Р
JENSEN 1-29Z1	29	010N	010W	4301330725	9110	FEE	OW	Р
CHASEL 2-17A1 V	17	010S	010W	4301330732	9112	FEE	OW	Р
BIRCHELL 1-27A1	27			4301330758		FEE	OW	Р
CHRISTENSEN 2-8B3	08	0208	030W	4301330780	9355	FEE	OW	Р
LAMICQ 2-5B2	05	0208	020W	4301330784	2302	FEE	OW	Р
BROTHERSON 2-14B4	14	0208	040W	4301330815	10450	FEE	OW	Р
MURRAY 3-2A2	02	010S	020W	4301330816	9620	FEE	OW	Р
HORROCKS 2-20A1 V	20	0108	010W	4301330833	8301	FEE	OW	Р
BROTHERSON 2-2B4	02	0208	040W	4301330855	8420	FEE	OW	P
ELLSWORTH 2-8B4	08	L	L	4301330898		FEE	OW	Р
OMAN 2-32A4	32	010S	040W	4301330904	10045	FEE	OW	Р
BELCHER 2-33B4	33	0208	040W	4301330907	9865	FEE	OW	Р
BROTHERSON 2-35B5	35	0208	050W	4301330908	9404	FEE	OW	P
HORROCKS 2-4A1 T	04	010S	010W	4301330954	9855	FEE	OW	Р
JENSEN 2-29A5	29	010S	050W	4301330974	10040	FEE	OW	P
UTE 2-34A4	34	010S	040W	4301330978	10070	FEE	OW	P
CHANDLER 2-5B4	05			4301331000			OW	P
BABCOCK 2-12B4	12	0208	040W	4301331005	10215	FEE	OW	Р
BADGER MR BOOM BOOM 2-29A1	29	0108	010W	4301331013	9463	FEE	OW	Р
BLEAZARD 2-18B4	18	020\$	040W	4301331025	1566	FEE	OW	Р
BROADHEAD 2-32B5	32	020S	050W	4301331036	10216	FEE	OW	P
ELLSWORTH 2-16B4	16			4301331046			OW	P
RUST 3-4B3	04			4301331070		FEE	OW	Р
HANSON TRUST 2-32A3	32	0108	030W	4301331072	1641	FEE	OW	Р
BROTHERSON 2-11B4	11	020\$	040W	4301331078	1541	FEE	OW	P

HANSON TRUST 2-5B3	05	0208	020/4/	4301331079	1626	FEE	OW	P	—
	15			4301331079	1	FEE	OW	P	
BROTHERSON 2-15B4								L L	4
MONSEN 2-27A3	27			4301331104		FEE	OW	P	
ELLSWORTH 2-19B4	19			4301331105		FEE	OW	P	
HUNT 2-21B4	21			4301331114		FEE	OW	P	
JENKINS 2-1B3	01			4301331117		FEE	OW	P	
POTTER 2-24B5	24			4301331118		FEE	OW	P	
POWELL 2-13A2 K	13			4301331120		FEE	OW	Р	
JENKINS 2-12B3	12			4301331121			OW	Р	
MURDOCK 2-26B5	26			4301331124		FEE	OW	Р	
BIRCH 3-27B5	27	.1	1	4301331126		FEE	OW	P	
ROBB 2-29B5	29			4301331130			OW	Р	
LAKE FORK 2-13B4	13			4301331134			OW	P	
DUNCAN 3-1A2 K	01	010S	020W	4301331135	10484	FEE	OW	Р	
HANSON 2-9B3	09			4301331136			OW	P	
ELLSWORTH 2-9B4	09	0208	040W	4301331138	10460	FEE	OW	P	
UTE 2-31A2	31	0108	020W	4301331139	10458	FEE	OW	Р	
POWELL 2-19A1 K	19	0108	010W	4301331149	8303	FEE	OW	Р	
CEDAR RIM 8-A	22	0308	060W	4301331171	10666	FEE	OW	Р	
POTTER 2-6B4	06	0208	040W	4301331249	11038	FEE	OW	P	
MILES 2-1B5	01			4301331257			OW	Р	
MILES 2-3B3	03			4301331261			OW	P	
MONSEN 2-22A3	22			4301331265			OW	Р	
WRIGHT 2-13B5	13			4301331267			OW	P	
TODD 2-21A3	21			4301331296			OW	P	
WEIKART 2-29B4	29			4301331298			OW	P	
YOUNG 2-15A3	15			4301331301			OW	P	
CHRISTENSEN 2-29A4	29			4301331303			OW	P	
BLEAZARD 2-28B4	28			4301331304	+		OW	P	
REARY 2-17A3	17		<u> </u>	4301331304			OW	P	
	11			4301331316			OW	P	
LAZY K 2-11B3	+			4301331354	L		OW	P	
LAZY K 2-14B3	14						OW	P	
MATTHEWS 2-13B2	13			4301331357			OW	P	
LAKE FORK 3-15B4	15			4301331358			OW	P	
STEVENSON 3-29A3	29			4301331376				P	
MEEKS 3-8B3	08			4301331377			OW	•	
ELLSWORTH 3-20B4	20			4301331389			OW	P	
DUNCAN 5-13A2	13			4301331516			OW	Р	
OWL 3-17C5	17			4301332112			OW	P	
BROTHERSON 2-24 B4	24			4301332695			OW	P	
BODRERO 2-15B3	15			4301332755			OW	P	
BROTHERSON 2-25B4	25			4301332791			OW	Р	
CABINLAND 2-16B3	16			4301332914			OW	Р	
KATHERINE 3-29B4	29			4301332923	+		OW	Р	
SHRINERS 2-10C5	10			4301333008			OW	Р	
BROTHERSON 2-26B4	26			4301333139			OW	Р	
MORTENSEN 4-32A2	32	0108	020W	4301333211	15720	FEE	OW	Р	
FERRARINI 3-27B4	27	0205	040W	4301333265	15883	FEE	OW	Р	
RHOADES 2-25B5	25	0208	050W	4301333467	16046	FEE	OW	P	
CASE 2-31B4	31	020S	040W	4301333548	16225	FEE	OW	P	
ANDERSON-ROWLEY 2-24B3	24			4301333616			OW	Р	
SPROUSE BOWDEN 2-18B1	18			4301333808			OW	Р	
BROTHERSON 3-11B4	11			4301333904			OW	Р	
KOFFORD 2-36B5	36			4301333988			OW	P	
ALLEN 3-7B4	07			4301334027			OW	P	No. 10 10 10 10 10 10 10 10 10 10 10 10 10
BOURNAKIS 3-18B4	18	<u> </u>	<u> </u>	4301334091	+		OW	Р	
MILES 3-12B5	12			4301334110			OW	P	
OWL and HAWK 2-31B5	31	·		4301334123	<u> </u>		OW	Р	
	<u> </u>	2200	COUTT	1001007120	1	·		<u> </u>	

OWL and HAWK 4-17C5	17	0206	OFO\A/	4301334193	17207	CEC	OW	Р	
	17 32			4301334193	<u> </u>		OW	P	 -
DWR 3-32B5			t	L				P	
LAKE FORK RANCH 3-22B4	22		+	4301334261			OW		ļ
HANSON 3-9B3	09			4301350065			OW	Р	ļ
DYE 2-28A1	28			4301350066			OW	Р	ļ
MEEKS 3-32A4	32			4301350069			OW	Р	<u></u>
HANSON 4-8B3	08			4301350088			OW	P	С
LAKE FORK RANCH 3-14B4	14			4301350097			OW	Р	
ALLEN 3-9B4	09			4301350123			OW	Р	<u></u>
HORROCKS 4-20A1	20	0108	010W	4301350155	17916	FEE	OW	P	
HURLEY 2-33A1	33	0108	010W	4301350166	17573	FEE	OW	Р	
HUTCHINS/CHIODO 3-20C5	20	0308	050W	4301350190	17541	FEE	OW	Р	
ALLEN 3-8B4	08	0208	040W	4301350192	17622	FEE	OW	P	
OWL and HAWK 3-10C5	10	0308	050W	4301350193	17532	FEE	OW	P	1
OWL and HAWK 3-19C5	19	030S	050W	4301350201	17508	FEE	OW	Р	
EL PASO 4-29B5	29		+	4301350208			ow	P	C
DONIHUE 3-20C6	20			4301350270			OW	Р	1=
HANSON 3-5B3	05			4301350275			OW	Р	С
SPRATT 3-26B5	26			4301350302			OW	P	1
REBEL 3-35B5	35			4301350388			ow	P	С
FREEMAN 4-16B4	16			4301350388			OW	P	C
					L		OW	P	C
WILSON 3-36B5	36			4301350439					
EL PASO 3-21B4	21			4301350474	1		OW	P	С
IORG 4-12B3	12			4301350487			OW	P	С
CONOVER 3-3B3	03			4301350526			OW	Р	С
ROWLEY 3-16B4	16			4301350569			OW	P	С
POTTS 3-14B3	14			4301350570			OW	Р	С
POTTER 4-27B5	27			4301350571			OW	P	С
EL PASO 4-21B4	21			4301350572	·		OW	Р	С
LAKE FORK RANCH 3-26B4	26	0208	040W	4301350707	18270	Fee	OW	Р	С
LAKE FORK RANCH 3-25B4	25	0208	040W	4301350711	18220	Fee	OW	Р	С
LAKE FORK RANCH 4-23B4	23	0208	040W	4301350713	18271	Fee	OW	P	С
LAKE FORK RANCH 4-15B4	15	0208	040W	4301350715	18314	Fee	OW	Р	С
LAKE FORK RANCH 3-24B4	24	0208	040W	4301350716	18269	Fee	OW	P	С
GOLINSKI 1-8C4	08	_1		4301350986			OW	Р	С
J ROBERTSON 1-1B1	01			4304730174		FEE	OW	P	+
TIMOTHY 1-8B1E	08			4304730215		FEE	OW	Р	+
MAGDALENE PAPADOPULOS 1-34A1E	34			4304730241		FEE	OW	P	
NELSON 1-31A1E	31			4304730671		FEE	OW	P	+
ROSEMARY LLOYD 1-24A1E	24			4304730707		FEE	ow	P	+
H D LANDY 1-30A1E	30			4304730790		FEE	ow	P	
						FEE	OW	P	+
WALKER 1-14A1E	14			4304730805					ļ
BOLTON 2-29A1E	29			4304731112		FEE	OW	Р	
PRESCOTT 1-35Z1	35			4304731173		FEE	OW	P	+
BISEL GURR 11-1	11			4304731213	1	FEE	OW	Р	
UTE TRIBAL 2-22A1E	22			4304731265		FEE	OW	Р	
L. BOLTON 1-12A1	12			4304731295		FEE	OW	Р	
FOWLES 1-26A1	26	010S	010W	4304731296		FEE	OW	Р	1
BRADLEY 23-1	23	0108	010W	4304731297	8435	FEE	OW	Р	
BASTIAN 1-2A1	02	010S	010W	4304731373	736	FEE	OW	P	
D R LONG 2-19A1E	19			4304731470		FEE	OW	Р	1
D MOON 1-23Z1	23			4304731479			OW	P	
O MOON 2-26Z1	26			4304731480			OW	P	
LILA D 2-25A1	25			4304731797			OW	P	+
LANDY 2-30A1E	30			4304731797			ow	P	+
WINN P2-3B1E	03			4304732321			ow	P	+
	- 			4304732321		The second secon	OW	P	+
BISEL-GURR 2-11A1	11	·			+		+		ļ
FLYING J FEE 2-12A1	12	<u></u>	UTUVV	4304739467	10000	ree	OW	Р	

HARVEST FELLOWSHIP CHURCH 2-14B1	14		<u> </u>	4304739591			OW	Р
OBERHANSLY 3-11A1	11			4304739679			OW	Р
DUNCAN 2-34A1	34			4304739944			OW	Р
BISEL GURR 4-11A1	11			4304739961			OW	P
KILLIAN 3-12A1	12			4304740226			OW	P
WAINOCO ST 1-14B1	14			4304730818		ML-24306-A	OW	Р
UTAH ST UTE 1-35A1	35			4304730182		ML-25432	OW	Р
STATE 1-19A4	19	010S	040W	4301330322	9118	ML-27912	OW	Р
FEDERAL 2-28E19E	28	050S	190E	4304732849	12117	UTU-0143512	OW	Р
FEDERAL 1-28E19E	28	050S	190E	4304730175	5680	UTU143512	OW	Р
BLANCHARD 1-3A2	03	0108	020W	4301320316	5877	FEE	OW	PA
W H BLANCHARD 2-3A2	03	010S	020W	4301330008	5775	FEE	OW	PA
YACK U 1-7A1	07	010S	010W	4301330018	5795	FEE	OW	PA
JAMES POWELL 3	13		+	4301330024		FEE	WD	PA
BASTIAN 1 (3-7D)	07			4301330026		FEE	OW	PA
LAMICQ-URRUTY 1-8A2	08			4301330036		FEE	OW	PA
BLEAZARD 1-18B4	18			4301330059			OW	PA
OLSEN 1-27A4	27			4301330064		FEE	OW	PA
EVANS 1-31A4	31	1		4301330067		FEE	OW	PA
HAMBLIN 1-26A2	26		1	4301330083	L	FEE	OW	PA
HARTMAN 1-31A3	31			4301330093			OW	PA
FARNSWORTH 1-7B4	07			4301330097		FEE	ow	PA
POWELL 1-33A3	33			4301330105		FEE	ow	PA
LOTRIDGE GATES 1-3B3	03			4301330103		FEE	OW	PA
REMINGTON 1-34A3	34		L	4301330117	L	FEE	OW	PA
						FEE	OW	PA
ANDERSON 1-28A2	28			4301330150				PA
RHOADES MOON 1-35B5	35			4301330155		FEE	OW	
JOHN 1-3B2	03			4301330160		FEE	OW	PA
SMITH 1-6C5	06			4301330163		FEE	OW	PA
HORROCKS FEE 1-3A1	03			4301330171		FEE	OW	PA
WARREN 1-32A4	32			4301330174		FEE	OW	PA
JENSEN FENZEL 1-20C5	20			4301330177		FEE	OW	PA
MYRIN RANCH 1-13B4	13			4301330180		FEE	OW	PA
BROTHERSON 1-27B4	27			4301330185		FEE	OW	PA
JENSEN 1-31A5	31			4301330186		FEE	OW	PA
ROBERTSON 1-29A2	29			4301330189		FEE	OW	PA
WINKLER 1-28A3	28			4301330191		FEE	OW	PA
CHENEY 1-33A2	33			4301330202		FEE	OW	PA
J LAMICQ STATE 1-6B1	06			4301330210		FEE	OW	PA
REESE ESTATE 1-10B2	10			4301330215		FEE	OW	PA
REEDER 1-17B5	17			4301330218		FEE	OW	PA
ROBERTSON UTE 1-2B2	02			4301330225		FEE	OW	PA
HATCH 1-5B1	05	020S	010W	4301330226	5470	FEE	OW	PA
BROTHERSON 1-22B4	22	0208	040W	4301330227	5935	FEE	OW	PA
ALLRED 1-16A3	16	0108	030W	4301330232	1780	FEE	OW	PA
BIRCH 1-35A5	35	0108	050W	4301330233	9116	FEE	OW	PA
MARQUERITE UTE 1-8B2	08	0205	020W	4301330235	9122	FEE	OW	PA
BUZZI 1-11B2	11			4301330248			OW	PA
SHISLER 1-3B1	03			4301330249			OW	PA
TEW 1-1B5	01	+	·	4301330264			OW	PA
EVANS UTE 1-19B3	19			4301330265			OW	PA
SHELL 2-27A4	27		+	4301330266			WD	PA
DYE 1-29A1	29			4301330271			OW	PA
VODA UTE 1-4C5	04			4301330283			OW	PA
BROTHERSON 1-28A4	28			4301330292		The same of the sa	OW	PA
MEAGHER 1-4B2	04			4301330292		FEE	OW	PA
NORLING 1-9B1	09			4301330315		FEE	OW	PA
	09			4301330316		FEE	OW	PA
S. BROADHEAD 1-9C5	UB	0303	UJUVV	490 (9909 10	JJ4U	I CL	UVV	

THACTING A GOAG	00	0400	000141	400400004	140000		10141	54
TIMOTHY 1-09A3	09			4301330321			OW	PA
BARRETT 1-34A5	34			4301330323		FEE	OW	PA
MEAGHER TRIBAL 1-9B2	09			4301330325		FEE	OW	PA
PHILLIPS UTE 1-3C5	03			4301330333		FEE	OW	PA
ELLSWORTH 1-20B4	20			4301330351		FEE	OW	PA
LAWSON 1-28A1	28			4301330358		FEE	ow	PA
AMES 1-23A4	23			4301330375		FEE	OW	PA
HORROCKS 1-6A1	06			4301330390		FEE	OW	PA
SHRINE HOSPITAL 1-10C5	10			4301330393		FEE	OW	PA
GOODRICH 1-18B2	18	020S	020W	4301330397	5485	FEE	OW	PA
SWD POWELL 3	13			4301330478		FEE	WD	PA
BODRERO 1-15B3	15	0208	030W	4301330565	4534	FEE	OW	PA
MOON TRIBAL 1-30C4	30	0308	040W	4301330576	2360	FEE	OW	PA
DUNCAN 2-9B5	09	0208	050W	4301330719	5440	FEE	OW	PA
FISHER 1-16A4	16	0108	040W	4301330737	2410	FEE	OW	PA
URRUTY 2-34A2	34			4301330753		FEE	OW	PA
GOODRICH 1-24A4	24			4301330760		FEE	OW	PA
CARL SMITH 2-25A4	25			4301330776		FEE	OW	PA
ANDERSON 1-A30B1	30			4301330783		FEE	OW	PA
CADILLAC 3-6A1	06			4301330834		FEE	ow	PA
MCELPRANG 2-31A1	31			4301330836		FEE	ow	PA
REESE ESTATE 2-10B2	10			4301330837		FEE	OW	PA
CLARK 2-9A3	09			4301330876		FEE	OW	PA
JENKINS 3-16A3	16			4301330877		FEE	OW	PA
CHRISTENSEN 2-26A5	26			4301330905			OW	PA
FORD 2-36A5	36			4301330903		FEE	OW	PA
MORTENSEN 2-32A2	32			4301330911		FEE	OW	PA
WILKERSON 1-20Z1	20			4301330929		FEE	OW	PA
	04			4301330942			OW	PA
UTE TRIBAL 2-4A3 S	<u> </u>							
OBERHANSLY 2-31Z1	31			4301330970		FEE	OW	PA
MORRIS 2-7A3	07			4301330977		FEE	OW	PA
POWELL 2-08A3	08			4301330979	1		OW	PA
FISHER 2-6A3	06			4301330984			OW	PA
JACOBSEN 2-12A4	12			4301330985			OW	PA
CHENEY 2-33A2	33			4301331042	1		OW	PA
HANSON TRUST 2-29A3	29			4301331043		FEE	OW	PA
BURTON 2-15B5	15			4301331044			OW	PA
EVANS-UTE 2-17B3	17			4301331056			ow	PA
ELLSWORTH 2-20B4				4301331090		FEE	OW	PA
REMINGTON 2-34A3	34			4301331091			OW	PA
WINKLER 2-28A3	28			4301331109			OW	PA
TEW 2-10B5	10			4301331125			OW	PA
LINDSAY 2-33A4	33	0108	040W	4301331141	1756	FEE	OW	PA
FIELDSTED 2-28A4	28	010S	040W	4301331293	10665	FEE	OW	PA
POWELL 4-13A2	13	0108	020W	4301331336	11177	FEE	GW	PA
DUMP 2-20A3				4301331505			OW	PA
SMITH 2X-23C7				4301331634			D	PA
MORTENSEN 3-32A2	32			4301331872			OW	PA
TODD USA ST 1-2B1	02			4304730167			OW	PA
STATE 1-7B1E	07			4304730180		FEE	OW	PA
BACON 1-10B1E	10			4304730881		FEE	OW	PA
PARIETTE DRAW 28-44	28			4304731408		FEE	OW	PA
REYNOLDS 2-7B1E	07			4304731840		FEE	OW	PA
STATE 2-35A2	35			4301330156	<u> </u>	ML-22874	ow	PA
UTAH STATE L B 1-11B1	11			4304730171		ML-23655	OW	PA
STATE 1-8A3	08			4301330286		ML-24316	ow	PA
UTAH FEDERAL 1-24B1	24			4304730220		ML-26079	OW	PA
						14-20-462-1329		S
CEDAR RIM 15	34	0305	00000	4301330383	0292	14-20-402-1329	UVV	3

LUTE TOIDAL O 0407	0.4	0000	070144	4004004000	40040	44 00 1100 4405	014/		
UTE TRIBAL 2-24C7	24					14-20-H62-1135		S S	
CEDAR RIM 12	28		1		1	14-20-H62-1323			
CEDAR RIM 16	33					14-20-H62-1328		S	
SPRING HOLLOW 2-34Z3	34	l		4301330234	·	14-20-H62-1480		S	
EVANS UTE 1-17B3	17			4301330274		14-20-H62-1733		S	
UTE JENKS 2-1-B4 G	01	·		l	·	14-20-H62-1782		S	
UTE 3-12B3	12					14-20-H62-1810		S	
UTE TRIBAL 9-4B1	04			4301330194		14-20-H62-1969		S	
UTE TRIBAL 2-21B6	21	J				14-20-H62-2489		S	
UTE 1-33B6	33			4301330441				S	
UTE 2-22B5	22	1				14-20-H62-2509		S	
UTE 1-18B1E	18			4304730969			OW	S	
LAUREN UTE 1-23A3	23	0108	030W	4301330895	9403	14-20-H62-3981	OW	S	
UTE 2-28B6	28	0208	060W	4301331434	11624	14-20-H62-4622		S	
UTE 1-27B6X	27	020S	060W	4301330517	11166	14-20-H62-4631	OW	S	
UTE 2-27B6	27	020S	060W	4301331449	11660	14-20-H62-4631		S	
CEDAR RIM 10-15C6	15	0308	060W	4301330328	6365	14-20-H62-4724	OW	S	
UTE 5-30A2	30	010S	020W	4301330169	5910	14-20-H62-4863	OW	S	
UTE TRIBAL G-1 (1-24C6)	24		1	4301330298		14-20-H62-4866		S	
UTE TRIBAL FEDERAL 1-30C5	30		1	4301330475		14-20-H62-4876		S	
SMB 1-10A2	10			4301330012		FEE	OW	S	
KENDALL 1-12A2	12			4301330013		FEE	OW	S	
CEDAR RIM 2	20			4301330019		FEE	ow	S	
URRUTY 2-9A2	09			4301330046	1	FEE	OW	S	
BROTHERSON 1-14B4	14			4301330051		FEE	ow	S	
RUST 1-4B3	04			4301330063		FEE	ow	S	
MONSEN 1-21A3	21	1		4301330082		FEE	ow	S	
	-			4301330062		FEE	OW	S	
BROTHERSON 1-10B4	10					FEE	OW	S	
FARNSWORTH 1-12B5	12			4301330124				S	
ELLSWORTH 1-16B4	16		I	4301330192		FEE	OW		
MARSHALL 1-20A3	20			4301330193		FEE	OW	S	
CHRISTMAN BLAND 1-31B4	31			4301330198		FEE	OW		
ROPER 1-14B3	14			4301330217		FEE	OW	S	
BROTHERSON 1-24B4	24			4301330229		FEE	OW	S	
BROTHERSON 1-33A4	33			4301330272		FEE	OW	S	
BROTHERSON 1-23B4	23			4301330483		FEE	OW	S	
SMITH ALBERT 2-8C5	08			4301330543			OW	S	
VODA JOSEPHINE 2-19C5	19			4301330553			OW	S	
HANSEN 1-16B3	16		·	4301330617	·		OW	S	
BROTHERSON 1-25B4	25			4301330668		FEE	OW	S	
POWELL 2-33A3	33	010S	030W	4301330704	2400	FEE	OW	S	
BROWN 2-28B5	28	0208	050W	4301330718	9131	FEE	OW	S	
EULA-UTE 1-16A1	16	0108	010W	4301330782	8443	FEE	OW	S	
JESSEN 1-15A4	15			4301330817		FEE	OW	S	
R HOUSTON 1-22Z1	22			4301330884		FEE	OW	S	
FIELDSTED 2-27A4	27			4301330915		FEE	OW	S	
HANSKUTT 2-23B5	23			4301330917			OW	S	
TIMOTHY 3-18A3	18			4301330940		FEE	OW	S	
BROTHERSON 2-3B4	03			4301331008			OW	S	
BROTHERSON 2-22B4	22			4301331086		FEE	OW	S	
MILES 2-35A4	35			4301331087			OW	S	
ELLSWORTH 2-17B4	17	+		4301331089		FEE	ow	S	
RUST 2-36A4	36			4301331092		FEE	OW	S	
EVANS 2-19B3	19			4301331092		FEE	OW	S	
	12			4301331115		FEE	OW	S	
FARNSWORTH 2-12B5							OW	S	
CHRISTENSEN 3-4B4	04	+		4301331142	+			S	
ROBERTSON 2-29A2	29		<u> </u>	4301331150	 		OW	A	
CEDAR RIM 2A	20	0308	UDUVV	4301331172	100/1	rct	OW	S	

El Paso E9 Company, L.P. (N3065) to EP Energy E9 Company, L.P. (N3850) effective 6/1/2012

HARTMAN 2-31A3	31	0108	030W	4301331243	11026	FEE	OW	S
GOODRICH 2-2B3	02	020\$	030W	4301331246	11037	FEE	OW	S
JESSEN 2-21A4	21	0108	040W	4301331256	11061	FEE	OW	S
BROTHERSON 3-23B4	23	020S	040W	4301331289	11141	FEE	OW	S
MYRIN RANCH 2-18B3	18	020\$	030W	4301331297	11475	FEE	OW	S
BROTHERSON 2-2B5	02	020\$	050W	4301331302	11342	FEE	OW	S
DASTRUP 2-30A3	30	010S	030W	4301331320	11253	FEE	OW	S
YOUNG 2-30B4	30	020S	040W	4301331366	11453	FEE	OW	S
IORG 2-10B3	10	0208	030W	4301331388	11482	FEE	OW	S
MONSEN 3-27A3	27	0108	030W	4301331401	11686	FEE	OW	S
HORROCKS 2-5B1E	05	0208	010E	4304732409	11481	FEE	OW	S
LARSEN 1-25A1	25	0108	010W	4304730552	815	FEE	OW	TA
DRY GULCH 1-36A1	36	0108	010W	4304730569	820	FEE	OW	TA

Sundry Number: 34196 API Well Number: 43013301870000

	STATE OF UTAH			FORM 9
	DEPARTMENT OF NATURAL RESOU DIVISION OF OIL, GAS, AND M			5.LEASE DESIGNATION AND SERIAL NUMBER: FEE
SUNDR	RY NOTICES AND REPORTS	S ON V	VELLS	6. IF INDIAN, ALLOTTEE OR TRIBE NAME:
Do not use this form for pro current bottom-hole depth, FOR PERMIT TO DRILL form	posals to drill new wells, significant reenter plugged wells, or to drill hori n for such proposals.	tly deepe izontal la	n existing wells below terals. Use APPLICATION	7.UNIT or CA AGREEMENT NAME:
1. TYPE OF WELL Oil Well				8. WELL NAME and NUMBER: DOYLE 1-10B3
2. NAME OF OPERATOR: EP ENERGY E&P COMPANY,	L.P.			9. API NUMBER: 43013301870000
3. ADDRESS OF OPERATOR: 1001 Louisiana , Houston,	TX, 77002 713 997	PHON 7-5038 E	E NUMBER: Ext	9. FIELD and POOL or WILDCAT: ALTAMONT
4. LOCATION OF WELL FOOTAGES AT SURFACE: 2382 FNL 2157 FWL				COUNTY: DUCHESNE
QTR/QTR, SECTION, TOWNSH Qtr/Qtr: SENW Section:	HIP, RANGE, MERIDIAN: 10 Township: 02.0S Range: 03.0W M	leridian: l	J	STATE: UTAH
11. CHEC	K APPROPRIATE BOXES TO INDIC	CATE NA	TURE OF NOTICE, REPOF	RT, OR OTHER DATA
TYPE OF SUBMISSION			TYPE OF ACTION	
	✓ ACIDIZE	☐ AL	TER CASING	CASING REPAIR
Approximate date work will start:	CHANGE TO PREVIOUS PLANS	Сн	ANGE TUBING	CHANGE WELL NAME
1/30/2013	CHANGE WELL STATUS	□ со	MMINGLE PRODUCING FORMATIONS	CONVERT WELL TYPE
SUBSEQUENT REPORT	DEEPEN	☐ FR	ACTURE TREAT	NEW CONSTRUCTION
Date of Work Completion:	OPERATOR CHANGE	PLU	UG AND ABANDON	PLUG BACK
	PRODUCTION START OR RESUME	RE	CLAMATION OF WELL SITE	RECOMPLETE DIFFERENT FORMATION
SPUD REPORT Date of Spud:	REPERFORATE CURRENT FORMATION	SID	DETRACK TO REPAIR WELL	TEMPORARY ABANDON
	TUBING REPAIR	VEI	NT OR FLARE	WATER DISPOSAL
DRILLING REPORT	WATER SHUTOFF	☐ si	TA STATUS EXTENSION	APD EXTENSION
Report Date:	WILDCAT WELL DETERMINATION	□ от	HER	OTHER:
12 DESCRIBE PROPOSED OR	COMPLETED OPERATIONS. Clearly sho	w all nerti	inent details including dates	
	Please see attachment for	-	•	Approved by the Utah Division of Oil, Gas and Mining
				Date: January 31, 2013
				By: Dar K Ount
NAME (PLEASE PRINT)	PHONE NUM	MBER	TITLE	
Lisa Morales	713 997-3587		Regulatory Analyst	
SIGNATURE N/A			DATE 1/29/2013	

Sundry Number: 34196 API Well Number: 43013301870000



Doyle 1-10B3 Rod Part Procedure Summary

API 43-013-30187-0000

- POOH w/rods, pump, and tubing
- Acidize existing perfs w/ 5,000 gal 15% HCl.
- RIH w/ BHA, tubing and rod string
- Clean location and resume production

RECEIVED: Jan. 29, 2013

Sundry Number: 37566 API Well Number: 43013301870000

					_		
	STATE OF UTAH			FORM	9		
I	DEPARTMENT OF NATURAL RESOULDIVISION OF OIL, GAS, AND M		3	5.LEASE DESIGNATION AND SERIAL NUMBER	₹:		
SUNDR	Y NOTICES AND REPORTS	S ON	WELLS	6. IF INDIAN, ALLOTTEE OR TRIBE NAME:	_		
	posals to drill new wells, significant reenter plugged wells, or to drill hori: n for such proposals.			7.UNIT or CA AGREEMENT NAME:	_		
1. TYPE OF WELL Oil Well				8. WELL NAME and NUMBER: DOYLE 1-10B3	_		
2. NAME OF OPERATOR: EP ENERGY E&P COMPANY,	L.P.			9. API NUMBER: 43013301870000			
3. ADDRESS OF OPERATOR: 1001 Louisiana, Houston,	TX, 77002 713 997		NE NUMBER: Ext	9. FIELD and POOL or WILDCAT: ALTAMONT	_		
4. LOCATION OF WELL FOOTAGES AT SURFACE: 2382 FNL 2157 FWL				COUNTY: DUCHESNE			
QTR/QTR, SECTION, TOWNSH	HIP, RANGE, MERIDIAN: 10 Township: 02.0S Range: 03.0W M	U	STATE: UTAH				
11. CHECI	K APPROPRIATE BOXES TO INDIC	ATE N	ATURE OF NOTICE, REPOR	RT, OR OTHER DATA			
TYPE OF SUBMISSION			TYPE OF ACTION				
	ACIDIZE		ALTER CASING	CASING REPAIR	_		
NOTICE OF INTENT	CHANGE TO PREVIOUS PLANS		CHANGE TUBING	CHANGE WELL NAME			
Approximate date work will start:	CHANGE WELL STATUS		COMMINGLE PRODUCING FORMATIONS	CONVERT WELL TYPE			
SUBSEQUENT REPORT Date of Work Completion:	DEEPEN	\Box	FRACTURE TREAT	New construction			
2/3/2013			PLUG AND ABANDON	PLUG BACK			
	OPERATOR CHANGE						
SPUD REPORT Date of Spud:	PRODUCTION START OR RESUME		RECLAMATION OF WELL SITE	☐ RECOMPLETE DIFFERENT FORMATION			
	REPERFORATE CURRENT FORMATION	□ :	SIDETRACK TO REPAIR WELL	LI TEMPORARY ABANDON			
DRILLING REPORT	TUBING REPAIR	<u></u>	/ENT OR FLARE	WATER DISPOSAL			
Report Date:	WATER SHUTOFF	□ ;	SI TA STATUS EXTENSION	APD EXTENSION			
	WILDCAT WELL DETERMINATION	1	OTHER	OTHER: Rod Part			
	completed operations. Clearly sho ng and replaced rods. See a		ned for details.	Accepted by the Utah Division of Oil, Gas and Mining FOR RECORD ONLY May 06, 2013			
NAME (PLEASE PRINT) Maria S. Gomez	PHONE NUM 713 997-5038	IBER	TITLE Principal Regulatory Analys	et			
SIGNATURE			DATE		_		
N/A			5/6/2013				

RECEIVED: May. 06, 2013

Sundry Number: 37566 API Well Number: 43013301870000

CENTRAL DIVISION

1 General

Customer Information 1.1

Company	CENTRAL DIVISION							
Representative								
Address								

1.2 **Well Information**

Well	DOYLE 1-10B3							
Project	ALTAMONT FIELD Site DOYLE 1-10B3							
Rig Name/No.	MAGNA/026	Event	LOE LAND					
Start Date	1/30/2013	End Date	2/4/2013					
Spud Date/Time	12/18/1972 UWI 010-002-S 003-W 30							
Active Datum	KB @6,048.0ft (above Mean Sea Level)							
Afe	160541/48002 / DOYLE UNIT 1-10 B3							
No./Description								

2 Summary

2.1 **Operation Summary**

Date		Γime art-End	Duratio n (hr)	Phase	Activit	Sub	OP Code	MD From (ft)	Operation
1/30/2013	6:00	7:30	1.50	PRDHEQ	46		Р		CREW TRAVEL HELD SAFETY MEETING ON RIGGING UP RIG.FILLED OUT JSA.
	7:30	9:30	2.00	PRDHEQ	18		Р		MIRU, RD HORSES HEAD WHILE PUMPING 60 BBLS DOWN CSG.
	9:30	12:30	3.00	PRDHEQ	42		Р		TOOH W/ 105-1" AND 55-7/8" RODS PARTED TOP PIN #56 7/8 @4000' (YR'10 RECONDITOINED). RIH W/ 2 1/2" OS W/ 1 5/8 INSERTAND RODS, ENGAGED FISH WORKED PUMP OFF SEAT WHILE PUMPING 70 BBLS DOWN CSG.
	12:30	15:00	2.50	PRDHEQ	18		Р		FLUSHED TBG W/70 BBLS. WHILE RIG CREW WENT TO ROD SCHOOL.
	15:00	18:00	3.00	PRDHEQ	42		Р		TOOH W/ 105-1", 114-7/8" LD 23 THRU BREAK, 253-3/4", 3-1 1/2" AND PUMP. SECURED WELL SDFN.
1/31/2013	6:00	7:30	1.50	PRDHEQ	46		Р		CREW TRAVEL HELD SAFETY MEETING ON TRIPPING RODS FILLED OUT JSA.
	7:30	8:30	1.00	PRDHEQ	24		Р		FLUSHED TBG W/ 65 BBLS.
	8:30	12:00	3.50	PRDHEQ	42		Р		PU AND PRIMED2' X 1 1/4" X28 ' PUMP RIH W/ PUMP,3 -1 1/2', WEIGHT BARS, 253-3/4", 114- 7/8",105 1" SPACEDOUT RODS W/ 2-2"X 1" RODS.
	12:00	13:30	1.50	PRDHEQ	24		Р		SEATED PUMP UMPED 100BBLS DOWN TBG NO PRESSURE.
	13:30	17:00	3.50	PRDHEQ					RU TO PULL RODS . UNSEATED PUMP. TOOH W/ 105-1", 114-7/8" AND 48-2/4 PUPOLISH ROD AND SECURED WELL SDFN.
2/1/2013									NO ACTIVITY
2/2/2013									NO ACTIVITY
2/3/2013	6:00	7:30	1.50	PRDHEQ	46		Р		CT HOLD SAFETY MTG ON POOH W/ RODS, WRITE & REVIEW JSA'S WHILE FLUSHING RODS W/ 20 BBLS 2% KCL
	7:30	9:00	1.50	PRDHEQ	42		Р		CONT POOH W/ 205 3/4" RODS, LD 3, 1-1/2" WT BARS & PUMP W/ DIP TUBE
	9:00	11:00	2.00	PRDHEQ	18		Р		C/O TO TBG EQUIP, R.D. LUFKIN P.U. NDWH, NUBOP, RU WORK FLOOR RELEASE 5" TAC @ 11878'
	11:00	14:30	3.50	PRDHEQ	18		Р		POOH W/ 330 JTS, 2-7/8" EUE N-80 TBG, 2-7/8" X 2-3/8" X OVER, 45 JTS 2-3/8" TBG, & 5" TAC COLLAR ON TOP OF TAC WAS SPLIT
	14:30	17:00	2.50	PRDHEQ	18		Р		CHANGE OUT TAC TIH W/ 45 JTS 2-3/8" TBG, X OVER, & 174 JTS 2-7/8" EUE N-80 TBG SECURE WELL SDFN

RECEIVED: May. 06, 2013

Sundry Number: 37566 API Well Number: 43013301870000

CENTRAL DIVISION

2.1 **Operation Summary (Continued)**

Date	1	Гіте	Duratio	Phase	Activit	Sub	ОР	MD From	Operation
	Start-End		n		у		Code	(ft)	
			(hr)						
2/4/2013	6:00	7:30	1.50	PRDHEQ	46		Р		CREW TRAVEL HELD SAFETY MEETING ON TRIPPING TBG.
									FILLED OUT JSA.
	7:30	10:00	2.50	PRDHEQ	16		Р		FINISHED RIH W/ 156-JTS 2 7/8 N-80 EUE TBG. SET TAC @
									11875', SN @ 12005', EOT @ 12104,
	10:00	12:00	2.00	PRDHEQ	18		Р		ND BOP, NU WELLHEAD, CHANGED OVER TO RUN RODS.
	12:00	13:00	1.00	MNTSSO	24		Р		FLUSHED TBG, W/ 60 BBLS.
	13:00	16:00	3.00	PRDHEQ	42		Р		PU AND PRIMED 2" X 1 1/4" X 28' PUMP. RIH W/ PUMP AND 3-1
									1/2" K-BARS, 252-3/4", 114-7/8", 105-1" SPACED OUT WELL
									WITH 2-2'X1" SUBS PU POLISH ROD.
	16:00	17:30	1.50	PRDHEQ	18		Р		RU PUMPING UNIT WHILE FILLING TBG W/ 50 BBLS,. PRESSURE
									AND STROKED TEST @ 1000 PSI. HELD PUTON PRODUCTION.

Sundry Number: 40296 API Well Number: 43013301870000

	STATE OF UTAH		FORM 9
	5.LEASE DESIGNATION AND SERIAL NUMBER:		
	FEE		
SUNDF	6. IF INDIAN, ALLOTTEE OR TRIBE NAME:		
Do not use this form for procurrent bottom-hole depth, FOR PERMIT TO DRILL form	7.UNIT or CA AGREEMENT NAME:		
1. TYPE OF WELL Oil Well	8. WELL NAME and NUMBER: DOYLE 1-10B3		
2. NAME OF OPERATOR: EP ENERGY E&P COMPANY,		9. API NUMBER: 43013301870000	
3. ADDRESS OF OPERATOR: 1001 Louisiana , Houston,		PHONE NUMBER: 38 Ext	9. FIELD and POOL or WILDCAT: ALTAMONT
4. LOCATION OF WELL FOOTAGES AT SURFACE: 2382 FNL 2157 FWL			COUNTY: DUCHESNE
QTR/QTR, SECTION, TOWNSH Qtr/Qtr: SENW Section:	HIP, RANGE, MERIDIAN: 10 Township: 02.0S Range: 03.0W Meric	lian: U	STATE: UTAH
11. CHEC	K APPROPRIATE BOXES TO INDICAT	E NATURE OF NOTICE, REPOR	RT, OR OTHER DATA
TYPE OF SUBMISSION		TYPE OF ACTION	
7	✓ ACIDIZE	ALTER CASING	CASING REPAIR
Approximate date work will start:	CHANGE TO PREVIOUS PLANS	CHANGE TUBING	CHANGE WELL NAME
7/22/2013	CHANGE WELL STATUS	COMMINGLE PRODUCING FORMATIONS	CONVERT WELL TYPE
SUBSEQUENT REPORT	DEEPEN	FRACTURE TREAT	NEW CONSTRUCTION
Date of Work Completion:	OPERATOR CHANGE	PLUG AND ABANDON	PLUG BACK
	PRODUCTION START OR RESUME	RECLAMATION OF WELL SITE	RECOMPLETE DIFFERENT FORMATION
SPUD REPORT Date of Spud:	REPERFORATE CURRENT FORMATION	SIDETRACK TO REPAIR WELL	TEMPORARY ABANDON
	TUBING REPAIR	VENT OR FLARE	WATER DISPOSAL
DRILLING REPORT	WATER SHUTOFF	SI TA STATUS EXTENSION	APD EXTENSION
Report Date:	WILDCAT WELL DETERMINATION	OTHER	OTHER:
12. DESCRIBE PROPOSED OR	COMPLETED OPERATIONS. Clearly show a	Il pertinent details including dates.	depths, volumes, etc.
	acidize with 7500 gals 15% H		Approved by the
	routine ops.		Utah Division of Oil, Gas and Mining
			Date: July 22, 2013
			By: Dorl K Quit
NAME (PLEASE PRINT)	PHONE NUMBE		
Maria S. Gomez	713 997-5038	Principal Regulatory Analys	şt
SIGNATURE N/A		DATE 7/22/2013	